

ASUS ESC4000 (90S6XA1000C100UET)

2 x Socket LGA1366, Intel 5520 IOH + NVIDIA NF200, 18 x DDR3 Max. 192GB RDIMM/Max. 48GB UDIMM, SATA/SAS, 8 x Hot-swap 3.5" HDD, 2 x Intel 82574L + 1 x Mgmt LAN, 2U



Price details:

Price excl. VAT: 2,842.32 €

Eco fees: 0.00 €

VAT 21 %: 596.89 €

Product details:

Product code: 90S6XA1000C100UET

EAN: 4719543381427

Manufacturer: ASUS

PDF generated on: 22 June, 2018



3,439.21 €

* VAT included

First ever high density 2U parallel computing design

Leading advanced system architecture

- Features dual all-new Intel® Xeon® 5600 series processors with Intel® Core microarchitecture for significant performance increases
- Supports 18 DIMM slots and up to 48GB/144GB high scalability memory for intense applications. DDR3 modules deliver higher speeds and more bandwidth with lower power consumption
- Embeds up to four NVIDIA® Tesla M2050/M2070/M2090 GPUs on full PCI-E Gen2 x16 slots with up to 2.66 teraflops, doubling precision performance
- The NVIDIA® Tesla M2090 GPU Computing Module is the world's fastest parallel computing processor for HPC

8+1 flexible expansion

- Eight PCI-E Gen2 x16 slot design supports up to four double-deck GPU computing cards for professional graphics
- Flex-E technology allows automatic switching between one PCI-E x16 and two PCI-E x8 links
- Additional PCI-E riser module compatible with both half-length/low-profile PCI-E cards and ASUS PIKE series cards

Intelligent system fan control

- Three independent smart system fans, two for GPU areas and one for general motherboard cooling
- Adjusts fan speed automatically according to system load to optimize cooling and energy saving

Flexible high storage capacity

- Designed with eight hard drive bays to support SAS or SATA drives
- Optional ASUS PIKE meets the various requirements of RAID functionality

High reliability

- 1600W 80PLUS Platinum power supply delivers reliable and highly efficient power
- Hot-swap hard drive design allows downtime-free drive replacement

Remote control and management

- Bundled ASMB4-iKVM module offers advanced server management
- KVM-over internet provides OS-independent manageability
- Ideal for remote office applications

Main specifications:

Processor

Motherboard chipset:

Intel 5520

Processor socket:

Socket B (LGA 1366)

Number of processors supported:

2

Processor family:	Intel
Compatible processor series:	Intel Xeon
Intel Xeon series:	X5500,X5600
System bus rate:	6.4 GT/s
Motherboard southbridge:	Intel ICH10R
Memory	
Number of DIMM slots:	18
Supported memory types:	DDR3-SDRAM
Maximum internal memory:	192 GB
Maximum UDIMM memory:	48 GB
Supported DIMM module capacities:	16GB,1GB,2GB,4GB,8GB
Storage	
Hot-swap hard drive bays:	Y
Number of storage drives supported:	8
Supported storage drive interfaces:	SAS,Serial ATA
Storage drive sizes supported:	3.5 "
Networking	
LAN controller:	Intel 82574L
Ethernet LAN data rates:	10,100,1000 Mbit/s
Ethernet LAN:	Y
Ports & interfaces	
USB 2.0 ports quantity:	4
Ethernet LAN (RJ-45) ports:	3
Serial ports quantity:	1
VGA (D-Sub) ports quantity:	1
Expansion slots	
PCI Express slots version:	1.0,2.0
Graphics	
Maximum graphics adapter memory:	8 MB
Design	
Form factor:	2U
Colour of product:	Black,Silver
Performance	
Compatible operating systems:	Windows Server 2008 R2,Windows Server 2008 Enterprise 32/64-bit,Windows Server 2003 R2 Enterprise 32/64-bit,RedHat Enterprise Linux AS5.5 32/64-bit,SuSE Linux Enterprise Server 11 32/64-bit
Power	
Power supply:	770 W
Redundant power supply (RPS) support:	Y
Number of power supply units:	2
Operational conditions	
Operating temperature (T-T):	10 - 35 °C
Storage temperature (T-T):	-40 - 70 °C
Operating relative humidity (H-H):	20 - 90 %
Weight & dimensions	
Width:	444 mm
Depth:	750 mm
Height:	88 mm
Weight:	18000 g
Other features	
Graphics adapter family:	Aspeed

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.