

ASUS TS500-E6/PS4 (90S57A0000C210UEZ)

TS500-E6/PS4 - 2 x Socket 1366, Intel 5500 IOH + Intel ICH10R, 6 x DDR3 1066/1333 Reg DIMM/ Unbuffered DIMM ECC max.48GB (RDIMM)/24GB (UDIMM), 1 x PCI-E x16 (x16 link), 2 x PCI-E x8 (x4 link), 2 x PCI 32bit/ 33MHz, 6 x SATA2 300MB/s, 2 x Intel 82574L LAN, Aspeed AST2050 8MB VGA, 470W PSU, 5U



Price details:

Price excl. VAT: 744.01 €

Eco fees: 0.00 €

VAT 21 %: 156.24 €

Product details:

Product code: 90S57A0000C210UEZ

EAN: 4719543354599

Manufacturer: ASUS

PDF generated on: 22 February, 2018



900.25 €

* VAT included

Cost-effective 45nm Ready Platform with Latest Technology

Versatile Applications

- Cost performance 2-way Intel® Xeon® processor based platform for small & medium business
- PCI-E 2.0 x16 slot is reserved for professional graphic card usage
- Optional ASUS unique MIO audio card delivers exhilarating surround sound for professional and entertainment usage

Expandable for Growing Business

- Support up to four SAS/SATA HDDs for storage demanding applications
- Hot-swap storage bay design makes online expansion easy

Quiet & Power-saving

- Adopt 80+ high efficiency power supply to reduce power loss
- Support of DDR3 memory provides higher transfer speed and lower power consumption
- Intelligent fan technology provides low acoustic and effective system cooling solution

Wide Memory Choices

6-DIMM slots support latest DDR3 1333/1066 Reg./Unbuffered ECC memory modules

ASUS PIKE Technology & Flexible I/O Expansion

- ASUS optional PIKE offers direct upgradability to support SAS storage for better I/O performance
- Provides more total RAID solution without additional effort for verification

Main specifications:

Processor

Motherboard chipset: Intel 5500
Processor socket: Socket B (LGA 1366)

Memory

Number of DIMM slots: 6
ECC: Y

Storage

Number of hard drives supported: 6
Controller interface type: Intel ICH10R
RAID levels: 0,1

Networking

LAN controller:	Intel 82574L
Ports & interfaces	
USB 2.0 ports quantity:	4
Ethernet LAN (RJ-45) ports:	2
PS/2 ports quantity:	2
Serial ports quantity:	1
VGA (D-Sub) ports quantity:	1
Expansion slots	
PCI slots:	2
PCI Express x16 slots:	1
PCI Express x8 slots:	2
Graphics	
Maximum graphics adapter memory:	8 MB
Performance	
Compatible operating systems:	- Windows Server 2008 Enterprise 32/64-bit,- Windows Server 2003 R2 Enterprise (32/64 bit),- RedHat Enterprise Linux AS5.0 (32/64 bit),- SuSE Linux Enterprise Server 10 (32/64 bit)
Power	
Power supply:	470 W
Operational conditions	
Operating temperature (T-T):	10 - 35 °C
Storage temperature (T-T):	-40 - 70 °C
Operating relative humidity (H-H):	20 - 90 %
Weight & dimensions	
Width:	217.5 mm
Depth:	545 mm
Height:	445 mm
Weight:	17000 g
Packaging content	
Bundled software:	ASWM2.0
Other features	
Expansion slots:	1 x PIKE, 1 x MIO
Drive bays:	4 x Hot-swap 3.5" HDD

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.