

ASUS TS100-E7/PI4 (90S6JA0000C300UET)

1 x Socket LGA1155, Intel C202 Chipset, 4 x Internal 3.5", 300W



Price details:

Price excl. VAT: 418.43 €

Eco fees: 0.00 €

VAT 21 %: 87.87 €

Product details:

Product code: 90S6JA0000C300UET

EAN: 4716659347927

Manufacturer: ASUS

PDF generated on: 20 October, 2017



506.30 €

* VAT included

Super-quiet and energy saving UP server with dual Intel® LAN for SMB applications

The TS100-E7/PI4 is a single-socket pedestal server system based on quad/dual-core Intel® E3-1200/Core™ i3-2100 series processors and the Intel® C202PCH chipset with support for up to 32GB of DDR3 1333Hz unbuffered ECC memory. Upscaled performance increases processing speeds, while the super-quiet design makes the TS100-E7/PI4 ideal for professional environments where noise reduction is important.

Super-quiet UP server with dual Intel® LAN for SMB applications

The latest Intel® CPUs

The TS100-E7/PI4 is ready for new-generation Intel® Xeon® 32nm quad/dual-core UP processors, which deliver a significant performance improvement (up to 25%) over previous generation CPUs. Also, with Intel® Turbo Boost Technology 2.0, the TS100-E7/PI4 provides more efficient, dynamic, and intelligent performance enhancement on demand.

Ultra-quiet and energy-saving

Strict acoustic testing has shown that the TS100-E7/PI4 performs excellently in noise control at less than 25.6dBA when idle - even lower than the noise output of a projector (42dB). It facilitates quiet working environments, and ships with an 80+ power supply to reduce power loss and power consumption, helping consumers save on energy bills.

Dual Intel® server-class Gigabit LAN

The TS100-E7/PI4 offers more reliable networking and wide-range virtualization, including VMWare®, Hyper-V and Xen. IPv6 readiness effortlessly resolves potential IPv4 address shortage problems even before they occur.

Optional ASUS TPM module

With the ASUS TPM module supporting TXT technology, the TS100-E7/PI4 avoids Trojan and malware incursions, while Hypervisor loads on start-up to provide hardware-level security against software attacks, protecting data from memory snooping.

Effortless install

Auto-setup in a few simple steps and the intuitive support CD mean users don't need to go through a lengthy process as the install is pre-configured, and all device drivers arrive fully installed with the latest versions, saving IT staff time and effort.

Main specifications:

Processor

Processor socket:	LGA 1155 (Socket H2)
Processor family:	Intel
Compatible processor series:	Celeron,Core i3,Pentium,Xeon

Memory

Number of DIMM slots:	4
-----------------------	---

Supported memory types:	DDR3-SDRAM
Maximum UDIMM memory:	32 GB
Supported UDIMM clock speeds:	1066,1333,1600 MHz
Storage	
Number of hard drives supported:	4
RAID levels:	1,5,10
Supported hard disk drive sizes:	3.5 "
Supported storage drive interfaces:	Serial ATA II
Networking	
Networking features:	2 x Intel 82574L
Ports & interfaces	
USB 2.0 ports quantity:	4
Ethernet LAN (RJ-45) ports:	2
PS/2 ports quantity:	2
Serial ports quantity:	1
VGA (D-Sub) ports quantity:	1
Expansion slots	
PCI Express x1 slots:	2
PCI Express x16 slots:	1
PCI Express x8 slots:	1
Design	
Colour of product:	Black,Silver
Performance	
Compatible operating systems:	Windows Server 2008 R2 Windows Server 2008 Enterprise 32/64-bit Windows Server 2003 R2 Enterprise 32/64-bit RedHat Enterprise Linux AS5.5 32/64-bit SuSE Linux Enterprise Server 10 32/64-bit SuSE Linux Enterprise Server 11 32/64-bit
Power	
Power supply:	300 W
Operational conditions	
Operating temperature (T-T):	10 - 35 °C
Storage temperature (T-T):	-40 - 70 °C
Operating relative humidity (H-H):	20 - 90 %
Safety:	CE, EN55022
Weight & dimensions	
Width:	436.8 mm
Depth:	478.8 mm
Height:	200 mm
Weight:	15000 g

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.