


ASUS ASMB4-iKVM remote management adapter (90-C1SD80-00UAN2YZ)

IPMI 2.0 Management Upgrade Kit with KVM (Keyboard, Video, Mouse) /SOL over LAN



Price details:

Price excl. VAT: 25.96 €

Eco fees: 0.00 €

VAT 21 %: 5.45 €

Product details:

Product code: 90-C1SD80-00UAN2YZ

EAN: 4719543041901

Manufacturer: ASUS

PDF generated on: 20 November, 2017



31.41 €

* VAT included

ASUS ASMB4-iKVM is an effective remote server management chip that is IPMI 2.0 compliant and provides the OS-independent and cross-platform interface for monitoring the server system such as temperature, voltage, and Fan status etc. MIS can be informed of the server working status from anywhere, anytime via real-time event notification.

With simple steps, MIS is able to control servers by functions keys and remote server screen to accomplish KVM (Keyboard, Video, Mouse) over LAN, which is based on BIOS-level access and keeps working to provide around-the-clock remote monitor and diagnosis through GUI (Web-based Graphical User Interface) even the server OS is down. Before watchdog resets, ASMB4-iKVM will capture the screen automatically.

Full Control Server Through ASUS Web GUI

Remote Server Screen

The ASMB4 iKVM module offers advanced server management functions including "remote OS installation", "remote power on/off/reset", "remote control via SOL" (Serial-over-LAN), "remote hardware health monitoring" and "system event log". Through the enhanced data encryption (in Advanced Encryption Standard), the internet security can be protected.

Remote Power Control

KVM over LAN allows administrators to share the data saved in a local drive (floppy, CD/DVD-ROM and flash device) to target servers, which provide a way for easy maintenance. At the same time, the KVM function also enables faster troubleshooting than before by fixing server problems from wherever you are and therefore reduces system downtime and operation cost. With ASMB4-iKVM, MIS has the most quick and efficient way to recover the system in service and improve the system's availability significantly by the complete remote management tools.

Main specifications:

Technical details

Chipset: Aspeed 2050
Form factor: 22 mm x 17 mm

Memory

RAM capacity: 57344 KB
ROM capacity: 16 MB
Video RAM: 8 MB

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.