

Aten CE775 AV extender (CE775)

USB KVM Extender, Dual view with Deskew



Price details:

Price excl. VAT: 741.03 €

Eco fees: 0.04 €

VAT 21 %: 155.62 €

Product details:

Product code: CE775

EAN: 4710423778511

Manufacturer: Aten

PDF generated on: 22 November, 2017



896.69 €

* VAT included

ATEN CE775 Dual View KVM Extenders with Deskew function allows access to a computer system from a remote Dual View console up to 300 m away. The dual view function provides support for two displays, allowing the video output to seamlessly display on two monitors. Its advanced PC Wake - Up feature that allows you simply uses a pushbutton from the remote dual view console to wake a PC at the local site via RS-232, no need to go to the local site to wake up the PC. It eliminates the need for traveling back and forth between the local computer and remote console, efficient and flexible.

Use the improved built-in front panel tuners to easily adjust the picture quality. In addition, you can automatically synchronize the time delay of RGB signals in order to compensate for distance, easy and fast than ever.

- Dual View Support - connect two screens to transmit two video output signals to a remote site up to 300 m away using inexpensive Cat 5e/6 cables
- Dual Console operation - control your system from both the local and remote USB keyboard, monitor, and mouse consoles
- Deskew Function - automatically synchronizes the time delay of RGB signals to compensate for distance
- PC Wakeup support - from the remote console, simply use a pushbutton to wake a computer at the local site via RS-232
- Superior video quality - 1920x1200@60Hz(150 m), 1280x1024@60Hz(300 m)
- Gain/Compensation Control - adjusts signal strength in order to compensate for distance
- On Screen Display - conveniently adjust video quality with the intuitive OSD menu system
- RS-232 Channel - allow you to connect to a serial terminal, or serial devices such as touchscreens and barcode scanners
- Built-in 8KV/15KV ESD protection (Contact voltage 8KV; Air voltage 15KV)
- Sun/Mac keyboard support and emulation *

* 1. PC keyboard combinations emulate Sun/Mac keyboards

2. Sun/Mac keyboards only work with their own computers

Main specifications:

Technical details

Type:	AV transmitter & receiver
Maximum resolution:	1920 x 1200 pixels
Cable types supported:	Cat5e
Maximum transfer distance:	300 m
Audio system:	Multichannel
Connector type:	USB, SPHD-17, RS-232
Colour of product:	Black

Ports & interfaces

RJ-45 input ports:	2
RJ-45 output ports:	2

VGA (D-Sub) input ports:	4
Audio input:	3.5mm
Audio output:	3.5mm
DC-in jack:	Y
Indication	
LED indicators:	Y
Operational conditions	
Operating temperature (T-T):	0 - 50 °C
Storage temperature (T-T):	-20 - 60 °C
Operating relative humidity (H-H):	0 - 80 %
Power	
Operating voltage:	5.3 V
External power adapter:	Y
Weight & dimensions	
Dimensions (WxDxH):	75.8 x 200 x 42 mm
Weight:	690 g

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.