

# Cisco Unified IP Phone 7945G w/ 1 CCME User License (CP-7945G-CCME)

Unified IP Phone 7945G w/ 1 CCME User License



## Price details:

Price excl. VAT: 443.74 €

Eco fees: 0.04 €

VAT 21 %: 93.19 €

## Product details:

Product code: CP-7945G-CCME

EAN: 0882658140426

Manufacturer: Cisco

PDF generated on: 15 December, 2018



**536.97 €**

\* VAT included

The Cisco Unified IP Phone 7945G demonstrates the latest advances in VoIP telephony, including wideband audio support, backlit color display, and an integrated Gigabit Ethernet port. It addresses the needs of transaction-type workers with significant phone traffic and the needs of those working with bandwidth-intensive applications on co-located PCs. This IP phone includes a large, backlit, easy-to-read color display for easy access to communication information, timesaving applications, and features such as date and time, calling party name, calling party number, digits dialed, and presence information. It also accommodates Extensible Markup Language (XML) applications that take advantage of the display. The phone provides direct access to two telephone lines (or combination of lines, speed dials, and direct access to telephony features), four interactive soft keys that guide you through call features and functions, and an intuitive four-way (plus Select key) navigation cluster. A hands-free speakerphone and headset designed for high-fidelity wideband audio are standard, as is a built-in headset connection.

## Main specifications:

### Design

Colour of product: Grey

### Phone features

Speakerphone: Y

Dialer location: base

### Call management

Caller ID: Y

Conference call: Y

Call forwarding: Y

Call waiting: Y

Explicit call transfer: Y

### Management features

Volume control: Digital

### Display

Display: LCD

Display resolution: 320 x 240 pixels

Display number of colours: 65536 colours

### Ports & interfaces

Wireless connection: N

Headset connectivity: Y

### Weight & dimensions

Weight: 1600 g

### Other features

Voice codecs:	G.711a,G.722,G.729a,iLBC
VoIP protocols:	SCCP, SIP
Mac compatibility:	N
Dimensions (WxDxH):	267 x 152 x 203 mm
Networking features:	IEEE 802.1Q (VLAN), IEEE 802.1p, PoE; ECN
Wall mountable:	Y
Supported network protocols:	DHCP, TFTP
I/O ports:	2 x Ethernet 10/100Base-TX/1000Base-T

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.