

Cisco Unified IP Phone 7945G (CP-7945G=)

Unified IP Phone 7945G



Price details:

Price excl. VAT: 391.55 €

Eco fees: 0.00 €

VAT 21 %: 82.23 €

Product details:

Product code: CP-7945G=

EAN: 0882658140358

Manufacturer: Cisco

473.78 €

* VAT included

PDF generated on: 15 December, 2018



The Cisco Unified IP Phone 7945G demonstrates the latest advances in VoIP telephony, including wideband audio support, backlit color display, and an integrated Gigabit Ethernet port. It addresses the needs of transaction-type workers with significant phone traffic and the needs of those working with bandwidth-intensive applications on co-located PCs. This IP phone includes a large, backlit, easy-to-read color display for easy access to communication information, timesaving applications, and features such as date and time, calling party name, calling party number, digits dialed, and presence information. It also accommodates Extensible Markup Language (XML) applications that take advantage of the display. The phone provides direct access to two telephone lines (or combination of lines, speed dials, and direct access to telephony features), four interactive soft keys that guide you through call features and functions, and an intuitive four-way (plus Select key) navigation cluster. A hands-free speakerphone and handset designed for high-fidelity wideband audio are standard, as is a built-in headset connection.

Main specifications:

Performance

Answering machine: N

Design

Mounting type: Wall

Product colour: Grey

Phone features

Speakerphone: Y

Dialer location: base

Multi handset capability: 1

Call management

Caller ID: Y

Conference call: Y

Call forwarding: Y

Call waiting: Y

Explicit call transfer: Y

Management features

Volume control: Digital

Display

Built-in display: Y

Display: TFT

Display resolution: 320 x 240 pixels

Display number of colours: 65536 colours

Ports & interfaces

Wireless connection: N

Headset connectivity: Y

Operational conditions

Operating temperature (T-T):	0 - 40 °C
Storage temperature (T-T):	-10 - 60 °C
Operating relative humidity (H-H):	10 - 95 %
Certificates	
Energy Star certified:	N
Weight & dimensions	
Weight:	1600 g
Other features	
Voice codecs:	G.711a,G.722,G.729a,iLBC
VoIP protocols:	SCCP, SIP
Mac compatibility:	N
Dimensions (WxDxH):	267 x 152 x 203 mm
Wall mountable:	Y
Cabling technology:	10/100/1000 BASE-T
Supported network protocols:	DHCP, TFTP
Security algorithms:	128-bit AES
Networking standards:	IEEE 802.1p,IEEE 802.1Q,IEEE 802.1x,IEEE 802.3af
Ethernet LAN (RJ-45) ports:	2
Power over Ethernet (PoE):	Y

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.