

Cisco 7965G IP phone (CP-7965G-CCME)

CP-7965G-CCME, Unified IP Phone 7965G, 1 x CUCME station user license



Price details:

Price excl. VAT: 532.53 €

Eco fees: 0.00 €

VAT 21 %: 111.83 €

Product details:

Product code: CP-7965G-CCME

EAN: 0882658140419

Manufacturer: Cisco

PDF generated on: 13 December, 2018



644.36 €

* VAT included

The Cisco Unified IP Phone 7965G demonstrates the latest advances in VoIP telephony, including wideband audio support, backlit color display, and an integrated Gigabit Ethernet port. It addresses the needs of the executive or major decision maker, administrative assistants, and those working with bandwidth-intensive applications on collocated PCs. This IP phone includes a large, backlit, easy-to-read color display for easy access to communication information, timesaving applications, and features such as date and time, calling party name, calling party number, digits dialed, and presence information. It also accommodates Extensible Markup Language (XML) applications that take advantage of the display. The phone provides direct access to six telephone lines (or combination of lines, speed dials, and direct access to telephony features), four interactive soft keys that guide you through call features and functions, and an intuitive four-way (plus Select key) navigation cluster. A hands-free speakerphone and handset designed for high-fidelity wideband audio are standard, as is a built-in headset connection.

Main specifications:

Features

Colour of product: Grey

Keypad number of keys: 12

Display

Touchscreen: N

Display resolution: 320 x 240 pixels

Display diagonal: 5 "

Phone features

Speed dialing: Y

Audio

Speakerphone: Y

Microphone mute: Y

Voice codecs: G.711a,G.722,G.729a,iLBC

Networking

Ethernet LAN: Y

Supported network protocols: LDAP3, DHCP, TFTP, SCCP, SIP

Quality of Service (QoS) support: Y

DHCP client: Y

Ports & interfaces

Ethernet LAN (RJ-45) ports: 2

Power

Power over Ethernet (PoE): Y

Security

Security algorithms: WPA-AES

Weight & dimensions

Weight:	1600 g
Certificates	
Compliance industry standards:	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.1Q/p, IEEE 802.3af
Operational conditions	
Operating temperature (T-T):	0 - 40 °C
Operating relative humidity (H-H):	10 - 95 %
Storage temperature (T-T):	-10 - 60 °C
System requirements	
Minimum system requirements:	CUCME
Other features	
Dimensions (WxDxH):	266.7 x 152.4 x 203.2 mm
Input voltage:	48 V

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.