

# Cisco SPA 303 IP phone (SPA303-G2)

SPA 303 3-Line IP Phone, Europe power adapter, 128 x 64 monochrome LCD, Grey



### Price details:

Price excl. VAT: 57.17 €

Eco fees: 0.04 €

VAT 21 %: 12.01 €

### Product details:

Product code: SPA303-G2

EAN: 0882658345364

Manufacturer: Cisco

**69.22 €**

\* VAT included

PDF generated on: 12 December, 2018



### Highlights

- 3-line business-class IP phone
- Connects directly to an Internet telephone service provider or to an IP private branch exchange (PBX)
- Dual switched Ethernet ports, speakerphone, caller ID, call hold, conferencing, and more
- Easy installation and highly secure remote provisioning, as well as menu-based and web-based configuration
- Supports both Session Initiation Protocol (SIP) and Smart Phone Control Protocol (SPCP) with the Cisco Unified Communications 500 Series

### Main specifications:

#### Features

Product colour: Grey  
Keypad number of keys: 12

#### Display

Display resolution: 128 x 64 pixels

#### Phone features

Lines quantity: 3 lines  
Caller ID: Y  
Phonebook capacity: 60 entries  
Call waiting: Y  
Distinctive ring: Y  
Speed dialing: Y  
Intercom: Y  
Call hold: Y  
Call forwarding: Y  
Conference call: Y  
Redialing: Y  
Do not disturb function: N  
On-hook dialing: Y

#### Audio

Speakerphone: Y  
Microphone mute: Y  
Voice codecs: G.711,G.722  
Voice activity detection: Y  
Adaptive jitter buffers: Y

#### Networking

Ethernet LAN: Y  
Supported network protocols: IPv4 (RFC 791), ARP, DNS (RFC 1706), SRV (RFC 2782), DHCP (RFC 2131), ICMP (RFC 792), TCP (RFC 793), UDP (RFC 768), RTP (RFC 1889, 1890), RTCP (RFC 1889), RTCP-XR (RFC 3611), DiffServ (RFC

	2475), ToS (RFC 791, 1349), SNTP (RFC 2030)
Quality of Service (QoS) support:	Y
DHCP client:	Y
<b>Ports &amp; interfaces</b>	
Ethernet LAN (RJ-45) ports:	2
RJ-9 ports quantity:	1
Headphone outputs:	1
DC-in jack:	Y
Microphone in:	Y
<b>Power</b>	
Power over Ethernet (PoE):	N
Suitable for use in country/location:	Europe
<b>Weight &amp; dimensions</b>	
Weight:	680 g
<b>Certificates</b>	
Certification:	FCC (15, B), UL, CE, A-Tick
Compliance industry standards:	IEEE 802.1p/Q, IEEE 802.3
<b>Operational conditions</b>	
Operating temperature (T-T):	0 - 40 °C
Operating relative humidity (H-H):	5 - 95 %
Storage relative humidity (H-H):	5 - 95 %
Storage temperature (T-T):	-20 - 70 °C
<b>Other features</b>	
Dimensions (WxDxH):	220 x 30 x 198 mm
Input voltage:	100 - 240 V

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.