

Cisco 7945G IP phone (CP-7945G-RF)

12.7 cm (5 ") TFT, 2 lines, Gigabit Ethernet, 2x RJ-45



Price details:

Price excl. VAT: 225.58 €

Eco fees: 0.04 €

VAT 21 %: 47.38 €

Product details:

Product code: CP-7945G-RF

EAN: 0882658258152

Manufacturer: Cisco

273.00 €

* VAT included

PDF generated on: 19 June, 2018



Product Overview

Cisco Unified Communications Solutions unify voice, video, data, and mobile applications on fixed and mobile networks, delivering a media-rich collaboration experience across business, government agency, and institutional workspaces. These applications use the network as the platform to enhance comparative advantage by accelerating decision time and reducing transaction time. The security, resilience, and scalability of the network enable users in any workspace to easily connect anywhere, anytime, and anyplace, using any media, device or operating system. Cisco Unified Communications is part of a comprehensive solution that includes network infrastructure, security, wireless, management applications, lifecycle services, flexible deployment and outsourced management options, and third-party applications.

The Cisco Unified IP Phone 7945G demonstrates the latest advances in VoIP telephony, including wideband audio support, backlit color display, and an integrated Gigabit Ethernet port. It addresses the needs of transaction-type workers with significant phone traffic and the needs of those working with bandwidth-intensive applications on colocated PCs. This IP phone includes a large, backlit, easy-to-read color display (Figure 2) for easy access to communication information, timesaving applications, and features such as date and time, calling party name, calling party number, digits dialed, and presence information. It also accommodates Extensible Markup Language (XML) applications that take advantage of the display. The phone provides direct access to two telephone lines (or combination of lines, speed dials, and direct access to telephony features), four interactive soft keys that guide you through call features and functions, and an intuitive four-way (plus Select key) navigation cluster. A hands-free speakerphone and headset designed for high-fidelity wideband audio are standard, as is a built-in headset connection.

Features and Benefits

The Cisco Unified IP Phone 7945G is designed to grow with your organization and enhancements to your system capabilities. The dynamic feature set allows the phone to keep pace with your requirements through regular software updates. Firmware changes can be downloaded from Cisco.com. No hands-on moves and changes are required with the phone-you can simply pick up the phone and move to a new location anywhere on your network. The Cisco Unified IP Phone 7945G also provides many accessibility features. Table 1 lists the phone's features.

Display: 5-inch (12.5 cm) graphical TFT color display, 16-bit color depth, 320 x 240 effective pixel resolution, with backlight. Allows for greater flexibility of features and applications, and significantly expands the information viewed when using features such as Services, Information, Messages, and Directory. Display also supports localization requiring double-byte Unicode encoding for fonts.

Wideband Audio: Support for wideband (G.722 codec, adherence to TIA 920), including handset, headset, and speakerphone (see Q&A for details).

Codec Support: G.711a, G.711µ, G.729a, G.729ab, G.722, and iLBC audio compression codecs are supported (see Q&A for details).

Speakerphone: Full-duplex speakerphone with acoustic echo cancellation.

Messages Key: Provides direct access to voicemail.

Directories Key: Ready access to missed, received or placed calls (plus intercom history and directories). Incoming messages are identified and categorized on the display, allowing users to quickly and effectively return calls using direct dial-back capability. Corporate directory integrates with the Lightweight Directory Access Protocol Version 3 (LDAP3) standard directory.

Settings Key: Allows user to adjust display brightness, select background images (if available), and select ringer sounds through the User Preference menu. Network Configuration preferences also can be set up (usually by the system administrator). Configuration can be set up either automatically or manually for Dynamic Host Control Protocol (DHCP), Trivial File Transfer Protocol (TFTP), Cisco Unified Communications Manager, and backup Cisco Unified Communications Manager instances. Other available Settings submenus include Device Configuration, Security

Configuration, and Model Information.

Services Key: Allows users to quickly access diverse information such as weather, stocks, quote of the day, or any Web-based information using XML.

Help Button: Online Help gives users information about the phone keys, buttons, and features.

Speakerphone, Mute, and Headset Buttons: Speakerphone includes Speaker On/Off, Microphone Mute, and Headset buttons that are lit when active. For added security, the audible dual tone multifrequency (DTMF) tones are masked when the speakerphone mode is used.

Navigation Cluster with `Select' Button: Four-way navigation cluster allows users to scroll vertically and horizontally. At the center of the cluster is a `Select' button that can be used for selection of an in-focus item (for example, to open an underlying menu).

Display Button: Indicates when phone is in power-saving sleep/inactivity mode (button is lit), and can be used to awaken the display. Inactivity period is configured by the system administrator.

Ethernet Switch: Internal 2-port Cisco Ethernet switch allows for a direct connection to a 10/100/1000 BASE-T Ethernet network through an RJ-45 interface with single LAN connectivity for both the phone and a collocated PC. System administrator can designate separate VLANs (802.1Q) for the PC and phone, providing improved security and reliability of voice and data traffic.

Headset Port: Dedicated headset port eliminates the need for a separate headset amplifier and allows the handset to remain in its cradle, making headset use simpler. Both wideband (G.722) and narrowband headsets are supported.

Volume Control: Provides easy decibel-level adjustments for the speakerphone, handset, headset, and ringer. The handset is hearing aid-compatible. Additional volume control gain can be achieved using an inline headset amplifier.

Adjustable Foot-Stand: Stand is adjustable from flat to 60 degrees to provide optimum display viewing and comfortable use of all buttons and keys. The foot-stand is keyed to match standard wall-jack configurations for wall mounting. Optional wall-mount brackets are also offered.

Multiple Ring Tones: More than 24 defined user-selectable ring tones are available. Ring tones may also be personalized through use of the Cisco Unified Phone Application Suite.

Americans with Disabilities Act (ADA) Features: Handset is hearing aid-compatible and meets Federal Communications Commission (FCC) loudness requirements for the Americans with Disabilities Act (ADA). Section 508 loudness requirements can be achieved using industry-standard inline headset amplifiers such as Walker Equipment W-10 or CE-100 amplifiers. Dial pad is also ADA-compliant.

Quality of Service (QoS) Options: Supports differentiated services code point (DSCP) and 802.1Q/p standards.

Security: Positive device identity through X.509v3 Certificates, digitally signed images, cryptographically secure provisioning, and secure signaling and secure media with AES-128. Cryptography is not enabled by default and may only be enabled through a cryptographically enabled CUCM. The phone also contains an 802.1X supplicant and supports EAPOL pass-through.

Language Support: Built-in support for more than 30 languages (dependent on Cisco Unified Communications Manager version).

Configuration Options: IP address assignment can be statically configured or configured through the DHCP client.

Main specifications:

Technical details

Handset type:	Wired handset
Speakerphone:	Y
Ethernet cable:	Y
Volume control:	Digital
Integrated voicemail:	Y

Display

Touchscreen:	N
Display:	TFT
Display resolution:	320 x 240 pixels
Aspect ratio:	4:3
Display diagonal:	5 "
Backlight display:	Y

Phone features

Speed dialing:	Y
Conference call:	Y

Camera

Built-in camera:	N
------------------	---

Security

Security algorithms:	128-bit AES
----------------------	-------------

Ports & interfaces

Ethernet LAN (RJ-45) ports:	2
-----------------------------	---

Power

Power over Ethernet (PoE):	Y
Weight & dimensions	
Width:	266.7 mm
Depth:	152.4 mm
Height:	203.2 mm
Weight:	1600 g
Operational conditions	
Operating temperature (T-T):	0 - 40 °C
Operating relative humidity (H-H):	10 - 95 %
Storage temperature (T-T):	-10 - 60 °C
Colour	
Colour of product:	Grey,Silver
Packaging content	
Number of handles included:	1 pc(s)

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.