

Cisco 9951 IP phone (CP-9951-W-CAM-K9=)

IP Phone 9951, Bluetooth, Radio & 2 USB, TFT 24-bit, 10/100/1000Base-T Ethernet, Standard Handset, White



Price details:

Price excl. VAT: 688.04 €

Eco fees: 0.04 €

VAT 21 %: 144.50 €

Product details:

Product code: CP-9951-W-CAM-K9=

EAN: 0882658344633

Manufacturer: Cisco

PDF generated on: 10 December, 2018



832.58 €

* VAT included

Product Overview

The Cisco Unified IP Phone 9951 is an advanced collaborative media endpoint that provides voice, video, applications, and accessories. Highlights include interactive video with support from the Cisco Unified Video Camera, High-definition (HD) voice, a high-resolution color display, Gigabit Ethernet and a new ergonomic design and user interface designed for simplicity and high usability. Accessories, sold separately, include a color Cisco Unified IP Color Key Expansion Module and the Cisco Unified Video Camera.

Features and Benefits

Key features of the Cisco Unified IP Phone 9951 include:

- Newly developed ergonomic design and user experience designed for use with the VGA display
- H.264 video support for multiparty standard-definition (SD) calling with USB support for the Cisco Unified Video Camera (Note: multiparty video communications supported with addition of a Multipoint Control Unit).
- Gigabit Ethernet network connectivity and switch port available for a downstream multimedia PC.
- Embedded Bluetooth radio and 2 USB ports support accessories for added freedom and convenience. Initial support for both wired and wireless headsets.
- Firmware support for XML and MIDlet-enabled applications.

Main specifications:

Technical details

Speakerphone:	Y
Expansion module support:	Y
Keypad number of keys:	12

Display

Display resolution:	640 x 480 pixels
Display diagonal:	5 "

Phone features

Lines quantity:	5 lines
Caller ID:	Y
Phonebook capacity:	200 entries
Call waiting:	Y
Distinctive ring:	Y
Speed dialing:	Y
Intercom:	Y

Call hold:	Y
Call forwarding:	Y
Conference call:	Y
Redialing:	Y
Audio	
Voice codecs:	G.711a,G.722,G.729a
Video	
Video codecs:	H.264/AVC
Video capturing speed:	30 fps
Video capture resolution (max):	640 x 480 pixels
Networking	
Ethernet LAN:	Y
Bluetooth:	Y
Supported network protocols:	DHCP, TFTP, DNS, SRTP, TLS, CAPF
Quality of Service (QoS) support:	Y
DHCP client:	Y
Ports & interfaces	
Ethernet LAN (RJ-45) ports:	2
USB 2.0 ports quantity:	2
RJ-9 ports quantity:	1
Power	
Power over Ethernet (PoE):	Y
Weight & dimensions	
Weight:	1620 g
Handset weight:	170 g
Package weight:	2074 g
Certificates	
Compliance industry standards:	IEEE 802.3af, 802.3at, IEEE 802.1Q
Operational conditions	
Operating temperature (T-T):	-5 - 55 °C
Operating relative humidity (H-H):	5 - 90 %
Storage relative humidity (H-H):	5 - 90 %
Storage temperature (T-T):	-25 - 70 °C
Microphone	
Microphone mute:	Y
Colour	
Colour of product:	White
Other features	
Dimensions (WxDxH):	262.5 x 39.7 x 234 mm

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.