

Cisco ISM-VPN-29= VPN security equipment (ISM-VPN-29=)

550 Mbps, ISM, DES/3DES, 20W, Spare



Price details:

Price excl. VAT: 2,146.86 €

Eco fees: 0.00 €

VAT 21 %: 450.84 €

Product details:

Product code: ISM-VPN-29=

EAN: 0882658362323

Manufacturer: Cisco

2,597.70 €

* VAT included

PDF generated on: 18 June, 2018



The Cisco 2900 Series Module (ISM-VPN-29) can provide hardware-based IPsec encryption services of 145 and 550 Mbps in the Cisco 2901, 150 and 600 Mbps in the Cisco 2911, 220 and 700 Mbps in the Cisco 2921, and 385 and 900 Mbps in the Cisco 2951 (IPsec IMIX and 1400-byte packets).

The Cisco ® VPN Internal Service Module (VPN ISM) is a module for the Cisco Integrated Services Routers Generation 2 (ISR G2) that provides the capability to considerably increase performance for VPN encrypted traffic. The module has a multicore processor that operates independently of the host router resources, helping ensure maximum concurrent encrypted application performance while maintaining competitive performance for other types of traffic. The Cisco VPN ISM supports the latest versions of cryptography standards, including stronger National Security Agency (NSA) regulated cryptographic algorithms such as Suite B Cryptography.

The Cisco VPN ISM is ready to use, allowing quick and easy installation of the module for increasing VPN encryption performance on Cisco ISR G2 routers. The VPN ISM is compatible with all Cisco ISR G2 routers that support the ISM card slot and runs the same level of feature-rich functions as found on the Cisco ISR G2. It integrates all elements necessary to optimize branch-office IT infrastructure for delivery of encrypted application data from the data center and deployment of branch-office applications on demand, and houses them under a single chassis - the Cisco ISR G2.

Main specifications:

Weight & dimensions

Weight: 206 g
Dimensions (WxDxH): 102 x 155 x 22 mm

Networking

Authentication method: RSA, ECDSA, AES, GMAC
Security algorithms: 3DES, AES, DES, IPSEC, MD5, RSA, SHA-1

Certificates

Certification: UL 60950-1, CAN/CSA-C22.2 No. 60950-1-03, IEC 60950-1:3, EN 60950-1:2001, AS/NZS 60950-1, CFR, CISPR22, EN300386, EN55022, ICES, VCCI, CISPR24, EN300386, EN55024, EN61000-6-1

Operational conditions

Operating relative humidity (H-H): 10 - 95 %
Operating temperature (T-T): 0 - 50 °C
Storage temperature (T-T): -25 - 65 °C
Storage relative humidity (H-H): 9 - 95 %

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.