

## Cisco UCS B230 M2 server (UCS-EZ-B230-EX512)

Server Blade, 2-way, 2 x Xeon E7-2870, 2.4 GHz, RAM 512 GB, SATA, 6.35 cm (2.5 ") , 32x 16GB, no HDD, 10 Gigabit Ethernet



### Price details:

Price excl. VAT: 15,715.81 €

Eco fees: 0.08 €

VAT 21 %: 3,300.34 €

### Product details:

Product code: UCS-EZ-B230-EX512

EAN: 0882658534263

Manufacturer: Cisco

PDF generated on: 13 December, 2017



# 19,016.23 €

\* VAT included

### High Performance Efficiency, Compact Size

The Cisco UCS B230 M2 Blade Server extends the capabilities of the Cisco Unified Computing System and delivers new levels of performance, efficiency, and reliability. With the Intel Xeon processor E7-2800 product family, the 2-socket Cisco UCS B230 M2 Blade Server platform delivers high performance and density in a compact, half-width form factor.

### Obtain Adaptability and Advanced Reliability

#### The B230 M2 offers:

- Intel Xeon® processor E7-2800 product family
- Enhanced memory capacity and bandwidth to support your virtualized environment
- Advanced reliability features for mission-critical workloads

In addition, the B230 M2 provides one dual-port mezzanine card for up to 20 Gbps I/O per blade. Options include a Cisco UCS M81KR Virtual Interface Card or converged network adapter (Emulex or QLogic compatible). Other features include:

- 32 dual in-line memory module (DIMM) slots
- Up to 512GB memory at 1066 MHz, based on Samsung 40-nanometer class (DDR3) technology
- Two optional front-accessible, hot-swappable solid-state drives (SSDs) and an LSI SAS2108 RAID Controller
- Simplified deployment and systems management, embedded integration into Cisco UCS Manager

### Main specifications:

#### Processor

Processor frequency:	2.4 GHz
Processor family:	Intel Xeon E7
Processor model:	E7-2870
Processor cores:	10
Number of processors installed:	2
Processor cache type:	Smart Cache
Processor cache:	30 MB
System bus rate:	6.4 GT/s
Processor socket:	LGA 1567 (Socket LS)
Processor boost frequency:	2.8 GHz
Processor lithography:	32 nm
Processor threads:	20
Processor operating modes:	64-bit
Stepping:	A2
FSB Parity:	N
Bus type:	QPI

Processor codename: Westmere EX  
Tcase: 69 °C  
Maximum internal memory supported by processor: 16 GB  
Memory types supported by processor: DDR3-SDRAM  
Memory clock speeds supported by processor: 800,978,1066,1333 MHz  
Memory channels supported by processor: Quad  
ECC supported by processor: Y  
Execute Disable Bit: Y  
Thermal Monitoring Technologies: Y  
Processor package size: 49.17 mm  
Supported instruction sets: SSE4.1,SSE4.2  
Processor code: SLC3U  
Scalability: S2S  
Embedded options available: N  
Thermal Design Power (TDP): 130 W  
CPU multiplier (bus/core ratio): 18  
Processor series: Intel Xeon E7-2800  
Conflict Free processor: N

#### Memory

Internal memory: 512 GB  
Internal memory type: DDR3-SDRAM  
Memory slots: 32  
Memory clock speed: 1333 MHz  
ECC: Y

#### Storage

Total storage capacity: 16 GB  
Number of hard drives installed: 32  
Hard drive size: 2.5 "  
Hard drive interface: Serial ATA  
RAID support: Y  
RAID levels: 0,1

#### Networking

Ethernet LAN: Y

#### Design

Chassis type: Rack (2U)  
Optical drive type: N

#### Processor special features

CPU configuration (max): 2  
Intel Rapid Storage Technology: N  
Enhanced Intel SpeedStep Technology: Y  
Intel® Wireless Display (Intel® WiDi): N  
Intel Virtualization Technology for Directed I/O (VT-d): Y  
Intel® Anti-Theft Technology (Intel® AT): N  
Intel® Hyper Threading Technology (Intel® HT Technology): Y  
Intel® My WiFi Technology (Intel® MWT): N  
Intel® Turbo Boost Technology: Y  
Intel® vPro® Technology: N  
Intel® Quick Sync Video Technology: N  
Intel® InTru® 3D Technology: N  
Intel® Clear Video HD Technology (Intel® CHTM): N  
Intel® Insider® Technology: N  
Intel Flex Memory Access: N  
Intel® AES New Instructions (Intel® AES-NI): Y  
Intel Trusted Execution Technology: Y  
Intel Enhanced Halt State: N  
Intel VT-x with Extended Page Tables (EPT): Y  
Intel Demand Based Switching: N  
Intel Clear Video Technology: N  
Intel® Clear Video Technology for Mobile Internet Devices (Intel CVT for MID): N  
Intel 64: Y  
Intel Virtualization Technology (VT-x): Y  
Intel Dual Display Capable Technology: N  
Intel FDI Technology: N  
Intel Fast Memory Access: N  
Processor ARK ID: 53578

#### Power

Redundant power supply (RPS) support: N  
Power supply: 130 W

#### Operational conditions

Operating temperature (T-T): 10 - 35 °C  
Storage temperature (T-T): -40 - 65 °C  
Operating relative humidity (H-H): 5 - 93 %  
Storage relative humidity (H-H): 5 - 93 %  
Operating altitude: 0 - 3000 m  
Non-operating altitude: 0 - 12000 m

#### Certificates

Safety: UL 60950-1, CAN/CSA-C22.2 No. 60950-1, EN 60950-1, IEC 60950-1, AS/NZS 60950-1, GB4943  
Certification: 47CFR Part 15 (CFR 47), AS/NZS CISPR22, CISPR2 2, EN55022, ICES003, VCCI, EN61000-3-2, EN61000-3-3, KN22, CNS13438, EN50082-1, EN61000-6-1, EN55024, CISPR24, EN300386, KN 61000-4