

Cisco Nexus 7000 F2e network switch module (N7K-F248XP-25E=)

Nexus 7000 Enhanced F2-Series 48x 1G/10G Ethernet Module, SFP/SFP+, Spare



Price details:

Price excl. VAT: 29,815.26 €

Eco fees: 0.00 €

VAT 21 %: 6,261.20 €

Product details:

Product code: N7K-F248XP-25E=

EAN: 0882658522123

Manufacturer: Cisco

PDF generated on: 18 February, 2019



36,076.46 €

* VAT included

The Cisco Nexus® 7000 Enhanced F2-Series 48-Port Fiber 1 and 10 Gigabit Ethernet Module (referred to as the Cisco Nexus 7000 F2e-Series Fiber Module in this document) offers outstanding flexibility and wire-rate performance on each port. The module enables the deployment of high-density, low-latency, scalable data center architecture.

The Cisco Nexus 7000 Switches provide the foundation for the Cisco® Unified Fabric. They are a modular data center-class product line designed for highly scalable 10 Gigabit Ethernet networks. The fabric architecture scales beyond 15 terabits per second (Tbps), designed to support future 40 and 100 Gigabit Ethernet interfaces. To meet the requirements of the most mission-critical network environments, the switches deliver continuous system operations and virtualized services. The Cisco Nexus 7000 Switches is powered by the proven Cisco NX-OS Software operating system, with enhanced features to deliver real-time system upgrades with exceptional manageability and serviceability. Its innovative unified fabric design is purpose built to support consolidation of IP and storage networks on a single lossless Ethernet fabric.

Main specifications:

Networking

| | |
|--------------------------|------------------------------|
| Ethernet LAN data rates: | 1000 Mbit/s |
| Flow control support: | Y |
| Networking standards: | IEEE 802.1Qaz, IEEE 802.1Qbb |

Optical fiber

| | |
|------------------------|-----------|
| Fiber optic connector: | SFP, SFP+ |
|------------------------|-----------|

Data transmission

| | |
|--------------------|---------------|
| MAC address table: | 16384 entries |
| Forwarding rate: | 720 Mpps |
| Bandwidth: | 480 Gbit/s |

Ports & interfaces

| | |
|-----------------------|----|
| Fiber ports quantity: | 48 |
|-----------------------|----|

Performance

| | |
|-----------------------|------------------|
| Buffer size per port: | 72 MB |
| Compatibility: | Cisco Nexus 7000 |

Management features

| | |
|-----------------------------------|------|
| Quality of Service (QoS) support: | Y |
| Management platform: | DCNM |
| Access Control List (ACL): | Y |

Power

| | |
|------------------------------|-------|
| Power consumption (typical): | 350 W |
|------------------------------|-------|

Operational conditions

| | |
|------------------------------------|-------------|
| Operating temperature (T-T): | 0 - 40 °C |
| Storage temperature (T-T): | -40 - 70 °C |
| Operating relative humidity (H-H): | 5 - 90 % |
| Storage relative humidity (H-H): | 5 - 95 % |
| Operating temperature (T-T): | 32 - 104 °F |

Certificates

| | |
|--------------------------------|--|
| Safety: | UL/CSA/IEC/EN 60950-1, AS/NZS 60950 |
| Electromagnetic compatibility: | FCC Part 15 (CFR 47) (USA) Class A, ICES-003 (Canada) Class A, EN55022 (Europe) Class A, CISPR22 (International) Class A, AS/NZS CISPR22 (Australia and New Zealand) Class A, VCCI (Japan) Class A, KN22 (Korea) Class A, CNS13438 (Taiwan) Class A, CISPR24, EN55024, EN50082-1, EN61000-3-2, EN61000-3-3, EN61000-6-1, EN300 386 |

Weight & dimensions

| | |
|---------------------|-------------------|
| Dimensions (WxDxH): | 389 x 556 x 44 mm |
| Weight: | 6300 g |

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.