

Cisco 1921 wired router (C1921-VA/K9)

Cisco 1921 ISR with EHWIC-VA-DSL-A bundle



Price details:

Price excl. VAT: 988.31 €

Eco fees: 0.00 €

VAT 21 %: 207.55 €

Product details:

Product code: C1921-VA/K9

EAN: 0882658453397

Manufacturer: Cisco

PDF generated on: 18 December, 2018



1,195.86 €

Product is discontinued. You can not order it anymore.

* VAT included

Cisco® 1900 Series Integrated Services Routers (ISRs) build on 25 years of Cisco innovation and product leadership. The new platforms are architected to enable the next phase of branch-office evolution, providing rich-media collaboration to the branch office while maximizing operational cost savings. The Cisco Integrated Services Routers Generation 2 (ISR G2) platforms are future-enabled with multicore CPUs, Gigabit Ethernet switching with enhanced Power over Ethernet (PoE), and new energy monitoring and control capabilities that enhance overall system performance. Additionally, a new Cisco IOS® Software Universal image enables you to decouple the deployment of hardware and software, providing a stable technology foundation that can quickly adapt to evolving network requirements. Overall, the Cisco 1900 Series offers exceptional Total Cost of Ownership (TCO) savings and network agility through the intelligent integration of market-leading security, unified communications, wireless, and application services.

Main specifications:

WAN connection

Ethernet WAN:	Y
DSL WAN:	Y
SIM card slot:	N
3G/4G USB modem compatibility:	Y

Ethernet LAN features

Ethernet LAN:	Y
Ethernet LAN data rates:	10,100,1000 Mbit/s

Ports & interfaces

Ethernet LAN (RJ-45) ports:	2
USB ports quantity:	2
Serial ports quantity:	2

DSL features

DSL:	Y
------	---

Networking

Networking standards:	IEEE 802.3af
VLAN support:	Y

Protocols

Routing protocols:	BGP,EIGRP,IGRP,IS-IS,OSPF
--------------------	---------------------------

Antenna

Antenna type:	Not supported
---------------	---------------

Management features

Web-based management:	Y
Quality of Service (QoS) support:	Y

Security

Firewall:	Y
Security algorithms:	IPSec,SSL/TLS
Design	
Product colour:	Black
Rack mounting:	Y
Form factor:	1U
Wall mountable:	Y
Performance	
Flash memory:	256 MB
Internal memory:	512 MB
Internal memory type:	DRAM
Power	
Power consumption (typical):	25 W
AC input voltage:	100 - 240 V
AC input frequency:	47 - 63 Hz
Output voltage:	32 - 60 V
Output current:	4 A
Power over Ethernet (PoE):	Y
Input current:	1.5 - 0.6 A
Weight & dimensions	
Width:	342.9 mm
Depth:	292.1 mm
Height:	44.5 mm
Operational conditions	
Operating temperature (T-T):	0 - 40 °C
Storage temperature (T-T):	-40 - 70 °C
Operating relative humidity (H-H):	10 - 85 %
Storage relative humidity (H-H):	5 - 95 %
Operating altitude:	0 - 3000 m
Non-operating altitude:	0 - 4570 m
Certificates	
Certification:	UL 60950-1, CAN/CSA C22.2 No. 60950-1, EN 60950-1, AS/NZS 60950-1, IEC 60950-1

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.