

Cisco Surveillance 6020 IP (CIVS-IPC-6020=)

1/2.7" CMOS, 69 dB, 0.5 lux, Pan: 350°, Tilt: 80°, Rotate: 350°, 30 fps, 1920 x 1080, MicroSD card slot, Spare



Price details:

Price excl. VAT: 985.64 €

Eco fees: 0.04 €

VAT 21 %: 206.99 €

Product details:

Product code: CIVS-IPC-6020=

EAN: 0882658542145

Manufacturer: Cisco

PDF generated on: 23 February, 2019



1,192.67 €

* VAT included

The Cisco® Video Surveillance 6020 IP Camera is a high-definition, full-functioned video endpoint with industry-leading image quality and processing power. The camera is capable of full 1080p resolution at 30 frames per second (fps) while optimizing network usage with either H.264 or MJPEG compression. Contact closures allow integration with access control systems. With its open, standards-based design, the camera provides an ideal platform for integration and operation as an independent device or as part of a Cisco Video Surveillance network.

The Cisco Video Surveillance 6020 IP Camera offers a variety of benefits, including:

- True high-definition video: The camera streams crisp and clear 1080p (1920 x 1080) (2.1 megapixel) video at 30 fps while maintaining low network bandwidth.
- Motorized focus and zoom: The lens on the 6020 IP Camera's dome allows the focus and zoom to be controlled remotely, greatly simplifying installations and field of view adjustments.
- Dual streaming: The camera can stream H.264 and MJPEG video simultaneously. Each video stream can be configured with individual resolution, quality, and frame-rate settings.
- Day/night operation: The camera provides true day/night functionality and includes an infrared filter that automatically switches to night mode in low-light scenes. This function can be set to manual, automatic, or scheduled control.
- Privacy regions: The camera supports up to four user-defined privacy regions. Any video within a privacy region is masked in the video stream.
- Local storage: Video data can automatically be recorded to a microSD card when the camera loses network connectivity.
- Bidirectional audio: The camera supports full-duplex audio and options for half-duplex operation.
- Open API. Support for ONVIF 2.0 allows for standards based interoperability and communications with other ONVIF appliances.
- Flexible power options: The camera supports Power over Ethernet (PoE) 802.3af, 12 VDC, or 24 VAC power through an optional external power supply.
- Medianet support: The camera supports the Cisco Medianet interface. When connected to a Cisco switch that also supports Medianet, the switch recognizes the camera as a video endpoint and then uses SmartPort macros to set the right network parameters for the video stream on the network. In addition, the camera can be automatically discovered and configured when connected to Cisco Video Surveillance Manager 7.0, thereby minimizing installation time and cost.

Main specifications:

Performance

Type:	IP security camera
Placement supported:	Indoor & outdoor
PTZ control (Pan/Tilt/Zoom):	Y
Day/night mode:	Y
Alarm input/output:	Y

Design

Form factor:	Dome
--------------	------

Product colour:	Black,White
Mounting type:	Ceiling/Wall
Housing material:	Aluminium
LED indicators:	Activity,Power
Video	
Maximum resolution:	1920 x 1080 pixels
Video formats supported:	H.264,M-JPEG
Supported graphics resolutions:	160 x 90,320 x 192,640 x 368,768 x 432,960 x 540,1024 x 576 (WSVGA),1280 x 720 (HD 720),1920 x 1080 (HD 1080)
Supported video modes:	1080p
Analog signal format system:	NTSC,PAL
Frame rate:	30 fps
Camera	
Minimum illumination:	0.5 lx
Tilt angle range:	0 - 80 °
Pan range:	0 - 350 °
Angle of rotation:	350 °
White balance:	Auto,Manual
Camera shutter speed:	0.000031 s
Image sensor	
Sensor type:	CMOS
Optical sensor size:	1/2.7 "
Lens system	
Zoom capability:	Y
Security	
IP address filtering:	Y
Storage	
Card reader integrated:	Y
Compatible memory cards:	MicroSD (TransFlash)
Night vision	
Night vision:	Y
Networking	
Ethernet LAN:	Y
Wi-Fi:	N
Bluetooth:	N
Cabling technology:	10/100Base-T(X)
Supported network protocols:	Dynamic Host Control Protocol (DHCP), Hypertext Transfer Protocol (HTTP), Secure HTTP (HTTPS), Network Time Protocol (NTP), Real - Time Transport Protocol (RTP), Real - Time Streaming Protocol (RTSP), Simple Mail Transfer Protocol (SMTP), Secure Sockets Layer/Transport Layer Security (SSL/TLS), TCP/IP, Cisco Discovery Protocol, Bonjour, Simple Network Management Protocol (SNMP), and Secure Shell (SSH) Protocol
Ports & interfaces	
Connectivity technology:	Wired
Microphone in:	Y
Ethernet LAN (RJ-45) ports:	1
Interface:	RJ-45
Audio	
Audio system full duplex:	Y
Audio system:	1-way
Weight & dimensions	
Width:	160 mm
Depth:	160 mm
Height:	109 mm
Weight:	765 g
Power	
Power source type:	PoE
AC input voltage:	24 V
Power consumption (typical):	6.3 W
DC-in jack:	Y
Management features	

Remotely operated:	Y
Operational conditions	
Operating temperature (T-T):	-10 - 50 °C
Packaging content	
Number of cameras:	1

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.