

Cisco 7841 IP phone (CP-7841-K9=)

Supporting four lines, 8.89 cm (3.5") 396 x 162, 2 x 10/100/1000BASE-T, PoE, Black/Silver



Price details:

Price excl. VAT: 149.81 €

Eco fees: 0.00 €

VAT 21 %: 31.46 €

Product details:

Product code: CP-7841-K9=

EAN: 0882658621871

Manufacturer: Cisco

PDF generated on: 10 December, 2018



181.27 €

* VAT included

Deploy high-quality voice communications for your information workers, the administrative and managerial staff. The affordable Cisco IP Phone 7841 is full-featured and easy to use. Business calls are more efficient and productive, which fosters collaboration. The 7841 also supports wideband audio for superior voice quality and offers advanced IP communications features.

The Cisco IP Phone 7841 is a four-line endpoint that is ideal for:

- Customers who currently use analog and digital phones but want to migrate to IP telephony
- Existing Cisco customers who want to expand or update their investment in Cisco Unified Communications

This phone is designed for information workers, the administrative staff and managers who have a moderate level of voice communications needs.

Excellent User Experience

For easier recognition at a glance, the 7841 phone includes four context-sensitive soft keys and a white-backlit display that:

- Measures 3.5 inches (89 millimeters)
- Has high-resolution graphics and grayscale
- Is 396 x 162 pixels

Other features and capabilities that contribute to a superior user experience include:

- Dedicated fixed keys for common functions such as conference, messaging, and directory, and a two-way navigation button
- Full wideband audio (G.722) support throughout the handset, headset, and speakerphone for superior clarity
- Electronic hookswitch control for added flexibility in managing personal calls when using third-party headsets

Simple Administration

The 7841 phone is easy to deploy and manage, with features such as:

- Power over Ethernet (PoE) Class 1 endpoint and Cisco EnergyWise to help reduce your energy costs and carbon footprint
- Enhanced flexibility and customization with a field-replaceable bezel option
- Integrated IEEE 10/100/1000 switch to support traffic from a co-located PC and reduce your cable infrastructure costs
- A wall-mount option for common areas such as cafeterias and shipping and receiving docks, or where desk space is limited

Main specifications:

Features

Colour of product:

Black, Silver

Handset type:

Wired handset

Wall mountable:

Y

Volume control:	Digital
Mounting:	Desk/Wall
Case material:	Polycarbonate
Integrated voicemail:	Y
Display	
Touchscreen:	N
Display:	LCD
Display resolution:	396 x 162 pixels
Display diagonal:	3.5 "
Phone features	
Lines quantity:	4 lines
Caller ID:	Y
Answering machine:	Y
Call waiting:	Y
Speed dialing:	Y
Call hold:	Y
Call forwarding:	Y
Conference call:	Y
Audio	
Speakerphone:	Y
Voice codecs:	G.711a,G.722,G.729A,G.729B,iLBC
Networking	
Ethernet LAN:	Y
Wi-Fi:	N
Bluetooth:	N
Supported network protocols:	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3af
Quality of Service (QoS) support:	Y
Ports & interfaces	
Ethernet LAN (RJ-45) ports:	2
Power	
Power over Ethernet (PoE):	Y
Security	
Security algorithms:	802.1x RADIUS
Weight & dimensions	
Width:	207 mm
Depth:	206 mm
Height:	28 mm
Weight:	868 g
Certificates	
Safety:	UL 60950, CAN/CSA - C22.2, EN 60950, IEC 60950, AS/NZS 60950, GB4943
Operational conditions	
Operating temperature (T-T):	0 - 40 °C
Operating relative humidity (H-H):	10 - 90 %
Storage relative humidity (H-H):	10 - 95 %
Storage temperature (T-T):	-10 - 60 °C

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.