

Cisco ISR 4431 AXV Bundle wired router (ISR4431-AXV/K9)

ISR 4431 AXV Bundle, with PVDM4-64 with CUBE-25, UC, IPBase, APP and SEC licenses



Price details:

Price excl. VAT: 8,474.34 €

Eco fees: 0.00 €

VAT 21 %: 1,779.61 €

Product details:

Product code: ISR4431-AXV/K9

EAN: 0882658767159

Manufacturer: Cisco

10,253.95 €

* VAT included

PDF generated on: 25 March, 2018



Cisco® Application Experience (AX) routers revolutionize the delivery of application-aware services in the branch office and WAN, with comprehensive solutions for application visibility, control, and optimization to enable customers to successfully deploy, monitor, and troubleshoot their applications from anywhere.

Cisco Intelligent WAN with Akamai Connect

Cisco Intelligent WAN (IWAN) with Akamai Connect is a fully integrated solution from Cisco and Akamai that provides the next-generation application and network optimization. It integrates the best-in-class advanced WAN optimization and intelligent caching techniques directly into the Cisco Integrated Services Routers with Application Experience (ISR-AX) at the branch office. It effectively extends the Akamai Intelligent Platform across the last mile from the Internet directly into the branch office with edge caching, thus significantly offloading traffic from the WAN and providing a superior user experience over bandwidth-constrained networks. Akamai Connect provides faster content delivery regardless of device, connectivity, or cloud, including the corporate private cloud and the public Internet cloud, where most business traffic traverses. Each Cisco 2911-AX, 2921-AX, and 2951-AX ISR, Cisco 3900-AX and 4400-AX Series ISR-AX, and Cisco 4351 and 4331-AX router bundle also includes the option to add Akamai Connected Cache licenses.

Main specifications:

Ethernet LAN features

Ethernet LAN:	Y
Ethernet LAN data rates:	10,100,1000 Mbit/s
Cabling technology:	10/100/1000Base-T(X)

Ports & interfaces

WAN connection:	Ethernet (RJ-45)
Ethernet LAN (RJ-45) ports:	8
USB ports quantity:	3
USB version:	2.0
RS-232 ports:	2
DC-in jack:	Y

Networking

Networking standards:	IEEE 802.1Q,IEEE 802.1ag,IEEE 802.3,IEEE 802.3ah
-----------------------	--

Protocols

Routing protocols:	BGP,EIGRP,IS-IS,OSPF
Supported network protocols:	IPv4, IPv6, RIP, RIPv2, IGMPv3

Management features

Web-based management:	Y
Quality of Service (QoS) support:	Y

Reset button:	Y
Security	
Firewall:	Y
Security algorithms:	128-bit AES,256-bit AES,AES,DES
MAC address filtering:	Y
Authentication method:	RSA (748/1024/2048 bit), ECDSA (256/384 bit) ; Integrity: MD5, SHA, SHA-256, SHA-384, SHA-512
Design	
Colour of product:	Black
Rack mounting:	Y
Form factor:	1U
LED indicators:	Y
On/off switch:	Y
Performance	
Flash memory:	16000 MB
Internal memory:	16384 MB
Maximum memory card size:	32 GB
Power	
Power consumption (typical):	65 W
Power source type:	AC
AC input voltage:	100-240 V
AC input frequency:	47/63 Hz
Power supply:	250 W
Input current:	3 A
Weight & dimensions	
Width:	438.15 mm
Depth:	507.2 mm
Height:	43.9 mm
Package width:	565.1 mm
Package depth:	730.25 mm
Package height:	200.2 mm
Operational conditions	
Operating temperature (T-T):	0 - 40 °C
Storage temperature (T-T):	-25 - 70 °C
Operating relative humidity (H-H):	5 - 90 %
Storage relative humidity (H-H):	5 - 95 %
Operating altitude:	0 - 3048 m
Non-operating altitude:	0 - 4570 m
Certificates	
Safety:	UL 60950-1, CAN/CSA C22.2 No. 60950-1, EN 60950-1, AS/NZS 60950-1, IEC 60950-1, GB-4943

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.