

## Cisco 8865 IP phone (CP-8865-K9=)

12.7 cm (5") , 800 x 480, 720p, H.264, AVC, DTMF, QoS, RJ-9, 3.5 mm, USB, Bluetooth, Wi-Fi, 257.34 x 98.39 x 228.78 mm, 1.35 kg



### Price details:

Price excl. VAT: 319.60 €

Eco fees: 0.00 €

VAT 21 %: 67.12 €

### Product details:

Product code: CP-8865-K9=

EAN: 0882658845505

Manufacturer: Cisco

PDF generated on: 15 December, 2018



**386.72 €**

\* VAT included

Would you like to increase your personal productivity with an engaging experience that is powerful and easy-to-use? The business-class Cisco® IP Phone 8865 combines high-fidelity voice and entry to HD video communications with Cisco Intelligent Proximity for telephony integration with your personal mobile devices.

The IP Phone 8865 combines an attractive new ergonomic design with 720p HD video and wideband audio for crystal-clear voice communications, &#8220;always-on" reliability. Encrypted voice communications for enhanced security. And access to a comprehensive suite of unified communications features.

In addition, with Cisco Intelligent Proximity you can use your desk and mobile phones together when you are at your desk. During mobile calls you can move the audio path over to the 8865 for better acoustics. You then could share a conversation with a colleague who listens in. This capability gives you greater flexibility and a superior user experience when at your desk.

The 8865 comes standard with two USB ports so you can charge your personal mobile devices when at your desk and stay connected when away from your desk.

The IP Phone 8865 offers five programmable line keys. You can configure keys to support either multiple directory numbers or calling features such as speed dial. You can also boost productivity by handling multiple calls for each directory number using the multicall-per-line feature. Fixed-function keys give you one-touch access to applications, messaging, directory, as well as often-used calling features such as hold/resume, transfer, and conference. A five-way navigation cluster helps you transition through menus more easily. Backlit acoustic keys provide flexibility for audio path selection and switching.

Other key features of the phone include:

- The phone offers a 5-in. high-resolution (800 x 480) widescreen VGA backlit color display. Localized language support, including right-to-left on-screen text, meets the needs of global users.

### Main specifications:

#### Features

Product colour:	Charcoal
Handset type:	Wired handset
Wall mountable:	Y
Display contacts list status:	Y
Volume control:	Digital
Device lock:	Y
Mounting:	Desk/Wall
Case material:	ABS
Integrated voicemail:	Y

#### Display

Display resolution:	800 x 480 pixels
Display diagonal:	5 "
<b>Phone features</b>	
Caller ID:	Y
Answering machine:	Y
Call waiting:	Y
Speed dialing:	Y
Intercom:	Y
Call hold:	Y
Call forwarding:	Y
Conference call:	Y
Redialing:	Y
Call park:	Y
Call pick up:	Y
Full duplex:	Y
Call transfer:	Y
Message-waiting indicator (MWI):	Y
<b>Audio</b>	
Speakerphone:	Y
Voice codecs:	G.711,G.722,G.729A,iLBC
<b>Video</b>	
Video call:	Y
Video codecs:	H.264
Video capture resolution (max):	1280 x 720 pixels
<b>Networking</b>	
Ethernet LAN:	Y
Wi-Fi:	Y
Bluetooth:	Y
Ethernet LAN interface type:	Gigabit Ethernet
Ethernet LAN data rates:	10,100,1000 Mbit/s
Bluetooth version:	4.1 LE
Quality of Service (QoS) support:	Y
DHCP client:	Y
Wi-Fi standards:	IEEE 802.11a,IEEE 802.11ac,IEEE 802.11b,IEEE 802.11g,IEEE 802.11n
Networking standards:	IEEE 802.11a,IEEE 802.11ac,IEEE 802.11b,IEEE 802.11e,IEEE 802.11g,IEEE 802.11n,IEEE 802.1Q,IEEE 802.1p,IEEE 802.1x,IEEE 802.3ab,IEEE 802.3af,IEEE 802.3at,IEEE 802.3i,IEEE 802.3u
<b>Ports &amp; interfaces</b>	
Ethernet LAN (RJ-45) ports:	2
USB 2.0 ports quantity:	2
RJ-9 ports quantity:	1
Headphone outputs:	1
<b>Camera</b>	
Built-in camera:	Y
<b>Power</b>	
Power over Ethernet (PoE):	Y
<b>Security</b>	
Security algorithms:	AES,EAP-FAST,EAP-TLS,HTTPS,SIPS,SSH,SSL/TLS,WEP,WPA
<b>Weight &amp; dimensions</b>	
Width:	257.34 mm
Depth:	98.39 mm
Height:	228.78 mm
Weight:	1350 g
<b>Certificates</b>	
Safety:	UL 60950, CAN/CSA-C22.2 # 60950, EN 60950 (A11, A12), IEC 60950 (A11, A12), AS/NZS 60950, GB4943
Certification:	CE 2004/108/EC, CE 2006/95/EC
<b>Operational conditions</b>	
Operating temperature (T-T):	0 - 40 °C
Operating relative humidity (H-H):	10 - 90 %
Storage relative humidity (H-H):	10 - 95 %
Storage temperature (T-T):	-10 - 60 °C
<b>Packaging content</b>	

Number of handles included:

1 pc(s)

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.