

Cisco 8821 IP phone (CP-8821-K9-BUN)

Wireless IP Phone 8821 World mode device bundle, 2.4 - 5GHz, 802.11a/b/g/n/ac, Bluetooth 3.0, 3.0 dBi, QoS, 6.096 cm (2.4") 240 x 320, IP67, 126 g



Price details:

Price excl. VAT: 355.68 €

Eco fees: 0.30 €

VAT 21 %: 74.76 €

Product details:

Product code: CP-8821-K9-BUN

EAN: 0882658958311

Manufacturer: Cisco

PDF generated on: 12 December, 2018



430.74 €

* VAT included

The Cisco® Wireless IP Phone 8821 is a ruggedized, resilient, and secure 802.11 wireless LAN handset that delivers cost-effective, on-premises, comprehensive voice over wireless LAN (VoWLAN) communications for the highly mobile in-campus worker.

The 8821 is specifically designed for workers whose roles are in more rigorous, industrial settings. Examples of ideal use cases include nurses and doctors in healthcare, operations and engineering staff in manufacturing, customer service representatives in retail, service staff such as maids in hospitality, and workers on rigs in the oil and chemical industries.

While the 8821 is sleek and lightweight, the design is hardened for users. It is Ingress Protection standard (IP67) rated and is sealed for protection against dust, splash and water. The device is also MIL-STD-810G tested, with a dozen drops onto concrete from heights of up to 6 feet (1.8 m), to help ensure shock resistance and avoid breakage if dropped.

The 8821 enhances security and simplifies configuration management. Stronger encryption is supported for certificate management and policy enablement with the support of Secure Hash Algorithm 2 (SHA-2). Simple Certificate Enrollment Protocol (SCEP) eases IT administration by enabling automatic certificate management on the device.

End users will enjoy a larger, higher-resolution color display and a user experience that is common with Cisco IP Phone 8800 Series desk phones. In addition, roaming between access points within the campus will support more seamless voice communications with the 8821's support of Fast Transition (802.11r). This protocol was specifically designed for mobile voice over IP (VoIP) communications devices within Wi-Fi networks. Bluetooth is supported for the user's choice of third-party wireless headsets and adds freedom by untethering the user from the handset.

The 8821 supports Cisco and/or third-party XML applications such as push-to-talk.

Features

The Cisco Wireless IP Phone 8821 is designed for users in rigorous workspaces as well as general office environments. It supports a wide range of features for enhanced voice communications, quality of service (QoS), and security. Some of the main benefits and highlights are listed here:

- IEEE 802.11a/b/g/n/ac radio for VoWLAN communications support
- The large 2.4-inch (6 cm) color (240 x 320 pixels) display makes viewing easy
- IP67 rated for protection against dust, splash, and water
- MIL-STD-810G standard for shock resistance
- The phone offers exceptional voice quality with high-definition (HD) voice
- A built-in full-duplex speakerphone offers high-quality hands-free communications
- The phone supports third-party Bluetooth 3.0 headsets and a 3.5-mm headphone jack for added freedom
- The Applications key provides direct access to XML applications such as push-to-talk and Lone Worker
- Battery life delivers a minimum of 13 hours of talk time
- Enhanced encryption support for SHA-1 and SHA-2 signatures
- Fast, secure roaming using 802.11r and Cisco Centralized Key Management roaming
- Automatic certificate renewal - SCEP support

Bundle includes:

- battery
 - power cord
 - power adapter
 - country clip
-

Main specifications:

Features

Colour of product:	Black
Handset type:	Wireless handset
Volume control:	Digital
Device lock:	Y
Data transfer rate:	54 Mbit/s
Integrated voicemail:	Y

Display

Touchscreen:	N
Display resolution:	240 x 320 pixels
Display diagonal:	2.4 "

Phone features

Caller ID:	Y
Call waiting:	Y
Speed dialing:	Y
Intercom:	Y
Call hold:	Y
Call forwarding:	Y
Conference call:	Y
Redialing:	Y
Call park:	Y
Call pick up:	Y
Full duplex:	Y
Vibrating alert:	Y
Frequency band:	2.412, 2.472, 5.180, 5.240, 5.260, 5.320, 5.500, 5.700, 5.745, 5.825 GHz
Call transfer:	Y

Audio

Speakerphone:	Y
Voice codecs:	G.711,G.711a,G.722,G.729,G.729ab,iLBC

Networking

Ethernet LAN:	N
Wi-Fi:	Y
Bluetooth:	Y
Bluetooth version:	3.0
Quality of Service (QoS) support:	Y
DHCP client:	Y
Syslog:	Y
Wi-Fi standards:	IEEE 802.11a,IEEE 802.11ac,IEEE 802.11b,IEEE 802.11g,IEEE 802.11n
Networking standards:	IEEE 802.11a,IEEE 802.11ac,IEEE 802.11b,IEEE 802.11d,IEEE 802.11e,IEEE 802.11g,IEEE 802.11n,IEEE 802.11r

Ports & interfaces

USB 2.0 ports quantity:	1
Headphone outputs:	1
Microphone in:	Y

Camera

Built-in camera:	N
------------------	---

Power

Power over Ethernet (PoE):	N
AC adapter input voltage:	100 - 240 V
Input frequency:	50 - 60 Hz
AC adapter output current:	0.2 A
Battery technology:	Lithium-Ion (Li-Ion)
Battery capacity:	2060 mAh
Battery voltage:	4.35 V

Standby time:	240 h
Talk time:	13 h
Security	
Security algorithms:	EAP-FAST,EAP-TLS,PEAP,WPA
Weight & dimensions	
Width:	56 mm
Depth:	17 mm
Height:	132 mm
Weight:	163 g
Certificates	
Safety:	UL 60950-1, CAN/CSA 60950-1, EN 60950-1, IEC 60950-1, AS/NZS 60950.1, IEC 60529 (IP 67)
Certification:	● 47 CFR Part 15 Class B● ICES-003 Class B● EN 55022 Class B● AS/NZS CISPR 22 Class B● CISPR 22 Class B● VCCI Class B● EN 61000-3-2● EN 61000-3-3● KN 22 Class B● EN 55024● EN 50082-1● EN 61000-6-1● EN61000-6-3● EN 300386● EN 60601-1-2● KN Immunity Series
Operational conditions	
Operating temperature (T-T):	-10 - 50 °C
Operating relative humidity (H-H):	10 - 95 %
Storage relative humidity (H-H):	10 - 95 %
Storage temperature (T-T):	-30 - 60 °C
Packaging content	
Number of handles included:	1 pc(s)
Cables included:	AC
AC adapter included:	Y

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.