

## Cisco 7821 IP phone (CP-7821-3PCC-K9=)

Supporting two lines, 8.89 cm (3.5") 396 x 162, 2 x 10/100BASE-T, PoE, Black/Silver, Third-Party Call Control



### Price details:

Price excl. VAT: 79.26 €

Eco fees: 0.30 €

VAT 21 %: 16.71 €

### Product details:

Product code: CP-7821-3PCC-K9=

EAN: 0882658829796

Manufacturer: Cisco

**96.27 €**

\* VAT included

PDF generated on: 15 December, 2018



### Increase Productivity with Clear Communications

Deploy reliable and highly secure voice communications with the Cisco IP Phone 7821. This full-featured phone is easy to use and easy on your budget. This endpoint supports wideband audio for superior voice communications quality and advanced IP telephony features to make your business calls more efficient and productive.

The Cisco IP Phone 7821 is a two-line endpoint that is designed for information workers and managers. This phone is ideal for:

- Customers who currently use traditional analog or digital phones but want to move to IP telephony
- Organizations that want to expand their voice communications investment by using Cisco Unified Communications

### Superior User Experience

To improve the user experience, this phone has four context-sensitive soft keys and a white-backlit display that:

- Measures 3.5 inches (89 millimeters)
- Has high-resolution graphics and grayscale
- Is 396 x 162 pixels

Other features and capabilities of the 7821 phone that contribute to an exceptional user experience include:

- Dedicated fixed keys for common functions such as conference, messaging, and directory, and a two-way navigation button
- Full wideband audio (G.722) performance throughout the handset, headset, and speakerphone for superior clarity
- Electronic hookswitch control for added flexibility in managing personal calls when using third-party headsets

### Easy Administration

The 7821 phone is easy to deploy and manage, with features such as:

- Power over Ethernet (PoE) Class 1 endpoint and Cisco EnergyWise to reduce your energy costs and carbon footprint
- Enhanced customization with a field-replaceable bezel option
- Integrated IEEE 10/100 switch to support traffic from a co-located PC for reduced cable infrastructure costs
- A wall-mount option for common areas such as aisles or hallways, or where desk space is limited

### Main specifications:

#### Features

Colour of product:	Black, Silver
Handset type:	Wired handset
Wall mountable:	Y
Volume control:	Digital

Mounting:	Desk/Wall
Case material:	Polycarbonate
Integrated voicemail:	Y
<b>Display</b>	
Touchscreen:	N
Display resolution:	396 x 162 pixels
Display diagonal:	3.5 "
<b>Phone features</b>	
Lines quantity:	2 lines
Caller ID:	Y
Answering machine:	Y
Call waiting:	Y
Speed dialing:	Y
Call hold:	Y
Call forwarding:	Y
Conference call:	Y
<b>Audio</b>	
Speakerphone:	Y
Voice codecs:	G.711a,G.722,G.729A,G.729B,iLBC
<b>Networking</b>	
Ethernet LAN:	Y
Wi-Fi:	N
Bluetooth:	N
Supported network protocols:	IEEE 802.3, IEEE 802.3u, IEEE 802.3af
Quality of Service (QoS) support:	Y
<b>Ports &amp; interfaces</b>	
Ethernet LAN (RJ-45) ports:	2
<b>Power</b>	
Power over Ethernet (PoE):	Y
<b>Security</b>	
Security algorithms:	802.1x RADIUS
<b>Weight &amp; dimensions</b>	
Width:	207 mm
Depth:	206 mm
Height:	28 mm
Weight:	867 g
<b>Certificates</b>	
Safety:	UL 60950, CAN/CSA - C22.2, EN 60950, IEC 60950, AS/NZS 60950, GB4943
<b>Operational conditions</b>	
Operating temperature (T-T):	0 - 40 °C
Operating relative humidity (H-H):	10 - 90 %
Storage relative humidity (H-H):	10 - 95 %
Storage temperature (T-T):	-10 - 60 °C

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.