

# Cisco 7811 IP phone (CP-7811-3PCC-K9=)



## Price details:

Price excl. VAT: 60.40 €

Eco fees: 0.30 €

VAT 21 %: 12.75 €

## Product details:

Product code: CP-7811-3PCC-K9=

EAN: 0882658885822

Manufacturer: Cisco

**73.45 €**

\* VAT included

PDF generated on: 10 December, 2018



/

## Main specifications:

### Features

Colour of product:	Black, Silver
Handset type:	Wired handset
Wall mountable:	Y
Volume control:	Digital
Mounting:	Desk/Wall
Case material:	Polycarbonate
Integrated voicemail:	Y

### Display

Touchscreen:	N
Display:	LED
Display resolution:	384 x 106 pixels
Display diagonal:	3.28 "

### Phone features

Lines quantity:	1 lines
Caller ID:	Y
Answering machine:	Y
Call waiting:	Y
Speed dialing:	Y
Call hold:	Y
Call forwarding:	Y
Conference call:	Y
Redialing:	Y
Full duplex:	Y

### Audio

Speakerphone:	Y
Number of microphones:	1
Microphone mute:	Y
Voice codecs:	G.711a, G.722, G.729A, G.729B, iLBC

### Networking

Ethernet LAN:	Y
Wi-Fi:	N
Bluetooth:	N
Supported network protocols:	IEEE 802.3, IEEE 802.3u, IEEE 802.3af

Quality of Service (QoS) support:	Y
<b>Ports &amp; interfaces</b>	
Ethernet LAN (RJ-45) ports:	2
RJ-9 ports quantity:	1
<b>Power</b>	
Power over Ethernet (PoE):	Y
<b>Security</b>	
Security algorithms:	802.1x RADIUS
<b>Weight &amp; dimensions</b>	
Width:	207 mm
Depth:	195 mm
Height:	33 mm
Weight:	806 g
<b>Certificates</b>	
Safety:	UL 60950, CAN/CSA - C22.2, EN 60950, IEC 60950, AS/NZS 60950, GB4943
<b>Operational conditions</b>	
Operating temperature (T-T):	0 - 40 °C
Operating relative humidity (H-H):	10 - 90 %
Storage relative humidity (H-H):	10 - 95 %
Storage temperature (T-T):	-10 - 60 °C

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.