

Cisco 8851 IP phone (CP-8851-3PCC-K9=)

800 x 480, 24-bit color, 5 WVGA, RJ-9, USB, 2 x 10/100/1000BASE-T Ethernet, Bluetooth 3.0+EDR, PoE, 1.19 kg, 3rd Party Call Ctrl



Price details:

Price excl. VAT: 184.08 €

Eco fees: 0.30 €

VAT 21 %: 38.72 €

Product details:

Product code: CP-8851-3PCC-K9=

EAN: 0882658829857

Manufacturer: Cisco

PDF generated on: 10 December, 2018



223.10 €

* VAT included

The Cisco® IP Phone 8851 is a business-class collaboration endpoint that combines high-fidelity, reliable, secure, and scalable voice communications with Cisco Intelligent Proximity for telephony integration for personal mobile devices to support midsize to large enterprise businesses.

With the Cisco IP Phone 8851, you can increase personal productivity through an engaging user experience that is both powerful and easy-to-use. The IP Phone 8851 combines an attractive new ergonomic design with wideband audio for crystal clear voice communications, "always-on" reliability, encrypted voice communications to enhance security, and access to a comprehensive suite of unified communication features from Cisco communication servers.

In addition, Cisco Intelligent Proximity brings the worlds of desk and mobile together for you when you are using your mobile device at the desk for your work. You can move the audio path over to the Cisco IP Phone 8851 during active mobile calls to take advantage of its superior audio acoustics. An example would be to share a conversation with a colleague who you want to listen in. This capability gives you greater flexibility and a superior user experience when at your desk.

The IP Phone 8851 also comes standard with a USB port so you can charge your smartphone when at your desk, and stay connected when away from your desk.

The Cisco IP Phone 8851 offers five programmable line keys. You can configure keys to support either multiple directory numbers or calling features such as speed dial. You can also boost productivity by handling multiple calls for each directory number using the multicall-per-line feature. Fixed-function keys give you one-touch access to applications, messaging, directory, as well as often-used calling features such as hold/resume, transfer, and conference. A five-way navigation cluster helps you transition through menus more easily. Backlit acoustic keys provide flexibility for audio path selection and switching.

Other key features of the phone follow:

- The Cisco IP Phone 8851 offers a 5-in. high-resolution (800 x 480) widescreen VGA backlit color display. Localized language support, including right-to-left on-screen text, meets the needs of global users.
- The phone supports a built-in Gigabit Ethernet switch for your PC connection.
- Support for Cisco EnergyWise technology makes the Cisco IP Phone 8851 more energy-efficient and ecofriendly; the phone is qualified by the Energy Star organization.
- An optional wall-mount kit is orderable as a spare part for customers seeking this capability.

Main specifications:

Features

Colour of product:	Black
Handset type:	Wired handset
Wall mountable:	Y
Backlight keypad:	Y

Volume control:	Digital
Device lock:	Y
Mounting:	Desk/Wall
Display	
Touchscreen:	N
Display resolution:	800 x 480 pixels
Display diagonal:	5 "
Phone features	
Caller ID:	Y
Call waiting:	Y
Speed dialing:	Y
Call hold:	Y
Call forwarding:	Y
Call pick up:	Y
Call transfer:	Y
Message-waiting indicator (MWI):	Y
Audio	
Speakerphone:	Y
Microphone mute:	Y
Voice codecs:	G.711a,G.722,G.729A,iLBC
Networking	
Ethernet LAN:	N
Wi-Fi:	N
Bluetooth:	Y
Bluetooth version:	3.0+EDR
Supported network protocols:	SIP, SPD, UDP, GARP, DNS, TFTP, HTTPS, VLAN, RTP, RTCP, PPDP
Quality of Service (QoS) support:	Y
DHCP client:	Y
Networking standards:	IEEE 802.3ab,IEEE 802.3af,IEEE 802.3at,IEEE 802.3i,IEEE 802.3u
Ports & interfaces	
Ethernet LAN (RJ-45) ports:	2
USB 2.0 ports quantity:	1
RJ-9 ports quantity:	1
DC-in jack:	Y
Power	
Power over Ethernet (PoE):	Y
Security	
Security algorithms:	EAP-FAST,EAP-TLS,HTTPS,SIPS,SSH,SSL/TLS
Weight & dimensions	
Width:	257.3 mm
Depth:	40 mm
Height:	229.1 mm
Weight:	1190 g
Operational conditions	
Operating temperature (T-T):	0 - 40 °C
Operating relative humidity (H-H):	10 - 90 %
Storage relative humidity (H-H):	10 - 95 %
Storage temperature (T-T):	-10 - 60 °C
Packaging content	
Number of handles included:	1 pc(s)

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.