

Cisco 6901 IP phone (CP-6901-W-K9=)

IP Phone 6901, IEEE Ethernet 802.3af, Class 1, 48 VDC, Standard Handset, Arctic White



Price details:

Price excl. VAT: 82.73 €

Eco fees: 0.00 €

VAT 21 %: 17.37 €

Product details:

Product code: CP-6901-W-K9=

EAN: 0882658289231

Manufacturer: Cisco

PDF generated on: 12 December, 2018



100.10 €

* VAT included

Product Overview

The Cisco Unified IP Phone 6901 is a single-line endpoint delivering cost-effective access to Cisco Unified Communications. Designed with a trimline-like low profile, the Cisco Unified IP Phone 6901 is an ideal solution for lobbies, hallways, elevators, hotel bathrooms, or other settings that have an occasional need for voice communications services.

The Cisco Unified IP Phone 6901 supports two incoming calls with call-waiting service. Fixed feature keys provide one-touch access to Hold, Redial, and Call waiting. Transfer and Conference can be supported by using the hook-switch similar to that of traditional analog phones.

The Cisco Unified IP Phone 6901 offers personalization, with the choice of two colors (charcoal and arctic white) and two handset style options (slimline and standard).

The Cisco Unified IP Phone 6901 is an earth-friendly solution. As with the other Cisco Unified IP Phone 6900 Series endpoints, the Cisco Unified IP Phone 6901 takes advantage of reground and recyclable plastics for a more earth-responsible solution.

Main specifications:

Features

Colour of product: White
Keypad number of keys: 12

Phone features

Caller ID: N
Call waiting: Y
Distinctive ring: N
Speed dialing: N
Intercom: N
Call hold: Y
Call forwarding: N
Conference call: Y
Redialing: Y
Do not disturb function: N
On-hook dialing: N

Audio

Speakerphone: N
Microphone mute: Y
Voice codecs: G.711,G.711a,G.729a

Networking

Ethernet LAN: Y
Supported network protocols: SCCP, SRTP, TLS, LLDP-MED, DHCP, IVR, RTCP
Quality of Service (QoS) support: Y

DHCP client:	Y
Ports & interfaces	
Ethernet LAN (RJ-45) ports:	2
Power	
Power over Ethernet (PoE):	Y
Power consumption (typical):	2.77 W
Weight & dimensions	
Weight:	695 g
Certificates	
Safety:	(UL) 60950, (CSA) C22.2 No. 60950, EN 60950, IEC 60950, AS/NZS60950, TS 001
Certification:	(FCC) 15 (CFR 47) BICES-003 BEN55022 BCISPR22 BAS/NZS CISPR 22 BCISPR 24VCCI BEN55024EN 50082-1EN 61000-3-2EN 61000-3-3EN 61000-6-1FCC 68 (CFR47) HACTIA 810ACE
Compliance industry standards:	IEEE 802.3af
Operational conditions	
Operating temperature (T-T):	30 - 60 °C
Operating relative humidity (H-H):	5 - 95 %
Storage relative humidity (H-H):	5 - 95 %
Storage temperature (T-T):	-25 - 70 °C
System requirements	
Minimum system requirements:	8MB Flash32MB RAM (SDRAM)
Other features	
Dimensions (WxDxH):	94 x 46 x 205 mm
Input voltage:	48 V

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.