

Datamax O'Neil MF4te label printer (200370-200)

200370-200 MF4te, RS-232, 802.11b/g ETSI, Swivel Belt Clip excluded. Order separately



Price details:

Price excl. VAT: 755.69 €

Eco fees: 0.04 €

VAT 21 %: 158.70 €

Product details:

Product code: 200370-200

EAN:

Manufacturer: Datamax O'Neil

914.43 €

* VAT included

PDF generated on: 23 February, 2019



The microFlash family is one of the most rugged and reliable printer series available with a design that helps keep mobile workers productive.

The microFlash family offers the most rugged and reliable performance for route accounting, direct store delivery and field service workers. Frequent drops, extreme vibration, constant jarring, and excessive dust are just a few examples of the regular abuse mobile technology endures. Few printers thrive in the demanding mobile workplace better, longer, or more reliably than the microFlash family of printers.

The microFlash 2te is a rugged and reliable 50.8 mm (2 in) wireless portable printer available in addition to being one of the smallest. USB connectivity allows the 2te to integrate easily into new or existing applications and is also available with optional Bluetooth® for wireless communication.

Main specifications:

Printing

Print technology:	Direct thermal
Maximum resolution:	203 x 203 DPI
Print speed:	51 mm/sec

Display

Display:	No
----------	----

Ports & interfaces

Ethernet LAN:	Y
Wi-Fi:	Y
Optional connectivity:	Serial (RS-232),USB 2.0
Connectivity technology:	Wireless
USB 2.0 ports quantity:	1
RS-232 ports:	1
Wi-Fi standards:	IEEE 802.11b,IEEE 802.11g

Memory

Internal memory:	2 MB
Flash memory:	4 MB

Paper handling

Maximum roll diameter:	57 mm
Supported paper width:	112 mm

Performance

Built-in barcodes:	EAN13,Interleaved 2/5,UPC-A,UPC-E
--------------------	-----------------------------------

Design

Colour of product:	Black
LED indicators:	Y

Power

Number of batteries supported:	2
Battery technology:	Lithium-Ion (Li-Ion)
Battery capacity:	2200 mAh

Weight & dimensions

Width:	193.5 mm
Depth:	68.3 mm
Height:	175.8 mm
Weight:	590 g

Operational conditions

Operating relative humidity (H-H):	10 - 90 %
Operating temperature (T-T):	-20 - 50 °C
Storage temperature (T-T):	-40 - 70 °C

Packaging content

AC adapter included:	Y
Wrist strap included:	Y
Manual:	Y