

## Datamax O'Neil MF4te label printer (200362-100)

200362-100 MF4te, RS-232, Bluetooth, E-Charge, Swivel Belt Clip excluded. Order separately



### Price details:

Price excl. VAT: 638.82 €

Eco fees: 0.11 €

VAT 21 %: 134.18 €

### Product details:

Product code: 200362-100

EAN: 0783555089668

Manufacturer: Datamax O'Neil

**773.11 €**

\* VAT included

PDF generated on: 24 May, 2018



The microFlash family is one of the most rugged and reliable printer series available with a design that helps keep mobile workers productive.

The microFlash family offers the most rugged and reliable performance for route accounting, direct store delivery and field service workers. Frequent drops, extreme vibration, constant jarring, and excessive dust are just a few examples of the regular abuse mobile technology endures. Few printers thrive in the demanding mobile workplace better, longer, or more reliably than the microFlash family of printers.

The microFlash 2te is a rugged and reliable 50.8 mm (2 in) wireless portable printer available in addition to being one of the smallest. USB connectivity allows the 2te to integrate easily into new or existing applications and is also available with optional Bluetooth® for wireless communication.

### Main specifications:

#### Printing

Print technology: Direct thermal  
Maximum resolution: 203 x 203 DPI  
Print speed: 51 mm/sec

#### Display

Display: No

#### Ports & interfaces

Ethernet LAN: Y  
Wi-Fi: N  
Optional connectivity: Bluetooth, Serial (RS-232), USB 2.0  
Connectivity technology: Wireless  
USB 2.0 ports quantity: 1  
Bluetooth: Y  
Bluetooth version: 1.2  
RS-232 ports: 1

#### Memory

Internal memory: 2 MB

#### Paper handling

Maximum roll diameter: 57 mm  
Supported paper width: 112 mm

#### Performance

Built-in barcodes: EAN13, Interleaved 2/5, UPC-A, UPC-E

#### Design

Colour of product:	Black
LED indicators:	Y
<b>Power</b>	
Number of batteries supported:	2
Battery technology:	Lithium-Ion (Li-Ion)
Battery capacity:	2200 mAh
<b>Weight &amp; dimensions</b>	
Width:	172.2 mm
Depth:	69.1 mm
Height:	175.8 mm
Weight:	540 g
<b>Operational conditions</b>	
Operating relative humidity (H-H):	10 - 90 %
Operating temperature (T-T):	-20 - 50 °C
Storage temperature (T-T):	-40 - 70 °C
<b>Packaging content</b>	
AC adapter included:	Y
Wrist strap included:	Y
Manual:	Y

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.