

# Datamax O'Neil M-Class LP3 label printer (200268-100)

200268-100 LP3, RS-232



## Price details:

Price excl. VAT: 620.11 €

Eco fees: 0.04 €

VAT 21 %: 130.23 €

## Product details:

Product code: 200268-100

EAN:

Manufacturer: Datamax O'Neil

**750.38 €**

\* VAT included

PDF generated on: 20 February, 2019



LP3 is a 3" direct thermal portable label printer that delivers great paper capacity, long battery life and a range of wireless connectivity options for the retail and manufacturing marketplace. And of course, the reliability Datamax-O'Neil is known for around the globe.

The retail floor is no place for downtime. Constantly reloading supplies or getting a flashing low battery light in the middle of a markdown is simply unacceptable. The LP3 label printer offers almost twice the media capacity and twice the power capacity when compared to other barcode printers on the market. And with its fast and easy side-loading design, this means fewer interruptions and increased productivity on the floor.

The LP3 prints 1" to 3" direct thermal labels and can accommodate a wide variety of labels and paper including the heavy stock necessary for hang tags and specialty label needs.

## Main specifications:

### Printing

Print technology:	Direct thermal
Colour:	N
Maximum resolution:	203 x 203 DPI
Print speed:	51 mm/sec

### Display

Display:	No
----------	----

### Ports & interfaces

Ethernet LAN:	N
Wi-Fi:	Y
Optional connectivity:	Serial (RS-232)
Connectivity technology:	Wireless
RS-232 ports:	1

### Memory

Internal memory:	2 MB
Flash memory:	4 MB

### Paper handling

Maximum roll diameter:	25.4 - 76.2 mm
Media thickness:	0.05 - 0.18 mm
Supported paper width:	19 - 76.2 mm

### Performance

Built-in barcodes:	EAN13, Interleaved 2/5, PDF417, UPC-A, UPC-E
--------------------	--

### Design

Product colour:	Black
-----------------	-------

LED indicators:	Y
<b>Power</b>	
AC adapter output voltage:	15 V
Number of batteries supported:	2
Battery technology:	Lithium-Ion (Li-Ion)
Battery capacity:	2200 mAh
<b>Weight &amp; dimensions</b>	
Width:	157.5 mm
Depth:	131.3 mm
Height:	199.6 mm
Weight:	1130 g
<b>Operational conditions</b>	
Operating relative humidity (H-H):	0 - 45 %
Operating temperature (T-T):	10 - 90 °C
Storage temperature (T-T):	5 - 40 °C
<b>Packaging content</b>	
Drivers included:	Y

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.