

# Datamax O'Neil OC2 label printer (200325-201)

200325-201 OC2 Receipt, RS-232, 802.11b/g ETSI



## Price details:

Price excl. VAT: 515.05 €

Eco fees: 0.11 €

VAT 21 %: 108.18 €

## Product details:

Product code: 200325-201

EAN:

Manufacturer: Datamax O'Neil

**623.34 €**

\* VAT included

PDF generated on: 22 March, 2018



The OC is ideal to meet the continually expanding requirements associated with retail, healthcare, hospitality, transportation, and field mobile service applications.

The OC is one of the world's most streamlined, lightweight and ergonomic family of portable label and receipt printers. Designed especially for those labeling and transaction applications where ergonomic considerations, ultimate portability and smart looks are paramount, the OC is ideal to meet the continually expanding requirements associated with retail, healthcare, hospitality, transportation and field mobile-service applications.

## Main specifications:

### Printing

|                     |                |
|---------------------|----------------|
| Print technology:   | Direct thermal |
| Maximum resolution: | 203 x 203 DPI  |
| Print speed:        | 76.2 mm/sec    |

### Display

|          |    |
|----------|----|
| Display: | No |
|----------|----|

### Memory

|                  |      |
|------------------|------|
| Internal memory: | 2 MB |
| Flash memory:    | 4 MB |

### Paper handling

|                        |                |
|------------------------|----------------|
| Maximum label width:   | 48 mm          |
| Maximum roll diameter: | 57 mm          |
| Media thickness:       | 0.05 - 0.18 mm |

### Performance

|                    |  |
|--------------------|--|
| Built-in barcodes: | EAN13, Interleaved 2/5, PDF417, UPC-A, UPC-E |
|--------------------|--|

### Design

|                    |       |
|--------------------|-------|
| Colour of product: | Black |
|--------------------|-------|

### Power

|                                |                      |
|--------------------------------|----------------------|
| Number of batteries supported: | 1                    |
| Battery technology:            | Lithium-Ion (Li-Ion) |
| Battery capacity:              | 2200 mAh             |
| Input voltage:                 | 12 - 15 V            |

### Weight & dimensions

|         |          |
|---------|----------|
| Width:  | 131.8 mm |
| Depth:  | 69.85 mm |
| Height: | 124.5 mm |
| Weight: | 430 g    |

### Operational conditions

|                                    |             |
|------------------------------------|-------------|
| Operating relative humidity (H-H): | 10 - 90 %   |
| Operating temperature (T-T):       | -20 - 50 °C |
| Storage temperature (T-T):         | 5 - 40 °C   |

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.