

Datamax O'Neil A-Class Mark II A-4212 label printer (LA2-00-460C0000)

203 DPI, TT, EU/Uk Plug, Right Hand, Ribbon Saver, Top Pinch Roller



Price details:

Price excl. VAT: 2,695.33 €

Eco fees: 0.04 €

VAT 21 %: 566.03 €

Product details:

Product code: LA2-00-460C0000

EAN:

Manufacturer: Datamax O'Neil

3,261.40 €

* VAT included

PDF generated on: 19 November, 2017



Reliable, High Performance, Rugged

The A-Class Mark II is a superior print engine used in high demand print and apply applications offering the highest level of performance and reliability. Known in the industry for its unique stainless steel cover, the A-Class is ideal for the specialized needs of harsh or corrosive environments. The state of the art modular design offers easy on-demand serviceability that significantly reduces down time of the demanding multi-shift mission critical applications. The industry standard mounting and intuitive menu navigation makes the A-Class the print engine of choice for automated print and apply applications.

Get the Most for Your Investment

The A-Class has many outstanding features that may benefit you in many ways. Below is a brief list of the features and the benefit of the feature when using the A-Class print engine.

- Stainless steel cabinet protects your printer for years of service in rugged and extreme environments
- Printer language emulation allows you to seamlessly integrate the A-Class into most existing competitive environments
- Large graphic display enables easy navigation, advanced set-ups and simple operator use
- Optional remote display with 6' cable can be added when location is a challenge
- IntelliSEAQ printhead proactive diagnostic tools allow easy access to printhead performance and history
- Pinch roller option provides added tension for increased printing accuracy and quality
- USB/SDIO adds flexibility for expanded memory and USB attachments such as keyboards and memory flash drives
- Modular design makes it easy to service or upgrade in the field; most operations can be done on-site with minimal downtime or decrease in productivity
- Fully integrated UHF/HF RFID solutions available

Main specifications:

Printing

| | |
|-----------------------------|----------------|
| Print technology: | Direct thermal |
| Colour: | N |
| Maximum resolution: | 203 x 203 DPI |
| Print speed: | 304 mm/sec |
| Maximum printing width: | 104 mm |
| Print speed: | 12 lpm |
| Vertical printing: | Y |
| Rotated printing: | Y |
| Mirror printing: | Y |
| Standard printer languages: | PL-I, PL-Z |
| Minimum print length: | 6 mm |

Display

| | |
|--------------------------------------|--|
| Display: | LCD |
| Touchscreen: | N |
| Colour display: | N |
| Ports & interfaces | |
| Ethernet LAN: | Y |
| Wi-Fi: | N |
| Optional connectivity: | Wireless LAN |
| Connectivity technology: | Wired |
| Parallel ports quantity: | 1 |
| USB 2.0 ports quantity: | 1 |
| Bluetooth: | N |
| RS-232 ports: | 1 |
| Memory | |
| Internal memory: | 16 MB |
| Flash memory: | 8 MB |
| Paper handling | |
| Maximum label length: | 2.5 m |
| Media thickness: | 0.06 - 0.25 mm |
| Supported paper width: | 25 - 118 mm |
| Maximum media length: | 6 mm |
| Autocutter: | N |
| Core diameter: | 25.6 mm |
| Performance | |
| Built-in barcodes: | 1D,2D,CODABAR (NW-7),EAN13,EAN8,Industrial 2/5,Interleaved 2/5,POSTNET,UPC-A,UPC-E |
| Number of fonts: | 10 |
| Ribbon length: | 650 m |
| Built-in RFID module: | N |
| Design | |
| Colour of product: | Metallic |
| Navigation key: | N |
| LED indicators: | Y |
| Housing material: | Metal |
| Certification: | ISO 9001:2008 |
| Power | |
| Power consumption (typical): | 200 W |
| Power consumption (standby): | 25 W |
| Input voltage: | 90 - 264 V |
| Input frequency: | 47 - 63 Hz |
| Technical details | |
| Clock function: | Y |
| Cutter: | N |
| Handle(s): | N |
| Keyboard: | N |
| Weight & dimensions | |
| Width: | 246 mm |
| Depth: | 390 mm |
| Height: | 300 mm |
| Weight: | 15300 g |
| System requirements | |
| Windows operating systems supported: | Y |
| Operational conditions | |
| Operating relative humidity (H-H): | 10 - 90 % |
| Storage relative humidity (H-H): | 5 - 95 % |
| Operating temperature (T-T): | 4 - 38 °C |
| Storage temperature (T-T): | 5 - 95 °C |
| Packaging content | |
| Bundled software: | DMX Config |
| Drivers included: | Y |
| Cables included: | AC |
| AC adapter included: | Y |

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.