

Elo Touch Solution ECM2 (E077771)

Intel G41 Express, Intel Celeron Dual-Core E1500, DDRII 1GB, 160GB, SATA, USB 2.0, Intel GMA X4500, Gigabit Ethernet, Windows 7 Professional 32-bit



Price details:

Price excl. VAT: 521.12 €

Eco fees: 0.00 €

VAT 21 %: 109.44 €

Product details:

Product code: E077771

EAN: 0741149321266

Manufacturer: Elo Touch Solution

630.56 €

* VAT included

PDF generated on: 22 February, 2018

The Elo TouchSystems IDS (Interactive Digital Signage) touch platform enables increased customer engagement and real-time metrics for OOH (out-of-home) environments by adding an exciting new dimension to traditional broadcast digital signage - the power of touch. The IDS solution incorporates two high-performance optional Computer Modules, ECM1 and ECM2, that are designed specifically for the Elo Interactive Display Signage (IDS) touch displays and offer maximum flexibility in delivering high quality digital signage functionality to increase customer engagement in OOH environments. The Computer Modules pair with the Elo IDS touch displays to form a professional platform that delivers a range of performance options in a sleek and stylish package. The Computer Modules, are easily installed into the IDS displays providing an integrated system that optimizes media bandwidth and interactivity for the delivery of highly engaging and measurable consumer content. The optional Computer Modules come in two powerful configurations providing a wide range of touch computing needs with a choice of Intel processors. The ECM1 and ECM2 provide a high standard of quality for customer registration stations and check-in points as well as interactive digital signage applications. For average computing needs, the ECM1 comes with the Intel Celeron Dual-Core 2.2GHz processor and the ECM2 is powered by the Intel Core 2 Duo 3.0GHz processor for high performance computing needs.

The system is interoperable with content management servers and Web-based consoles for seamless connection with the Internet and applications such as multimedia sharing and electronic point-of-sale. The Computer Modules can support optimal partitioning of locally cached and network stored content, allowing developers to monitor and deploy content via device-to-device or Web connections. Separately, a USB kit is available to enable wireless connectivity to your signage network.

Main specifications:

Processor

Processor frequency:	2.2 GHz
Processor model:	E1500
Processor family:	Intel Celeron
Processor cores:	2
Processor front side bus:	800 MHz
L2 cache:	0.5 MB
Motherboard chipset:	Intel G41 Express

Memory

Internal memory:	1 GB
Internal memory type:	DDR2-SDRAM
Memory slots:	1x SO-DIMM
Memory layout (slots x size):	1 x 1 GB

Storage

Total storage capacity:	160 GB
Storage media:	HDD
Card reader integrated:	N

Storage drive interface:	Serial ATA
Storage drive size:	2.5 "
Graphics	
On-board graphics adapter model:	Intel GMA X4500
Video	
On-board graphics adapter:	Y
Networking	
Wi-Fi:	N
Ethernet LAN:	Y
Cabling technology:	10/100/1000Base-T(X)
Ports & interfaces	
VGA (D-Sub) ports quantity:	1
Ethernet LAN (RJ-45) ports:	1
USB 2.0 ports quantity:	4
Headphone outputs:	1
Microphone in:	Y
Line-out:	Y
Design	
Colour of product:	Grey
Display	
Display included:	N
Software	
Operating system installed:	Windows 7 Professional
Operational conditions	
Operating temperature (T-T):	0 - 40 °C
Storage temperature (T-T):	-20 - 50 °C
Operating relative humidity (H-H):	20 - 80 %
Storage relative humidity (H-H):	10 - 90 %
Certificates	
Certification:	UL, cJUL, FCC, CE, VCCI, IC, C-TICK, CCC, KC, BSMI, CB
Weight & dimensions	
Weight:	2600 g
Width:	287 mm
Depth:	229 mm
Height:	58 mm
Packaging data	
Package weight:	2900 g
Other features	
Package dimensions (WxDxH):	360 x 395 x 180 mm
Graphics adapter family:	Intel

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.