

Elo Touch Solution 22C3 POS terminal (E208024)

Intel Core 2 Duo E8400, 3.0GHz, 6MB L2 Cache, DDR2 2GB, Intel GMA X4500, HDD 160GB SATA, 54.61 cm (21.5 ") TFT LED LCD, 1920 x 1080, 16:9, CR 1000:1, 6 x USB 2.0, 2 x USB-to-Serial RS-232, 1 x HDMI, 1 x RJ-45, AccuTouch, Dark Grey, w/o OS, 113W



Price details:

Price excl. VAT: 1,256.12 €

Eco fees: 0.04 €

VAT 21 %: 263.79 €

Product details:

Product code: E208024

EAN: 0741149325400

Manufacturer: Elo Touch Solution

1,519.95 €

* VAT included

PDF generated on: 19 June, 2018

The Elo TouchSystems C-Series All-in-One touchcomputer platform leverages the same quality, performance, configurations and design as our popular B-Series 15" and 17" POS touchcomputer systems. The C-Series offers bigger, brighter displays in a wide-aspect ratio. This makes the C-Series an excellent choice for retail point-of-information, countertop product demonstration or customer information systems. In addition, hospitality host and seating systems that depend on an accurate display of restaurant layouts can utilize the wide screen of the C-Series and the additional screen space available to display their seating/floorspace.

The C-Series touchcomputers bring flexibility with your choice of configuration and connectivity, serviceability with easy access to key components, and a choice in processing power. In addition, an array of field-installable peripherals, spill-resistant sealing, and a selection of input/output port connection options make the C-Series both versatile and powerful. It is designed with your future in mind, allowing easy field serviceability of all of the main components.

The C-Series is engineered for flexibility, with optional memory and storage configurations, as well as scalable computing power featuring two high-performance processor configurations:

- Cool and Quiet C2 Fan-less Intel Atom Dual-Core 1.66 GHz
- Performance Ultra C3 Fan-cooled Intel Core 2 Duo 3.0 GHz

The flexibility, serviceability and performance of the C-Series are rare in commercial all-in-one touchcomputers. In a stylish, compact design, the C-Series provides highly configurable, ruggedized touchcomputers, in two screen sizes: 19-inch and 22-inch, plus the choice of industry-leading Elo touch technologies. The C-Series touchcomputer family has been developed to meet the demanding needs of a wide variety of hospitality and retail point-of-sale (POS), point-of-information (POI), point-of-service, point-of-presence, hospitality host station, kitchen systems, digital signage, customer loyalty, internet access sites, bedside entertainment and home automation and control.

Main specifications:

Display

Display diagonal:	21.5 "
Display resolution:	1920 x 1080 pixels
Touchscreen:	Y
Display brightness:	200 cd/m ²
Touchscreen technology:	Resistive
Contrast ratio (typical):	1000:1
Viewing angle, horizontal:	170 °
Viewing angle, vertical:	160 °
Response time:	5 ms
Effective viewing area:	476.6 x 268.1 mm
Aspect ratio:	16:9

Display number of colours:	16.78 million colours
Processor	
Processor frequency:	3 GHz
Processor family:	Intel Core 2 Duo
Processor model:	E8400
Processor cache:	6 MB
Processor front side bus:	1333 MHz
Motherboard chipset:	Intel G41 Express
Memory	
Internal memory:	2 GB
Internal memory type:	DDR2
Maximum internal memory:	4 GB
Storage	
Total storage capacity:	160 GB
Storage media type:	HDD
Hard drive capacity:	160 GB
Hard drive interface:	Serial ATA
Hard drive size:	2.5 "
Graphics	
Graphics adapter manufacturer:	Intel
Graphics adapter:	GMA X4500
Multimedia	
Built-in speaker(s):	Y
Number of speakers:	2
Card reader integrated:	N
Networking	
Ethernet LAN:	Y
Ethernet LAN data rates:	10,100,1000 Mbit/s
Ports & interfaces	
Ethernet LAN (RJ-45) ports:	1
USB 2.0 ports quantity:	6
HDMI ports quantity:	1
Line-out:	Y
Microphone in:	Y
Serial ports quantity:	2
ExpressCard slot:	N
Design	
Colour of product:	Grey
Software	
Operating system installed:	N
Power	
AC input voltage:	100-240 V
AC input frequency:	50/60 Hz
Power consumption (typical):	113 W
Operational conditions	
Operating relative humidity (H-H):	20 - 80 %
Operating temperature (T-T):	0 - 35 °C
Storage temperature (T-T):	-30 - 60 °C
Storage relative humidity (H-H):	5 - 95 %
Certificates	
Certification:	UL/cUL, FCC, TUV, CE, NOM COC, AR S-Mark, GOST-R, C-Tick, VCCI, CB, MPR II, 1PX1
Ergonomics	
Wall mountable:	Y
VESA mounting interfaces:	100 x 100 mm
On Screen Display (OSD):	Y
Mean time between failures (MTBF):	50000 h
Weight & dimensions	
Width:	540 mm
Depth:	98 mm

Height: 333 mm
Weight: 8500 g

Packaging data
Package weight: 15000 g

Security
Cable lock slot: Y
Cable lock slot type: Kensington

Other features
Memory slots: 1