

## Elo Touch Solution 22C3 POS terminal (E208024)

Intel Core 2 Duo E8400, 3.0GHz, 6MB L2 Cache, DDR2 2GB, Intel GMA X4500, HDD 160GB SATA, 54.61 cm (21.5 ") TFT LED LCD, 1920 x 1080, 16:9, CR 1000:1, 6 x USB 2.0, 2 x USB-to-Serial RS-232, 1 x HDMI, 1 x RJ-45, AccuTouch, Dark Grey, w/o OS, 113W



### Price details:

Price excl. VAT: 1,246.68 €

Eco fees: 0.04 €

VAT 21 %: 261.81 €

### Product details:

Product code: E208024

EAN: 0741149325400

Manufacturer: Elo Touch Solution

**1,508.53 €**

\* VAT included

PDF generated on: 18 October, 2017

The Elo TouchSystems C-Series All-in-One touchcomputer platform leverages the same quality, performance, configurations and design as our popular B-Series 15" and 17" POS touchcomputer systems. The C-Series offers bigger, brighter displays in a wide-aspect ratio. This makes the C-Series an excellent choice for retail point-of-information, countertop product demonstration or customer information systems. In addition, hospitality host and seating systems that depend on an accurate display of restaurant layouts can utilize the wide screen of the C-Series and the additional screen space available to display their seating/floorspace.

The C-Series touchcomputers bring flexibility with your choice of configuration and connectivity, serviceability with easy access to key components, and a choice in processing power. In addition, an array of field-installable peripherals, spill-resistant sealing, and a selection of input/output port connection options make the C-Series both versatile and powerful. It is designed with your future in mind, allowing easy field serviceability of all of the main components.

The C-Series is engineered for flexibility, with optional memory and storage configurations, as well as scalable computing power featuring two high-performance processor configurations:

- Cool and Quiet C2 Fan-less Intel Atom Dual-Core 1.66 GHz
- Performance Ultra C3 Fan-cooled Intel Core 2 Duo 3.0 GHz

The flexibility, serviceability and performance of the C-Series are rare in commercial all-in-one touchcomputers. In a stylish, compact design, the C-Series provides highly configurable, ruggedized touchcomputers, in two screen sizes: 19-inch and 22-inch, plus the choice of industry-leading Elo touch technologies. The C-Series touchcomputer family has been developed to meet the demanding needs of a wide variety of hospitality and retail point-of-sale (POS), point-of-information (POI), point-of-service, point-of-presence, hospitality host station, kitchen systems, digital signage, customer loyalty, internet access sites, bedside entertainment and home automation and control.

### Main specifications:

#### Display

Display diagonal:	21.5 "
Display resolution:	1920 x 1080 pixels
Touchscreen:	Y
Display brightness:	200 cd/m <sup>2</sup>
Touchscreen technology:	Resistive
Contrast ratio (typical):	1000:1
Viewing angle, horizontal:	170 °
Viewing angle, vertical:	160 °
Response time:	5 ms
Effective viewing area:	476.6 x 268.1 mm
Aspect ratio:	16:9

Display number of colours:	16.78 million colours
<b>Processor</b>	
Processor frequency:	3 GHz
Processor family:	Intel Core 2 Duo
Processor model:	E8400
Processor cache:	6 MB
Processor front side bus:	1333 MHz
Motherboard chipset:	Intel G41 Express
<b>Memory</b>	
Internal memory:	2 GB
Internal memory type:	DDR2
Maximum internal memory:	4 GB
<b>Storage</b>	
Total storage capacity:	160 GB
Storage media type:	HDD
Hard drive capacity:	160 GB
Hard drive interface:	Serial ATA
Hard drive size:	2.5 "
<b>Graphics</b>	
Graphics adapter manufacturer:	Intel
Graphics adapter:	GMA X4500
<b>Multimedia</b>	
Built-in speaker(s):	Y
Number of speakers:	2
Card reader integrated:	N
<b>Networking</b>	
Ethernet LAN:	Y
Ethernet LAN data rates:	10,100,1000 Mbit/s
<b>Ports &amp; interfaces</b>	
Ethernet LAN (RJ-45) ports:	1
USB 2.0 ports quantity:	6
HDMI ports quantity:	1
Line-out:	Y
Microphone in:	Y
Serial ports quantity:	2
ExpressCard slot:	N
<b>Design</b>	
Colour of product:	Grey
<b>Software</b>	
Operating system installed:	N
<b>Power</b>	
AC input voltage:	100-240 V
AC input frequency:	50/60 Hz
Power consumption (typical):	113 W
<b>Operational conditions</b>	
Operating relative humidity (H-H):	20 - 80 %
Operating temperature (T-T):	0 - 35 °C
Storage temperature (T-T):	-30 - 60 °C
Storage relative humidity (H-H):	5 - 95 %
<b>Certificates</b>	
Certification:	UL/cUL, FCC, TUV, CE, NOM COC, AR S-Mark, GOST-R, C-Tick, VCCI, CB, MPR II, 1PX1
<b>Ergonomics</b>	
Wall mountable:	Y
VESA mounting interfaces:	100 x 100 mm
On Screen Display (OSD):	Y
Mean time between failures (MTBF):	50000 h
<b>Weight &amp; dimensions</b>	
Width:	540 mm
Depth:	98 mm

Height:	333 mm
Weight:	8500 g
<b>Packaging data</b>	
Package weight:	15000 g
<b>Security</b>	
Cable lock slot:	Kensington
<b>Other features</b>	
Memory slots:	1

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.