

## Elo Touch Solution 22C2 (E531206)

Intel Atom Dual-Core D510, 1.66GHz, 1MB L2 Cache, DDR2 2GB, Intel GMA 3150, HDD 160GB SATA, 46.99 cm (18.5 ") TFT LED LCD, 1920 x 1080, 16:9, CR 1000:1, 6 x USB 2.0, 2 x USB-to-Serial RS-232, 1 x RJ-45, IntelliTouch Plus, Dark Grey, w/o OS, 54W



### Price details:

Price excl. VAT: 997.98 €

Eco fees: 0.04 €

VAT 21 %: 209.58 €

### Product details:

Product code: E531206

EAN: 0741149325394

Manufacturer: Elo Touch Solution

**1,207.60 €**

\* VAT included

PDF generated on: 13 December, 2017

The Elo TouchSystems C-Series All-in-One touchcomputer platform leverages the same quality, performance, configurations and design as our popular B-Series 15" and 17" POS touchcomputer systems. The C-Series offers bigger, brighter displays in a wide-aspect ratio. This makes the C-Series an excellent choice for retail point-of-information, countertop product demonstration or customer information systems. In addition, hospitality host and seating systems that depend on an accurate display of restaurant layouts can utilize the wide screen of the C-Series and the additional screen space available to display their seating/floorspace.

The C-Series touchcomputers bring flexibility with your choice of configuration and connectivity, serviceability with easy access to key components, and a choice in processing power. In addition, an array of field-installable peripherals, spill-resistant sealing, and a selection of input/output port connection options make the C-Series both versatile and powerful. It is designed with your future in mind, allowing easy field serviceability of all of the main components.

The C-Series is engineered for flexibility, with optional memory and storage configurations, as well as scalable computing power featuring two high-performance processor configurations:

- Cool and Quiet C2 Fan-less Intel Atom Dual-Core 1.66 GHz
- Performance Ultra C3 Fan-cooled Intel Core 2 Duo 3.0 GHz

The flexibility, serviceability and performance of the C-Series are rare in commercial all-in-one touchcomputers. In a stylish, compact design, the C-Series provides highly configurable, ruggedized touchcomputers, in two screen sizes: 19-inch and 22-inch, plus the choice of industry-leading Elo touch technologies. The C-Series touchcomputer family has been developed to meet the demanding needs of a wide variety of hospitality and retail point-of-sale (POS), point-of-information (POI), point-of-service, point-of-presence, hospitality host station, kitchen systems, digital signage, customer loyalty, internet access sites, bedside entertainment and home automation and control.

### Main specifications:

#### Display

Display diagonal:	21.5 "
Display resolution:	1920 x 1080 pixels
HD type:	Full HD
Touchscreen:	Y
Full HD:	Y
Aspect ratio:	16:9
Display brightness:	225 cd/m <sup>2</sup>
Contrast ratio (typical):	1000:1
Viewing angle, horizontal:	170 °
Viewing angle, vertical:	160 °
Display number of colours:	16.78 million colours

#### Processor

Processor frequency:	1.66 GHz
Processor family:	Intel Atom
Processor cores:	2
Processor threads:	4
Processor cache:	1 MB
System bus rate:	2.5 GT/s
64-bit computing:	Y

#### Memory

Internal memory:	2 GB
Maximum internal memory:	4 GB
Internal memory type:	DDR2-SDRAM
Memory slots type:	DIMM

#### Storage

Total storage capacity:	160 GB
Storage media:	HDD
Number of storage drives installed:	1
Number of hard drives installed:	1
Hard drive interface:	Serial ATA
Hard drive size:	2.5 "

#### Graphics

On-board graphics adapter:	Y
On-board graphics adapter model:	Intel GMA 3150
On-board graphics adapter family:	Intel GMA

#### Audio

Built-in speaker(s):	N
RMS rated power:	2 W
Number of speakers:	2

#### Networking

Ethernet LAN:	Y
Bluetooth:	N
Ethernet LAN data rates:	10,100,1000 Mbit/s

#### Ports & interfaces

USB 2.0 ports quantity:	6
Headphone outputs:	1
Microphone in:	Y
FireWire 800:	N
Ethernet LAN (RJ-45) ports:	1
DVI port:	N
Serial ports quantity:	2
S/PDIF out port:	N

#### Design

Colour of product:	Grey
--------------------	------

#### Software

Operating system installed:	N
-----------------------------	---

#### Power

AC adapter power:	150 W
AC adapter frequency:	50/60 Hz
AC adapter input voltage:	100 - 240 V
Power consumption (typical):	54 W

#### Weight & dimensions

Width:	540 mm
Depth:	98 mm
Height:	333 mm
Weight:	8300 g
Package weight:	14900 g

#### Operational conditions

Operating temperature (T-T):	0 - 35 °C
Storage temperature (T-T):	-30 - 60 °C
Operating relative humidity (H-H):	20 - 80 %
Storage relative humidity (H-H):	5 - 95 %

#### Certificates

Certification:

UL/cUL, FCC, TUV, CE, NOM COC, AR S-Mark, GOST-R, C-Tick, VCCI, CB, MPR II, 1PX1

#### Other features

Graphics adapter family:	Intel
Package dimensions (WxDxH):	600 x 360 x 516 mm
Storage drive interface:	Serial ATA
Chassis type:	All-in-One
Display included:	Y
Ethernet interface type:	Gigabit Ethernet
Fibre Channel:	N
HDMI:	N
Headphone connectivity:	3.5 mm
Internal modem:	N
Line-in:	Y
Microphone connectivity:	3.5 mm
Number of processors installed:	1
Processor manufacturer:	Intel

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.