

Elo Touch Solution E518070 thin client (E518070)

Intel Core i5-2405S 2.5 GHz/ 3.3 GHz turbo, 4 GB DDR3, 320 GB 2.5" SATA HDD, Intel HD Graphics 3000, Gigabit Ethernet, 4 x USB 2.0, VGA, Windows 7 Professional 32-bit



Price details:

Price excl. VAT: 747.19 €

Eco fees: 0.38 €

VAT 21 %: 156.99 €

Product details:

Product code: E518070

EAN: 7411493313028

Manufacturer: Elo Touch Solution

904.56 €

* VAT included

PDF generated on: 18 October, 2017

The Elo TouchSystems IDS (Interactive Digital Signage) touch platform enables increased customer engagement and real-time metrics for OOH (out-of-home) environments by adding an exciting new dimension to traditional broadcast digital signage - the power of touch. The IDS solution incorporates three high-performance optional Computer Modules, ECM1, ECM2 and ECM3, that are designed specifically for the Elo Interactive Display Signage (IDS) touch displays and offer maximum flexibility in delivering high quality digital signage functionality to increase customer engagement in OOH environments. The Computer Modules pair with the Elo IDS touch displays to form a professional platform that delivers a range of performance options in a sleek and stylish package. The Computer Modules, are easily installed into the IDS displays providing an integrated system that optimizes media bandwidth and interactivity for the delivery of highly engaging and measurable consumer content. The optional Computer Modules come in three configurations providing a wide range of touch computing needs with a choice of Intel® processors. The ECM1, ECM2 and ECM3 provide a high standard of quality for customer registration stations and check-in points as well as interactive digital signage applications. For average computing needs, the ECM1 comes with the Intel Celeron Dual-Core 2.2GHz processor. For high performance computing needs, ECM2 is powered by Intel Core 2 Duo 3.0GHz processor and ECM3 is powered by Intel Core i5 2.5GHz processor

The system is interoperable with content management servers and Web-based consoles for seamless connection with the Internet and applications such as multimedia sharing and electronic point-of-sale. The Computer Modules can support optimal partitioning of locally cached and network stored content, allowing developers to monitor and deploy content via device-to-device or Web connections. Separately, a USB kit is available to enable wireless connectivity to your signage network.

Main specifications:

Processor

Processor frequency:	2.5 GHz
Processor model:	i5-2405S
Processor family:	Intel Core i5
Processor cores:	4
L3 cache:	6 MB
Motherboard chipset:	Intel H61 Express

Memory

Internal memory:	4 GB
Internal memory type:	DDR3-SDRAM
Memory layout (slots x size):	1 x 2 GB

Storage

Total storage capacity:	320 GB
Storage media:	HDD
Storage drive interface:	Serial ATA
Storage drive size:	2.5 "

Graphics

On-board graphics adapter model:	Intel HD Graphics 3000
Networking	
Wi-Fi:	N
Ethernet LAN:	Y
Cabling technology:	10/100/1000Base-T(X)
Ports & interfaces	
VGA (D-Sub) ports quantity:	1
Ethernet LAN (RJ-45) ports:	1
USB 2.0 ports quantity:	4
Headphone outputs:	1
Microphone in:	Y
Design	
Colour of product:	Grey
Display	
Display included:	N
Software	
Operating system installed:	Windows 7 Professional
Operating system architecture:	32-bit
Operational conditions	
Operating temperature (T-T):	0 - 40 °C
Storage temperature (T-T):	-20 - 50 °C
Operating relative humidity (H-H):	20 - 80 %
Storage relative humidity (H-H):	10 - 90 %
Weight & dimensions	
Weight:	2600 g
Width:	287 mm
Depth:	229 mm
Height:	58 mm
Packaging data	
Package width:	360 mm
Package depth:	395 mm
Package height:	180 mm
Package weight:	2900 g

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.