

Elo Touch Solution X2-17 POS terminal (E127426)

Intel Celeron J1900(2M Cache, up to 2.42 GHz), 2GB 1600MHz DDR3L, 320GB 2.5" 5400RPM, 43.18 cm (17 ") TFT 1280 x 1024, IntelliTouch, Intel HD, 9 x USB, 2 x RS-232, RJ45, 802.11 b/g/n, Bluetooth 4.0, Windows 7 Pro SP1 (64-bit)



Price details:

Price excl. VAT: 1,054.46 €

Eco fees: 0.00 €

VAT 21 %: 221.44 €

Product details:

Product code: E127426

EAN: 0834619005282

Manufacturer: Elo Touch Solution

1,275.90 €

* VAT included

PDF generated on: 18 June, 2018

The new Elo X-Series 15-inch and 17-inch All-in-One (AiO) touchcomputers bring style, flexibility and functionality to point-of-sale (POS), point-of-information (POI) and point-of-service applications within retail and hospitality environments. Configuration customization, serviceability and performance combine to deliver touchcomputing that adapts to your existing hardware, software and connectivity requirements.

The X-Series AiO touchcomputers are available with industry-leading touchscreen technologies from Elo including AccuTouch® micro-bezel 5-wire resistive, IntelliTouch® surface acoustic wave, IntelliTouch zero-bezel surface acoustic wave (SAW) and IntelliTouch Pro Projected Capacitive (PCAP).

The fan-less models utilize the Intel® Celeron Quad-Core processor for environments where noise may be an issue. Higher performance, the fan-cooled models feature 4th Generation Intel Core i3, i5 and i7 processors and HD2500 graphics. A wide array of field-installable peripherals, spill-resistant sealing and a range of input/output port connection options make the X-Series a versatile and powerful AiO solution.

The X-Series configuration choices meet the diverse needs of a wide variety of POS, POI and point-of-service venues, including retail and hospitality display units, customer loyalty systems and in-store kiosks, just to name a few.

Main specifications:

Display

Display diagonal:	17 "
Display resolution:	1280 x 1024 pixels
Touchscreen:	Y
Display brightness:	225 cd/m ²
Contrast ratio (typical):	700:1
Viewing angle, horizontal:	170 °
Viewing angle, vertical:	160 °
Response time:	16 ms
Effective viewing area:	337.92 x 270.36 mm
Aspect ratio:	5:4
Display number of colours:	16.78 million colours

Processor

Processor frequency:	2 GHz
Processor family:	Intel Celeron
Processor model:	J1900
Processor cores:	4
Processor cache:	2 MB
Processor front side bus:	5 MHz

Processor threads:	4
Memory	
Internal memory:	2 GB
Internal memory type:	DDR3L-SDRAM
Maximum internal memory:	8 GB
Number of memory slots:	2
Memory slots type:	SO-DIMM
Memory clock speed:	1600 MHz
Storage	
Total storage capacity:	320 GB
Storage media type:	HDD
Hard drive capacity:	320 GB
Hard drive interface:	Serial ATA
Hard drive speed:	5400 RPM
Hard drive size:	2.5 "
Graphics	
Graphics adapter manufacturer:	Intel
Graphics adapter:	HD Graphics
Networking	
Ethernet LAN:	Y
Ethernet LAN data rates:	10,100,1000 Mbit/s
Wi-Fi:	Y
Wi-Fi standards:	IEEE 802.11b,IEEE 802.11g,IEEE 802.11n
Ports & interfaces	
Ethernet LAN (RJ-45) ports:	1
USB 2.0 ports quantity:	9
Powered USB:	Y
VGA (D-Sub) ports quantity:	1
Line-in:	Y
Line-out:	Y
Serial ports quantity:	2
RS-232 ports:	2
Design	
Number of 2.5" bays:	1
Colour of product:	Black
Software	
Operating system installed:	Windows 7 Professional
Power	
AC input voltage:	100-240 V
AC input frequency:	50/60 Hz
Operational conditions	
Operating relative humidity (H-H):	20 - 80 %
Operating temperature (T-T):	0 - 35 °C
Storage temperature (T-T):	-20 - 60 °C
Storage relative humidity (H-H):	5 - 95 %
Certificates	
Certification:	UL/cUL, FCC, TUV, CE, CB, COC, S-mark, C-Tick, VCCI, CCC
Energy Star certified:	N
Ergonomics	
Wall mountable:	Y
VESA mounting:	Y
VESA mounting interfaces:	100 x 100 mm
Weight & dimensions	
Width:	397.3 mm
Depth:	391.1 mm
Height:	72.7 mm
Weight:	5600 g
Weight with stand:	8300 g
Packaging data	
Package width:	517 mm

Package depth:	487 mm
Package height:	367 mm
Package weight:	10800 g

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.