

Elo Touch Solution X2-15 POS terminal (E131321)

38.1 cm (15 ") TFT LCD, Intel Celeron J1900 (2 GHz, 4-Core), RAM 2GB, 320GB HDD, Gigabit Ethernet, WiFi 802.11 b/g/n, Bluetooth 4.0, AccuTouch, Expansion Module, Windows POSReady 7 (64-bit), Black



Price details:

Price excl. VAT: 1,008.35 €

Eco fees: 0.00 €

VAT 21 %: 211.75 €

Product details:

Product code: E131321

EAN: 0834619005480

Manufacturer: Elo Touch Solution

1,220.10 €

* VAT included

PDF generated on: 12 December, 2017

The new Elo X-Series 15-inch and 17-inch All-in-One (AiO) touchcomputers bring style, flexibility and functionality to point-of-sale (POS), point-of-information (POI) and point-of-service applications within retail and hospitality environments. Configuration customization, serviceability and performance combine to deliver touchcomputing that adapts to your existing hardware, software and connectivity requirements.

The X-Series AiO touchcomputers are available with industry-leading touchscreen technologies from Elo including AccuTouch micro-bezel 5-wire resistive, IntelliTouch surface acoustic wave, IntelliTouch zero-bezel surface acoustic wave (SAW) and IntelliTouch Pro Projected Capacitive (PCAP).

The fan-less models utilize the Intel Celeron Quad-Core processor for environments where noise may be an issue. Higher performance, the fan-cooled models feature 4th Generation Intel Core i3, i5 and i7 processors and HD2500 graphics. A wide array of field-installable peripherals, spill-resistant sealing and a range of input/output port connection options make the X-Series a versatile and powerful AiO solution.

The X-Series configuration choices meet the diverse needs of a wide variety of POS, POI and point-of-service venues, including retail and hospitality display units, customer loyalty systems and in-store kiosks, just to name a few.

Main specifications:

Display

Display diagonal:	15 "
Display resolution:	1024 x 768 pixels
Touchscreen:	Y
Display brightness:	200 cd/m ²
Touchscreen technology:	Resistive
Contrast ratio (typical):	700:1
Viewing angle, horizontal:	165 °
Viewing angle, vertical:	150 °
Response time:	16 ms
Effective viewing area:	304.12 x 228.1 mm
Aspect ratio:	4:3
Display number of colours:	16.78 million colours

Processor

Processor frequency:	2 GHz
Processor family:	Intel Celeron
Processor model:	J1900
Processor cores:	4
Processor cache:	2 MB

Processor threads:	4
Memory	
Internal memory:	2 GB
Internal memory type:	DDR3L-SDRAM
Memory slots type:	SO-DIMM
Memory clock speed:	1600 MHz
Storage	
Total storage capacity:	320 GB
Storage media type:	HDD
Hard drive capacity:	320 GB
Hard drive interface:	Serial ATA
Hard drive speed:	5400 RPM
Hard drive size:	2.5 "
Graphics	
Graphics adapter manufacturer:	Intel
Graphics adapter:	HD Graphics
Multimedia	
Card reader integrated:	N
Networking	
Ethernet LAN:	Y
Ethernet LAN data rates:	10,100,1000 Mbit/s
Wi-Fi:	Y
Wi-Fi standards:	802.11b,802.11g,802.11n
Ports & interfaces	
Ethernet LAN (RJ-45) ports:	2
DVI port:	N
VGA (D-Sub) ports quantity:	1
Line-out:	Y
Microphone in:	Y
RS-232 ports:	4
Design	
Chassis type:	All-in-one
Colour of product:	Black
Software	
Operating system installed:	Windows Embedded POSReady 7
Operating system architecture:	64-bit
Power	
Power consumption (typical):	35 W
Operational conditions	
Operating relative humidity (H-H):	20 - 80 %
Operating temperature (T-T):	0 - 35 °C
Storage temperature (T-T):	-20 - 60 °C
Relative humidity:	5 - 95 %
Certificates	
Certification:	UL/cUL, FCC, TUV, CE, CB, Mexico COC, Argentina S-mark (power brick only), C-Tick, VCCI, CCC
Ergonomics	
Wall mountable:	Y
VESA mounting:	Y
VESA mounting interfaces:	100 x 100 mm
Mean time between failures (MTBF):	50000 h
Weight & dimensions	
Width:	365.2 mm
Depth:	67.2 mm
Height:	348.8 mm
Weight:	4800 g
Weight with stand:	7500 g
Packaging data	
Package width:	482 mm
Package depth:	442 mm

Package height: 352 mm
Package weight: 9600 g

Security

Cable lock slot: Kensington