

## Elo Touch Solution X2-17 POS terminal (E133275)

Intel Celeron J1900(2M Cache, up to 2.42 GHz), 2GB 1600MHz DDR3L, 320GB 2.5" 5400RPM, 43.18 cm (17 ") TFT 1280 x 1024, IntelliTouch Pro PCAP, Intel HD, 9 x USB, 2 x RS-232, RJ45, 802.11 b/g/n, Bluetooth 4.0, No OS



### Price details:

Price excl. VAT: 1,043.71 €

Eco fees: 0.00 €

VAT 21 %: 219.18 €

### Product details:

Product code: E133275

EAN: 0834619005589

Manufacturer: Elo Touch Solution

**1,262.89 €**

\* VAT included

PDF generated on: 19 October, 2017

The new Elo X-Series 15-inch and 17-inch All-in-One (AiO) touchcomputers bring style, flexibility and functionality to point-of-sale (POS), point-of-information (POI) and point-of-service applications within retail and hospitality environments. Configuration customization, serviceability and performance combine to deliver touchcomputing that adapts to your existing hardware, software and connectivity requirements.

The X-Series AiO touchcomputers are available with industry-leading touchscreen technologies from Elo including AccuTouch® micro-bezel 5-wire resistive, IntelliTouch® surface acoustic wave, IntelliTouch zero-bezel surface acoustic wave (SAW) and IntelliTouch Pro Projected Capacitive (PCAP).

The fan-less models utilize the Intel® Celeron Quad-Core processor for environments where noise may be an issue. Higher performance, the fan-cooled models feature 4th Generation Intel Core i3, i5 and i7 processors and HD2500 graphics. A wide array of field-installable peripherals, spill-resistant sealing and a range of input/output port connection options make the X-Series a versatile and powerful AiO solution.

The X-Series configuration choices meet the diverse needs of a wide variety of POS, POI and point-of-service venues, including retail and hospitality display units, customer loyalty systems and in-store kiosks, just to name a few.

### Main specifications:

#### Display

|                            |                       |
|----------------------------|-----------------------|
| Display diagonal:          | 17 "                  |
| Display resolution:        | 1280 x 1024 pixels    |
| Touchscreen:               | Y                     |
| Contrast ratio (typical):  | 700:1                 |
| Viewing angle, horizontal: | 170 °                 |
| Viewing angle, vertical:   | 160 °                 |
| Response time:             | 16 ms                 |
| Effective viewing area:    | 337.92 x 270.36 mm    |
| Aspect ratio:              | 5:4                   |
| Display number of colours: | 16.78 million colours |

#### Processor

|                      |               |
|----------------------|---------------|
| Processor frequency: | 2 GHz         |
| Processor family:    | Intel Celeron |
| Processor model:     | J1900         |
| Processor cores:     | 4             |
| Processor cache:     | 2 MB          |
| Processor threads:   | 4             |

#### Memory

|                                    |  |
|------------------------------------|--|
| Internal memory:                   | 2 GB   |
| Internal memory type:              | DDR3L-SDRAM  |
| Maximum internal memory:           | 8 GB   |
| Number of memory slots:            | 2  |
| Memory slots type:                 | SO-DIMM  |
| Memory clock speed:                | 1600 MHz   |
| <b>Storage</b>                     |  |
| Total storage capacity:            | 320 GB   |
| Storage media type:                | HDD  |
| Hard drive capacity:               | 320 GB   |
| Hard drive interface:              | Serial ATA   |
| Hard drive speed:                  | 5400 RPM   |
| Hard drive size:                   | 2.5 "  |
| <b>Graphics</b>                    |  |
| Graphics adapter manufacturer:     | Intel  |
| Graphics adapter:                  | HD Graphics  |
| <b>Networking</b>                  |  |
| Ethernet LAN:                      | Y  |
| Ethernet LAN data rates:           | 10,100,1000 Mbit/s                                       |
| Wi-Fi:                             | Y  |
| Wi-Fi standards:                   | 802.11b,802.11g,802.11n                                  |
| <b>Ports &amp; interfaces</b>      |  |
| Ethernet LAN (RJ-45) ports:        | 1  |
| USB 2.0 ports quantity:            | 9  |
| Powered USB:                       | Y  |
| VGA (D-Sub) ports quantity:        | 1  |
| Line-in:                           | Y  |
| Line-out:                          | Y  |
| Serial ports quantity:             | 2  |
| RS-232 ports:                      | 2  |
| DC-in jack:                        | Y  |
| <b>Design</b>                      |  |
| Number of 2.5" bays:               | 1  |
| Colour of product:                 | Black  |
| <b>Software</b>                    |  |
| Operating system installed:        | N  |
| <b>Power</b>                       |  |
| AC input voltage:                  | 100-240 V  |
| AC input frequency:                | 50/60 Hz   |
| Power consumption (typical):       | 38 W   |
| <b>Operational conditions</b>      |  |
| Operating relative humidity (H-H): | 20 - 80 %  |
| Operating temperature (T-T):       | 0 - 35 °C  |
| Storage temperature (T-T):         | -20 - 60 °C  |
| Storage relative humidity (H-H):   | 5 - 95 %   |
| <b>Certificates</b>                |  |
| Certification:                     | UL/cUL, FCC, TUV, CE, CB, COC, S-mark, C-Tick, VCCI, CCC |
| <b>Ergonomics</b>                  |  |
| Wall mountable:                    | Y  |
| VESA mounting:                     | Y  |
| VESA mounting interfaces:          | 100 x 100 mm   |
| <b>Weight &amp; dimensions</b>     |  |
| Width:                             | 397.3 mm   |
| Depth:                             | 391.1 mm   |
| Height:                            | 72.7 mm  |
| Weight:                            | 5600 g   |
| Weight with stand:                 | 8300 g   |
| <b>Packaging data</b>              |  |
| Package width:                     | 517 mm   |
| Package depth:                     | 487 mm   |
| Package height:                    | 367 mm   |

Package weight:

10800 g

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.