

Elo Touch Solution ECMG2B (E001296)

Intel Core i5-4590S, 6M Cache, 3 GHz, Intel H81 Express, Intel HD 4600, 4GB DDR3L SDRAM, 320GB 2.5" HDD; USB x 4, 2 kg, Windows 7



Price details:

Price excl. VAT: 666.92 €

Eco fees: 0.00 €

VAT 21 %: 140.05 €

Product details:

Product code: E001296

EAN: 0834619002748

Manufacturer: Elo Touch Solution

806.97 €

* VAT included

PDF generated on: 17 December, 2017

The Elo Interactive Digital Signage (IDS) touch platform featuring the Intel® Core 4th Generation CPUs with enhanced graphic engines enables increased customer engagement and immersive brand experiences by adding an exciting new dimension to traditional broadcast digital signage - the power of touch. Elo's ECMG2B computer modules, available for use with the Elo 3201L, 4201L, 5501L and 7001LT IDS touchscreens are well-suited for interactive media delivery and online collaboration for modern office environments. The computer modules are easily installed into the IDS display - avoiding costs of in-wall installation of a traditional player or PC. Computer modules are available in a choice of three models: ECMG2B-i3 based on a 3.40GHz Intel® Core i3 processor and HD4400 graphics; ECMG2B-i5 based on a 3.70GHz Intel® Core i5 processor and HD4600 graphics; and ECMG2B-i7 based on a 4.00GHz Intel® Core i7 processor and HD4600 graphics.

Centralized management and security capabilities of Microsoft® Windows® ensures compatibility with many content management servers and web-based consoles for seamless connection with the internet, digital marketing, interactive whiteboard, building directory, virtual receptionist, and point-of-information (POI) applications.

The ECMG2B computer modules can support optimal partitioning of locally cached and network stored content, allowing developers to monitor and deploy content via device-to-device or web connections.

- Designed specifically for the new series of Elo IDS touch displays (3201L, 4201L, 5501L, 7001LT)
- No cables required - seamless docking integration.
- Choice of Intel® Core i3 3.40GHz, Core i5 3.70GHz or Core i7 4.00GHz processors.
- Available with Microsoft® Windows® 7, without OS or Microsoft® Windows® Embedded 8.1 Industry.
- 2, 4 or 8GB RAM, expandable up to 16GB RAM, and 320 GB, quick access hard drive.
- Multiple interfaces: 2 USB 2.0 Type A & 2 USB 3.0 Type A, Ethernet LAN RJ45, Audio MIC in & Line out 3.5mm, HDMI & Display Port video out.
- Platform for collaboration, digital whiteboard, building directory, virtual receptionist and other applications.
- Vandal-resistant connector panel with included cable cover.
- 3 year global warranty.

Main specifications:

Processor

Processor frequency:	3 GHz
Processor model:	i5-4590S
Processor family:	Intel Core i5
Processor cores:	4
Processor boost frequency:	3.7 GHz
L3 cache:	6 MB
Motherboard chipset:	Intel H81

Memory

Internal memory:	4 GB
------------------	------

Internal memory type:	DDR3L-SDRAM
Memory slots:	2x SO-DIMM
Memory layout (slots x size):	1 x 4 GB
Maximum internal memory:	16 GB
Storage	
Total storage capacity:	320 GB
Storage media:	HDD
Storage drive interface:	Serial ATA II
Storage drive size:	2.5 "
Maximum memory card size:	16 GB
Graphics	
On-board graphics adapter model:	Intel HD Graphics 4600
Networking	
Wi-Fi:	N
Ethernet LAN:	Y
Cabling technology:	10/100/1000Base-T(X)
Ports & interfaces	
Ethernet LAN (RJ-45) ports:	1
USB 2.0 ports quantity:	4
Design	
Colour of product:	Black
Display	
Display included:	N
Software	
Operating system installed:	Windows 7 Professional
Operational conditions	
Operating temperature (T-T):	0 - 40 °C
Storage temperature (T-T):	-20 - 60 °C
Operating relative humidity (H-H):	20 - 80 %
Storage relative humidity (H-H):	5 - 95 %
Weight & dimensions	
Weight:	2000 g
Width:	274 mm
Depth:	248 mm
Height:	37 mm
Packaging data	
Package width:	390 mm
Package depth:	362 mm
Package height:	120 mm

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.