

## Elo Touch Solution E270176 POS terminal (E270176)

PCAP Win Pro 7, 13.3" Active matrix TFT LCD, 1920 x 1080 @ 60Hz, 16:9, 400 nits, Intel 2.42 GHz Celeron Quad-Core, 4GB 1600MHz DDR3L DIMM on 1 slot , 128GB 2.5" SATA SSD



### Price details:

Price excl. VAT: 1,305.92 €

Eco fees: 0.00 €

VAT 21 %: 274.24 €

### Product details:

Product code: E270176

EAN: 0834619008030

Manufacturer: Elo Touch Solution

**1,580.16 €**

\* VAT included

PDF generated on: 17 December, 2017

PayPoint is an all-in-one mPOS solution that brings simplicity and elegance to the point of sale. Offering sleek, modern style with peripherals built in, the PayPoint platform is retail hardened and built to last with a three-year warranty.

With its single cable design, PayPoint makes setting up the point of sale system fast and easy. Just unbox, plug in, connect, and go.

For retailers and operators, counter space is always at a premium. Ensuring that the counter looks inviting and remains functional is of the utmost importance. With its small footprint and attractive design, PayPoint turns the cash wrap into a beautiful and functional space to allow you to better serve your customers.

PayPoint integrates a receipt printer, cash drawer, MSR, barcode scanner and customer facing display. The flip-for-signature screen encourages shopper engagement and electronic receipt delivery. Bluetooth connectivity and expansion ports allows for the addition of optional peripherals such as a handheld scanner or weight scale.

For traditional payments, leverage the built-in MSR or add Elo's optional NFC reader for contactless payments and proximity marketing. For EMV support, pair with your preferred EMV reader via USB or Bluetooth to provide your customers with a full-function, mobile point of sale experience that supports highly secure EMV transactions.

Whether working with one of Elo's strategic point of sale software partners or deploying your own application, you can easily add the mPOS functionality you need to run your business.

### Main specifications:

#### Display

Display diagonal:	13.3 "
Display resolution:	1920 x 1080 pixels
Touchscreen:	Y
Display brightness:	400 cd/m <sup>2</sup>
Touchscreen technology:	Projected capacitive system
Contrast ratio (typical):	700:1
Viewing angle, horizontal:	170 °
Viewing angle, vertical:	170 °
Response time:	25 ms
Effective viewing area:	293.47 x 165.07 mm
Aspect ratio:	16:9
Display number of colours:	262144 colours

#### Processor

Processor frequency:	2.42 GHz
----------------------	----------

Processor family:	Intel Celeron
Processor model:	J1900
Processor cores:	4
Processor cache:	2 MB
Processor threads:	4
<b>Memory</b>	
Internal memory:	4 GB
Internal memory type:	DDR3L-SDRAM
Maximum internal memory:	4 GB
Number of memory slots:	1
Memory slots type:	SO-DIMM
Memory clock speed:	1600 MHz
<b>Storage</b>	
Total storage capacity:	128 GB
Storage media type:	SSD
Solid-state drive capacity:	128 GB
Solid-state drive interface:	Serial ATA
<b>Graphics</b>	
Graphics adapter manufacturer:	Intel
Graphics adapter:	HD Graphics
<b>Multimedia</b>	
Built-in speaker(s):	Y
Number of speakers:	1
<b>Networking</b>	
Ethernet LAN:	Y
Ethernet LAN data rates:	10,100,1000 Mbit/s
Wi-Fi:	Y
Wi-Fi standards:	IEEE 802.11a,IEEE 802.11ac,IEEE 802.11b,IEEE 802.11g,IEEE 802.11n
<b>Ports &amp; interfaces</b>	
Ethernet LAN (RJ-45) ports:	1
USB 2.0 ports quantity:	3
<b>Design</b>	
Chassis type:	All-in-one
Colour of product:	Black,Grey
<b>Software</b>	
Operating system installed:	Windows 7 Professional
<b>Power</b>	
AC input voltage:	100-240 V
AC input frequency:	50/60 Hz
<b>Operational conditions</b>	
Operating relative humidity (H-H):	20 - 80 %
Operating temperature (T-T):	0 - 35 °C
Storage temperature (T-T):	-20 - 60 °C
Storage relative humidity (H-H):	5 - 95 %
Operating temperature (T-T):	32 - 95 °F
<b>Certificates</b>	
Certification:	UL/cUL, FCC, CE, CB, CCC
<b>Ergonomics</b>	
Mean time between failures (MTBF):	50000 h
<b>Weight &amp; dimensions</b>	
Width (with stand):	345 mm
Depth (with stand):	288 mm
Height (with stand):	212 mm
Weight with stand:	9700 g
<b>Packaging data</b>	
Package width:	450 mm
Package depth:	475 mm
Package height:	340 mm
Package weight:	12100 g

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.