

Elo Touch Solution E353405 POS terminal (E353405)

19.5", 16:9, 1920 x 1080 60Hz, Intel Core i5-4590T 3 GHz, Intel HD Graphics 4600, 128 GB SSD, 4 GB 1600MHz DDR3L, USB 3.0, RJ-45, VGA



Price details:

Price excl. VAT: 1,657.10 €

Eco fees: 0.00 €

VAT 21 %: 347.99 €

Product details:

Product code: E353405

EAN: 0834619009747

Manufacturer: Elo Touch Solution

2,005.09 €

* VAT included

PDF generated on: 18 October, 2017

Overview

The Elo 20-inch X-Series is an innovative, all-in-one, widescreen touchscreen computer that offers a sleek form factor with flexibility, power and endless configuration possibilities. With a compact design, the X-Series is ideal for applications in any retail, self-service or hospitality environment that requires a small footprint POS terminal or kiosk. The highly versatile platform provides maximum configurability and offers you unprecedented freedom of choice in the design of your AiO system.

Configurability.

A wide range of processor, interface, storage, expansion, operating system and mounting options allow you to further tailor the X-Series to meet your needs. The seamless zero-bezel display measures 19.5 inches diagonally is available with 10-touch TouchPro projected capacitive (PCAP) technology offering an edge-to-edge glass design with fast and extremely sensitive responses right out of the box. With processor options that scale from the value-based Intel Celeron J1900 to the high-performance Intel Core i7, the Elo X-Series is one of the most powerful systems in its class.

Versatility.

Every X-Series system is built with transactions in mind, and the wide assortment of peripheral options reflect just that. Whether for staff- or guest-facing applications, easily attach any combination of up to three peripherals, including an EMV reader, a near-field communication (NFC/RFID) reader, mag stripe reader (MSR), barcode reader or fingerprint scanner to the bezel of the X-Series via a universal snap-in connector. To enhance customer engagement at checkout, choose from a wide array of customer facing displays ranging from 2-line to 20-inch. For self-service applications, transform the Elo X-Series from counter-top terminal to kiosk with the optional wall-mount kit.

Reliability.

Rigorously tested and backed by a three-year warranty, the X-Series delivers superior quality and reliability. The splash-proof housing and rugged retail-hardened design easily withstand the adverse conditions associated with most commercial environments. The unique, modular chassis provides easy access to storage and memory for quick, tool-less service.

Other features.

- Small footprint, retail-hardened design
- Field serviceable design allows for quick troubleshoot and fix, no tools needed
- Full range of standard connectivity ports for retail POS, POI and hospitality applications with option to add expansion module if needed
- Removable base with 100mm VESA mounting
- Kensington lock

Main specifications:

Display	
Display diagonal:	19.5 "
Display resolution:	1920 x 1080 pixels
Touchscreen:	Y
Display brightness:	212.5 cd/m ²
Touchscreen technology:	Capacitive
Contrast ratio (typical):	3000:1
Viewing angle, horizontal:	178 °
Viewing angle, vertical:	178 °
Response time:	20 ms
Effective viewing area:	434.88 x 238.68 mm
Aspect ratio:	16:9
Display number of colours:	16.78 million colours
Processor	
Processor frequency:	3 GHz
Processor family:	Intel Core i5
Processor model:	i5-4590T
Processor cores:	4
Processor cache:	6 MB
Processor threads:	4
System bus rate:	5 GT/s
Memory	
Internal memory:	4 GB
Internal memory type:	DDR3L-SDRAM
Maximum internal memory:	16 GB
Number of memory slots:	2
Memory slots type:	SO-DIMM
Memory clock speed:	1600 MHz
Storage	
Total storage capacity:	128 GB
Storage media type:	SSD
Hard drive interface:	Serial ATA
Hard drive size:	2.5 "
Solid-state drive capacity:	128 GB
Graphics	
Graphics adapter manufacturer:	Intel
Graphics adapter:	HD Graphics 4600
Multimedia	
Built-in speaker(s):	Y
Number of speakers:	2
Networking	
Ethernet LAN:	Y
Ethernet LAN data rates:	10,100,1000 Mbit/s
Wi-Fi:	Y
Wi-Fi standards:	IEEE 802.11b,IEEE 802.11g,IEEE 802.11n
Ports & interfaces	
Ethernet LAN (RJ-45) ports:	1
USB 2.0 ports quantity:	2
USB 3.0 (3.1 Gen 1) Type-A ports quantity:	4
VGA (D-Sub) ports quantity:	2
Microphone in:	Y
Serial ports quantity:	1
Design	
Chassis type:	All-in-one
Colour of product:	Black
Performance	
Trusted Platform Module (TPM):	Y
Trusted Platform Module (TPM) version:	1.2
Software	
Operating system installed:	Windows 7 Professional
Power	

AC input voltage:	100-240 V
AC input frequency:	50/60 Hz
Power consumption (typical):	75 W
Operational conditions	
Operating relative humidity (H-H):	20 - 80 %
Operating temperature (T-T):	0 - 35 °C
Storage temperature (T-T):	-20 - 60 °C
Storage relative humidity (H-H):	5 - 95 %
Operating temperature (T-T):	32 - 95 °F
Certificates	
Certification:	UL, cUL, FCC, IC, TUV, CE, CB, VCCI, RCM
Energy Star certified:	Y
Ergonomics	
Wall mountable:	Y
VESA mounting:	Y
VESA mounting interfaces:	100 x 100 mm
Mean time between failures (MTBF):	50000 h
Weight & dimensions	
Width:	492.12 mm
Depth:	65 mm
Height:	320.03 mm
Width (with stand):	492.12 mm
Depth (with stand):	251.7 mm
Height (with stand):	356.9 mm
Weight:	4950 g
Weight with stand:	7530 g
Packaging data	
Package width:	595 mm
Package depth:	440 mm
Package height:	310 mm
Package weight:	11730 g
Security	
Cable lock slot:	Kensington

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.