

Fujitsu PRIMERGY CX420-M server (BDL:1461V135-CLB31)



Price details:

Price excl. VAT: 23,276.88 €

Eco fees: 0.07 €

VAT 21 %: 4,888.16 €

Product details:

Product code: BDL:1461V135-CLB31

EAN:

Manufacturer: Fujitsu

28,165.11 €

* VAT included

PDF generated on: 18 June, 2018



/

Main specifications:

Processor

Processor frequency:	2.3 GHz
Processor family:	Intel Xeon E5
Processor model:	E5-2630
Processor cores:	6
Number of processors installed:	2
Processor cache type:	Smart Cache
Processor cache:	15 MB
System bus rate:	7.2 GT/s
Processor socket:	LGA 2011 (Socket R)
Motherboard chipset:	Intel C600
Processor boost frequency:	2.8 GHz
Processor lithography:	32 nm
Processor threads:	12
Processor operating modes:	64-bit
Stepping:	C2
FSB Parity:	N
Bus type:	QPI
Number of QPI links:	2
Processor codename:	Sandy Bridge EP
Tcase:	77.4 °C
Maximum internal memory supported by processor:	750 GB
Memory types supported by processor:	DDR3-SDRAM
Memory clock speeds supported by processor:	800,1066,1333,1600 MHz
Memory bandwidth supported by processor (max):	42.6 GB/s
Memory channels supported by processor:	Quad
ECC supported by processor:	Y
Execute Disable Bit:	Y
Idle States:	Y
Thermal Monitoring Technologies:	Y
Maximum number of PCI Express lanes:	40
Processor package size:	52.5 mm
Supported instruction sets:	AVX
Scalability:	2S

Embedded options available:	N
Graphics & IMC lithography:	32 nm
Thermal Design Power (TDP):	95 W
CPU multiplier (bus/core ratio):	28
Processor series:	Intel Xeon E5-2600
Conflict Free processor:	N

Memory

Internal memory:	64 GB
Internal memory type:	DDR3-SDRAM
Maximum internal memory:	256 GB
Memory clock speed:	1600 MHz

Storage

Total storage capacity:	1000 GB
Number of hard drives installed:	2
Hard drive size:	2.5 "
Hard drive interface:	Serial ATA
RAID support:	Y
Maximum storage capacity:	4.8 TB
Hard drive speed:	7200 RPM
Hard drive capacity:	500 GB
RAID levels:	0,1
Drive device, transfer rate:	6000 MB/s

Networking

Ethernet LAN:	Y
Cabling technology:	10/100/1000Base-T(X)
Ethernet interface type:	Fast Ethernet,Gigabit Ethernet

Ports & interfaces

USB 2.0 ports quantity:	2
VGA (D-Sub) ports quantity:	1
Ethernet LAN (RJ-45) ports:	7

Expansion slots

PCI Express slots version:	3.0
----------------------------	-----

Design

Chassis type:	Rack (2U)
---------------	-----------

Performance

Operating system installed:	Windows Server 2012 Datacenter
Compatible operating systems:	Windows Server 2012 R2 Datacenter
Integrated BMC with IPMI:	Y

Processor special features

CPU configuration (max):	2
Intel Rapid Storage Technology:	N
Enhanced Intel SpeedStep Technology:	Y
Intel® Identity Protection Technology (Intel® IPT):	N
Intel® Wireless Display (Intel® WiDi):	N
Intel Virtualization Technology for Directed I/O (VT-d):	Y
Intel® Anti-Theft Technology (Intel® AT):	N
Intel® Hyper Threading Technology (Intel® HT Technology):	Y
Intel® My WiFi Technology (Intel® MWT):	N
Intel® Turbo Boost Technology:	Y
Intel® vPro® Technology:	Y
Intel® Quick Sync Video Technology:	N
Intel® InTru® 3D Technology:	N
Intel® Clear Video HD Technology (Intel® CVT HD):	N
Intel® Insider® Technology:	N
Intel Flex Memory Access:	Y
Intel® Smart Cache:	Y
Intel® AES New Instructions (Intel® AES-NI):	Y
Intel Trusted Execution Technology:	Y
Intel Enhanced Halt State:	Y
Intel VT-x with Extended Page Tables (EPT):	Y
Intel Demand Based Switching:	Y
Intel Clear Video Technology:	N
Intel® Clear Video Technology for Mobile Internet Devices (Intel CVT for MID):	N

Intel 64:	Y
Intel Identity Protection Technology version:	0.00
Intel Virtualization Technology (VT-x):	Y
Intel Dual Display Capable Technology:	N
Intel FDI Technology:	N
Intel Fast Memory Access:	N
Processor ARK ID:	64593

Power

Power supply:	1200 W
---------------	--------

Operational conditions

Operating temperature (T-T):	10 - 35 °C
Operating relative humidity (H-H):	10 - 85 %

Certificates

Certification:	FCC Class A certified, CSA, UL, BSMI CNS 13438 Class A, EN55022, ICES-003, IEC 60950, EN 61000-3-3, EN55024, CB, RoHS, EN 60950-1, KCC, WEEE, EN 50371, BSMI CNS 13436, KN22, KN24, NMB-3 Class A
----------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Weight & dimensions

Width:	447 mm
Depth:	774.7 mm
Height:	87.3 mm
Weight:	38000 g

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.