

HP RP7 Retail System Model 7800 POS terminal (H6T44EA#ABB)

RP7 Retail System Model 7800



Price details:

Price excl. VAT: 1,499.35 €

Eco fees: 0.00 €

VAT 21 %: 314.86 €

Product details:

Product code: H6T44EA#ABB

EAN: 0887758564066

Manufacturer: HP

1,814.21 €

* VAT included

PDF generated on: 13 December, 2017



Get ready for the next-generation all-in-one retail solution from HP. Sleek, stylish, and able to effortlessly integrate into your current environment, the HP RP7 Retail System can be customized for everything you need and nothing you don't.

Impressive everywhere you look

- Enhance your store image with the modern, space-saving HP RP7, which has all the capabilities of a traditional retail solution and a sleek design that effortlessly fits into retail and hospitality environments.
- Use it on a counter or mounted on a wall (mounting hardware sold separately); the unique dual-hinge base supports adjustable tilt and height for maximum comfort.
- Sleek, flush-bezel edges make this an appealing self-service kiosk that will attract attention and that your employees can't wait to use.
- Connection points on all four sides of the display let you customize the exact combination of stylish peripherals (MSR, fingerprint reader or webcam/sold separately) that you need.

Performance you can trust

- Quad-core 2nd Generation Intel® Core processors with Intel® vPro Technology (select configurations) deliver hardware-based remote management technologies and a stable, secure, and reliable IT infrastructure.
- Select a 38,1 cm (15") or 43,2 cm (17") diagonal display, and then customize it with intuitive and familiar projected capacitive touch technology or the flexible navigation features of resistive touchscreen.
- Add a sharp customer-facing display. The HP RP7 26,4 cm (10.4") CFD Display (B0T22AV) is perfect for additional advertising and promotional opportunities. The HP RP7 VFD Customer Display (B0T26AV) offers easy-to-read price and product information.

Substance beyond style

- The HP RP7 is retail-hardened for use in ambient environments up to 40°C. The steel chassis, on-board monitoring and alerts, and environmental and shock testing stand up to the long term wear and tear of retail environments.
- The extended product lifecycle helps ensure consistency in your install base, and the three-year limited warranty on the entire solution gives you peace of mind about your investment.

Main specifications:

Display

Display diagonal:	15 "
Display resolution:	1024 x 768 pixels
Touchscreen:	Y
Touchscreen technology:	Capacitive

Processor

Processor frequency:	2.9 GHz
Processor family:	Intel Pentium
Processor model:	G850

Processor cores:	2
Processor cache:	3 MB
Processor threads:	2
System bus rate:	5 GT/s
Motherboard chipset:	Intel Q67 Express
Memory	
Internal memory:	4 GB
Internal memory type:	DDR3-SDRAM
Maximum internal memory:	16 GB
Number of memory slots:	2
Memory slots type:	SO-DIMM
Storage	
Total storage capacity:	320 GB
Storage media type:	HDD
Hard drive capacity:	320 GB
Hard drive interface:	Serial ATA
Hard drive speed:	7200 RPM
Graphics	
Graphics adapter manufacturer:	Intel
Graphics adapter:	HD Graphics
Multimedia	
Built-in speaker(s):	Y
Networking	
Ethernet LAN:	Y
Ethernet LAN data rates:	10,100,1000 Mbit/s
Wi-Fi:	Y
Wi-Fi standards:	802.11a,802.11g,802.11n
Ports & interfaces	
Ethernet LAN (RJ-45) ports:	1
USB 2.0 ports quantity:	6
DVI port:	Y
Line-in:	Y
Line-out:	Y
Parallel ports quantity:	1
RS-232 ports:	2
PS/2 ports quantity:	1
RJ-12 ports quantity:	1
DC-in jack:	Y
Design	
Number of 2.5" bays:	2
Software	
Operating system installed:	Windows Embedded POSReady 7
Operating system architecture:	32-bit
Power	
Power consumption (typical):	180 W
Certificates	
Energy Star certified:	Y
Weight & dimensions	
Width:	366 mm
Depth:	43 mm
Height:	40 mm
Weight:	6250 g
Security	
Cable lock slot:	Kensington

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.