

# HP RP2 Retail System Model 2030 POS terminal (K1D02EA#ABH)

Intel Pentium J2900 (2.41GHz, 2MB), 35.56 cm (14 ") LED touch (1366 x 768), 4GB (1 x 4GB) DDR3 SDRAM, 128GB SATA SSD, Intel HD Graphics, Windows Embedded 8.1 Industry Pro Retail 64



## Price details:

Price excl. VAT: 1,394.82 €

Eco fees: 0.11 €

VAT 21 %: 292.94 €

## Product details:

Product code: K1D02EA#ABH

EAN:

Manufacturer: HP

PDF generated on: 16 December, 2017



**1,687.87 €**

Product is discontinued. You can not order it anymore.

\* VAT included

Get reliable, robust performance from the HP RP2 Retail System, a stylish, compact, and easily serviceable touchscreen All-in-One (AiO) that's deployable across your business as a customer self-service solution or operator station.

## Main specifications:

### Display

Display diagonal:	14 "
Display resolution:	1366 x 768 pixels
Touchscreen:	Y
Touchscreen technology:	Capacitive
Effective viewing area:	309.4 x 173.95 mm
Aspect ratio:	16:9

### Processor

Processor frequency:	2.41 GHz
Processor family:	Intel Pentium
Processor model:	J2900
Processor cores:	4
Processor cache:	2 MB
Processor front side bus:	2.67 MHz
Processor threads:	4

### Memory

Internal memory:	4 GB
Internal memory type:	DDR3-SDRAM
Maximum internal memory:	8 GB
Number of memory slots:	1
Memory slots type:	SO-DIMM
Memory clock speed:	1333 MHz

### Storage

Total storage capacity:	128 GB
Storage media type:	SSD
Solid-state drive capacity:	128 GB
Solid-state drive interface:	Serial ATA

### Graphics

Graphics adapter manufacturer:	Intel
Graphics adapter:	HD Graphics
<b>Multimedia</b>	
Built-in speaker(s):	Y
Number of speakers:	2
Audio system:	DTS Studio Sound
<b>Networking</b>	
Ethernet LAN:	Y
Ethernet LAN data rates:	10,100,1000 Mbit/s
<b>Ports &amp; interfaces</b>	
Ethernet LAN (RJ-45) ports:	1
USB 2.0 ports quantity:	3
USB 3.0 (3.1 Gen 1) Type-A ports quantity:	1
DisplayPorts quantity:	1
DisplayPort version:	1.2
Line-in:	Y
Line-out:	Y
<b>Design</b>	
Chassis type:	All-in-one
Colour of product:	Black
<b>Software</b>	
Operating system installed:	Windows Embedded 8.1 Industry
Operating system architecture:	64-bit
<b>Power</b>	
AC input voltage:	100 - 240 V
AC input frequency:	50/60 Hz
Power supply:	180 W
<b>Certificates</b>	
Energy Star certified:	Y
<b>Ergonomics</b>	
VESA mounting:	Y
VESA mounting interfaces:	75 x 75 mm
<b>Weight &amp; dimensions</b>	
Width (with stand):	355.9 mm
Depth (with stand):	225.3 mm
Height (with stand):	366.2 mm
Weight with stand:	6830 g
<b>Security</b>	
Cable lock slot:	Y

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.