

HP RP7 Retail System Model 7800 POS terminal (T0E98EA#ABH)

Intel Core i3-2120 (3.3GHz, 3MB), 38.1 cm (15 ") Projective capacitive touch (1024 x 768), 4GB DDR3 SDRAM, 500GB 7200 rpm SATA, Intel HD Graphics 2000, FreeDOS



Price details:

Price excl. VAT: 1,490.59 €

Eco fees: 0.00 €

VAT 21 %: 313.02 €

Product details:

Product code: T0E98EA#ABH

EAN:

Manufacturer: HP

PDF generated on: 18 October, 2017



1,803.61 €

* VAT included

Get ready for the next-generation all-in-one retail solution from HP. Sleek, stylish, and able to effortlessly integrate into your current environment, the HP RP7 Retail System can be customized for everything you need and nothing you don't.

Impressive everywhere you look

- Enhance your store image with the modern, space-saving HP RP7, which has all the capabilities of a traditional retail solution and a sleek design that effortlessly fits into retail and hospitality environments.
- Use it on a counter or mounted on a wall (mounting hardware sold separately); the unique dual-hinge base supports adjustable tilt and height for maximum comfort.
- Sleek, flush-bezel edges make this an appealing self-service kiosk that will attract attention and that your employees can't wait to use.
- Connection points on all four sides of the display let you customize the exact combination of stylish peripherals (MSR, fingerprint reader or webcam/sold separately) that you need.

Performance you can trust

- Quad-core 2nd Generation Intel® Core processors with Intel® vPro Technology (select configurations) deliver hardware-based remote management technologies and a stable, secure, and reliable IT infrastructure.
- Select a 38,1 cm (15") or 43,2 cm (17") diagonal display, and then customize it with intuitive and familiar projected capacitive touch technology or the flexible navigation features of resistive touchscreen.
- Add a sharp customer-facing display. The HP RP7 26,4 cm (10.4") CFD Display (B0T22AV) is perfect for additional advertising and promotional opportunities. The HP RP7 VFD Customer Display (B0T26AV) offers easy-to-read price and product information.

Substance beyond style

- The HP RP7 is retail-hardened for use in ambient environments up to 40°C. The steel chassis, on-board monitoring and alerts, and environmental and shock testing stand up to the long term wear and tear of retail environments.
- The extended product lifecycle helps ensure consistency in your install base, and the three-year limited warranty on the entire solution gives you peace of mind about your investment.

Main specifications:

Display

| | |
|-------------------------|-----------------------------|
| Display diagonal: | 15 " |
| Display resolution: | 1024 x 768 pixels |
| Touchscreen: | Y |
| Touchscreen technology: | Projected capacitive system |

Processor

| | |
|----------------------|---------------|
| Processor frequency: | 3.3 GHz |
| Processor family: | Intel Core i3 |

| | |
|----------------------|-------------------|
| Processor model: | i3-2120 |
| Processor cores: | 2 |
| Processor cache: | 3 MB |
| Processor threads: | 4 |
| System bus rate: | 5 GT/s |
| Motherboard chipset: | Intel Q67 Express |

Memory

| | |
|--------------------------|------------|
| Internal memory: | 4 GB |
| Internal memory type: | DDR3-SDRAM |
| Maximum internal memory: | 16 GB |
| Number of memory slots: | 2 |
| Memory slots type: | SO-DIMM |
| Memory clock speed: | 1600 MHz |

Storage

| | |
|-------------------------|------------|
| Total storage capacity: | 500 GB |
| Storage media type: | HDD |
| Hard drive capacity: | 500 GB |
| Hard drive interface: | Serial ATA |
| Hard drive speed: | 7200 RPM |

Graphics

| | |
|--------------------------------|------------------|
| Graphics adapter manufacturer: | Intel |
| Graphics adapter: | HD Graphics 2000 |

Multimedia

| | |
|----------------------|----|
| Built-in speaker(s): | Y |
| Number of speakers: | 2 |
| Audio system: | HD |

Networking

| | |
|--------------------------|--------------------|
| Ethernet LAN: | Y |
| Ethernet LAN data rates: | 10,100,1000 Mbit/s |

Ports & interfaces

| | |
|-----------------------------|---|
| Ethernet LAN (RJ-45) ports: | 1 |
| USB 2.0 ports quantity: | 6 |
| Parallel ports quantity: | 1 |
| RS-232 ports: | 2 |
| PS/2 ports quantity: | 1 |
| RJ-12 ports quantity: | 1 |
| DC-in jack: | Y |

Design

| | |
|----------------------|------------|
| Chassis type: | All-in-one |
| Number of 2.5" bays: | 2 |
| Colour of product: | Black |

Software

| | |
|-----------------------------|---------|
| Operating system installed: | FreeDOS |
|-----------------------------|---------|

Power

| | |
|------------------------------|-------|
| Power consumption (typical): | 180 W |
|------------------------------|-------|

Operational conditions

| | |
|------------------------------------|------------|
| Operating relative humidity (H-H): | 20 - 85 % |
| Operating temperature (T-T): | 10 - 40 °C |

Certificates

| | |
|------------------------|---|
| Energy Star certified: | Y |
|------------------------|---|

Weight & dimensions

| | |
|----------------------|--------|
| Width (with stand): | 366 mm |
| Depth (with stand): | 43 mm |
| Height (with stand): | 40 mm |
| Weight: | 6250 g |

Security

| | |
|------------------|------------|
| Cable lock slot: | Kensington |
|------------------|------------|

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.