

Hewlett Packard Enterprise ProLiant BL460c Gen9 server (727029-B21)

Intel Xeon E5-2650 v3 (2.3GHz, 25MB), 32GB (2 x 16GB) RDIMM, Smart Array P244br, Blade



Price details:

Price excl. VAT: 4,397.99 €

Eco fees: 0.04 €

VAT 21 %: 923.59 €

Product details:

Product code: 727029-B21

EAN: 0887758383100

Manufacturer: Hewlett Packard Enterprise

5,321.62 €

* VAT included

PDF generated on: 18 June, 2018



Are you looking for the right server blade to be your data center workhorse for your demanding core IT and virtualization workloads? Designed for a wide range of configuration and deployment options, the HP ProLiant BL460c Gen9 Server Blade provides the flexibility to optimize your core IT applications with right-sized storage for the right workload for a lower TCO. All of this is managed by HP OneView, 1 the converged management platform that accelerates IT service delivery and boosts business performance. The BL460c Gen9 Server Blade uses Intel® Xeon® E5-2600 v3 processors with up to 70% performance 2 gain over the previous generation, plus enhanced HP DDR4 SmartMemory offering up to 33% performance 3 increase.

Flexible storage controller options additional support includes an optional 12 Gb/s SAS controller, 20 Gb FlexibleLOM NICs, and USB 3.0 on the internal connector.

Features

Superior Value Across Different Workloads

- The HP ProLiant BL460c Gen9 Server Blade delivers the right performance, scalability, and economics for the converged data center in the new era of compute at the lowest cost, fastest time to value with latest innovations.
- Provides the flexibility to optimize your core IT applications, with right-sized storage for the right workload lowering TCO, all managed by HP OneView the converged management platform that accelerates IT service delivery and boosts business performance.

Increased Performance in the Data Center

- The HP ProLiant BL460c Gen9 Server Blade delivers up to 70% performance increases with Intel® Xeon® E5-2600 v3 processors.
- HP DDR4 SmartMemory at 2133 MHz (up to 512 GB): +14% - 33% throughput compared to competition and 35% lower power consumption than 1.5v DDR3 at the same bin speed.
- Optional HP Smart Array P244br storage controller with 1 GB Flash-Write Back Cache (FWBC) DDR3 at 1866 MHz improves storage performance for demanding workloads.

More Versatile Than Ever Before

- The HP ProLiant BL460c Gen9 Server Blade delivers a flexible embedded storage controller options (HP Smart Array P244br, HP H244br Smart Host Bus Adapter, or the HP Dynamic Smart Array B140i Controller) for increased deployment flexibility.
- Every BL460c Gen9 Server Blade includes USB 3.0, future optional dual Micro-SD, and future optional M.2 support for configuration variety of system boot options at the best price.
- Both Unified Extensible Firmware Interface (UEFI) and Legacy BIOS modes available for increased configuration and deployment versatility.

Transforming Business Economics by Accelerating Service Delivery

- HP OneView provides the Power of One-a single comprehensive view of the data center, managing hardware, software, firmware, and drivers.
- HP Integrated Lights-out (iLO) software features server lifecycle management advancements including iLO Federation, which remotely manages groups of servers at scale with built-in rapid discovery of all iLOs, group configurations, group

health status, and ability to determine iLO licenses.

Main specifications:

Processor

| | |
|---|-----------------------|
| Processor frequency: | 2.3 GHz |
| Processor family: | Intel Xeon E5 v3 |
| Processor model: | E5-2650V3 |
| Processor cores: | 10 |
| Number of processors installed: | 1 |
| Processor cache type: | Smart Cache |
| Processor cache: | 25 MB |
| System bus rate: | 9.6 GT/s |
| Maximum number of SMP processors: | 2 |
| Processor socket: | LGA 2011-v3 |
| Motherboard chipset: | Intel C610 |
| Processor boost frequency: | 3 GHz |
| Processor lithography: | 22 nm |
| Processor threads: | 20 |
| Processor operating modes: | 64-bit |
| Stepping: | M1 |
| FSB Parity: | N |
| Bus type: | QPI |
| Number of QPI links: | 2 |
| Processor codename: | Haswell |
| Tcase: | 78.9 °C |
| Maximum internal memory supported by processor: | 368 GB |
| Memory types supported by processor: | DDR4-SDRAM |
| Memory clock speeds supported by processor: | 1600,1866,2133 MHz |
| Memory bandwidth supported by processor (max): | 68 GB/s |
| Memory channels supported by processor: | Quad |
| ECC supported by processor: | Y |
| Execute Disable Bit: | Y |
| Idle States: | Y |
| Thermal Monitoring Technologies: | Y |
| Maximum number of PCI Express lanes: | 40 |
| PCI Express configurations: | x4, x8, x16 |
| Processor package size: | 52.5 mm |
| Supported instruction sets: | AVX 2.0 |
| Processor code: | SR1YA |
| Scalability: | 2S |
| Physical Address Extension (PAE): | 46 bit |
| Embedded options available: | N |
| Thermal Design Power (TDP): | 105 W |
| Processor series: | Intel Xeon E5-2600 v3 |
| Conflict Free processor: | N |

Memory

| | |
|-------------------------------|------------|
| Internal memory: | 32 GB |
| Internal memory type: | DDR4-SDRAM |
| Maximum internal memory: | 512 GB |
| Memory slots: | 16 DIMM |
| Memory clock speed: | 2133 MHz |
| ECC: | Y |
| Memory layout (slots x size): | 2 x 16 GB |

Storage

| | |
|----------------------------------|---------------------------------------|
| Hard drive size: | 2.5 " |
| Hard drive interface: | Serial ATA,Serial Attached SCSI (SAS) |
| RAID support: | Y |
| Maximum storage capacity: | 4 TB |
| RAID levels: | 0,1 |
| Hot-Plug support: | Y |
| Number of hard drives supported: | 2 |

Networking

| | |
|-------------------------------|--|
| Ethernet LAN: | Y |
| Ethernet interface type: | 10 Gigabit |
| Ports & interfaces | |
| Ethernet LAN (RJ-45) ports: | 2 |
| Expansion slots | |
| PCI Express slots version: | 3.0 |
| Design | |
| Chassis type: | Blade |
| Optical drive type: | N |
| Performance | |
| Operating system installed: | N |
| Compatible operating systems: | Microsoft Windows ServerRed Hat Enterprise Linux (RHEL)SUSE Linux Enterprise Server (SLES)Canonical UbuntuOracle SolarisVMwareCitrix XenServer |

Processor special features

| | |
|--|-------|
| CPU configuration (max): | 2 |
| Intel Rapid Storage Technology: | N |
| Enhanced Intel SpeedStep Technology: | Y |
| Intel® Identity Protection Technology (Intel® IPT): | N |
| Intel® Wireless Display (Intel® WiDi): | N |
| Intel Virtualization Technology for Directed I/O (VT-d): | Y |
| Intel® Anti-Theft Technology (Intel® AT): | N |
| Intel® Hyper Threading Technology (Intel® HTT): | Y |
| Intel® My WiFi Technology (Intel® MWT): | N |
| Intel® Turbo Boost Technology: | 2.0 |
| Intel® vPro® Technology: | Y |
| Intel® Quick Sync Video Technology: | N |
| Intel® InTru® 3D Technology: | N |
| Intel® Clear Video HD Technology (Intel® CVT HD): | N |
| Intel® Insider®: | N |
| Intel Flex Memory Access: | N |
| Intel® Smart Cache: | Y |
| Intel® AES New Instructions (Intel® AES-NI): | Y |
| Intel Trusted Execution Technology: | Y |
| Intel Enhanced Halt State: | Y |
| Intel VT-x with Extended Page Tables (EPT): | Y |
| Intel Demand Based Switching: | Y |
| Intel® Secure Key: | Y |
| Intel TSX-NI: | N |
| Intel Clear Video Technology: | N |
| Intel® Clear Video Technology for Mobile Internet Devices (Intel CVT for MID): | N |
| Intel 64: | Y |
| Intel Identity Protection Technology version: | 0.00 |
| Intel Secure Key Technology version: | 1.00 |
| Intel Virtualization Technology (VT-x): | Y |
| Intel TSX-NI version: | 0.00 |
| Intel Dual Display Capable Technology: | N |
| Intel FDI Technology: | N |
| Intel Fast Memory Access: | N |
| Processor ARK ID: | 81705 |

Power

| | |
|---------------------------------------|---|
| Redundant power supply (RPS) support: | N |
|---------------------------------------|---|

Certificates

| | |
|------------------------|---|
| Energy Star certified: | Y |
|------------------------|---|

Weight & dimensions

| | |
|---------|----------|
| Width: | 55.4 mm |
| Depth: | 517.6 mm |
| Height: | 180.7 mm |
| Weight: | 6330 g |

Other features

| | |
|--------------------------|--------|
| Graphics adapter: | G200eh |
| Graphics adapter family: | Matrox |

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.