

Hewlett Packard Enterprise ProLiant MicroServer Gen8 server (F9A40A)

Intel Xeon E3-1220L v2 (2.3GHz, 3MB), 8GB (1 x 8GB) DDR3, Smart Array B120i, 200W Non-Hot Plug PS



Price details:

Price excl. VAT: 620.11 €

Eco fees: 0.08 €

VAT 21 %: 130.24 €

Product details:

Product code: F9A40A

EAN: 0888182336809

Manufacturer: Hewlett Packard Enterprise

750.43 €

* VAT included

PDF generated on: 13 December, 2017



Product is discontinued. You can not order it anymore.

The HP ProLiant MicroServer Gen8 is a small, quiet, and stylishly designed server that is ideal as a first server solution for small businesses. With a form factor that is easy to use and service, it helps small businesses drive down their expenses while improving productivity, efficiency, and security.

What's New

- Personalize your MicroServer Gen8 with the new colored bezel kit
- HP RDX options provide disk based protection for your data
- HP PS1810-24G Switch now provides more network ports for larger office environments

Features

Simplified IT Management with Built-in Gen8 Technologies

- HP ProLiant MicroServer Gen8 comes with HP iLO4, providing access to innovations like Intelligent Provisioning for quick and simple installation and setup.
- Instant out-of-box server set up and deployment.
- Embedded remote management technology reduces on-site server administration and travel expenses.
- Continuous, proactive health monitoring ensures faster and more accurate problem resolution.

Hassle-free Serviceability Maximizing Uptime and Productivity

- Tool-less access to hard drives, memory, and PCI slots for simple installation or upgrade.
- Two up-front USB ports allow for easy deployment.
- New iLO Essentials license provides ability to connect media from your client device to your server and receive email alerts regarding server events.

Unique Server Design Ideal for Small Offices

- Personalize your MicroServer with the new Front Bezel Faceplate Kit
- Small, quiet, energy efficient, and can be placed anywhere.
- Stylish blue LED light bar for at-a-glance system health status.
- Stackable managed switch creates clean, elegant look for networking and compute.

Seamless Network Connectivity Extends Benefits of Converged Infrastructure

- Compatible with HP PS1810 Switch Series. Unique chassis design for the 8-port managed switch that enables physical stacking. A 24-port switch is available for larger office environments.
- Common pool of resources and applications results in a higher level of simplicity and flexibility in operations.
- User-friendly interface on HP PS1810 Switch Series allows for consolidated view of servers and switches in the network so workloads can be prioritized.
- Link aggregation allows for faster file transfers and greater data availability.

Main specifications:

Processor

Processor frequency:	2.3 GHz
Processor family:	Intel Xeon E3 v2
Processor model:	E3-1220LV2
Processor cores:	2
Number of processors installed:	1
Processor cache type:	Smart Cache
Processor cache:	3 MB
System bus rate:	5 GT/s
Processor socket:	LGA 1155 (Socket H2)
Motherboard chipset:	Intel C204
Processor boost frequency:	3.5 GHz
Processor lithography:	22 nm
Processor threads:	4
Processor operating modes:	64-bit
Stepping:	L1
FSB Parity:	N
Bus type:	DMI
Processor codename:	Ivy Bridge
Maximum internal memory supported by processor:	32 GB
Memory types supported by processor:	DDR3-SDRAM
Memory clock speeds supported by processor:	1333,1600 MHz
Memory bandwidth supported by processor (max):	25.6 GB/s
Memory channels supported by processor:	Dual
ECC supported by processor:	Y
Execute Disable Bit:	Y
Idle States:	Y
Thermal Monitoring Technologies:	Y
PCI Express configurations:	1x16+1x4,1x8+3x4,2x8+1x4
Processor package size:	37.5 mm
Supported instruction sets:	AVX,SSE4.1,SSE4.2
Processor code:	SR0R6
Embedded options available:	N
Thermal Design Power (TDP):	17 W
CPU multiplier (bus/core ratio):	23
Processor series:	Intel Xeon E3-1200 v2
Conflict Free processor:	N

Memory

Internal memory:	8 GB
Internal memory type:	DDR3-SDRAM
Maximum internal memory:	16 GB
Memory slots:	2 DIMM
Memory clock speed:	1333 MHz
ECC:	Y
Memory layout (slots x size):	1 x 8 GB

Storage

Hard drive size:	3.5 "
Hard drive interface:	Serial ATA
RAID support:	Y
Maximum storage capacity:	16 TB
RAID levels:	0,1,10
Number of hard drives supported:	4

Networking

Ethernet LAN:	Y
Cabling technology:	10/100/1000Base-T(X)
Ethernet interface type:	Gigabit Ethernet

Ports & interfaces

USB 2.0 ports quantity:	4
VGA (D-Sub) ports quantity:	1
Ethernet LAN (RJ-45) ports:	2
USB 3.0 (3.1 Gen 1) Type-A ports quantity:	2

Expansion slots

PCI Express slots version:	3.0
----------------------------	-----

Design

Chassis type:	Ultra Micro Tower
Optical drive type:	N
Performance	
Operating system installed:	N
Compatible operating systems:	Microsoft Windows ServerRed Hat Enterprise Linux (RHEL)SUSE Linux Enterprise Server (SLES)VMware

Processor special features

CPU configuration (max):	1
Intel Rapid Storage Technology:	N
Enhanced Intel SpeedStep Technology:	Y
Intel® Identity Protection Technology (Intel® IPT):	N
Intel® Wireless Display (Intel® WiDi):	N
Intel Virtualization Technology for Directed I/O (VT-d):	Y
Intel® Anti-Theft Technology (Intel® AT):	N
Intel® Hyper Threading Technology (Intel® HT Technology):	Y
Intel® My WiFi Technology (Intel® MWT):	N
Intel® Smart Response Technology:	N
Intel® Turbo Boost Technology:	2.0
Intel® vPro® Technology:	Y
Intel® Quick Sync Video Technology:	N
Intel® InTru® 3D Technology:	N
Intel® Clear Video HD Technology (Intel® CVT HD):	N
Intel® Insider®:	N
Intel Flex Memory Access:	Y
Intel® Smart Cache:	Y
Intel® AES New Instructions (Intel® AES-NI):	Y
Intel Trusted Execution Technology:	Y
Intel Enhanced Halt State:	N
Intel VT-x with Extended Page Tables (EPT):	Y
Intel Demand Based Switching:	Y
Intel® Small Business Advantage (Intel® SBA):	N
Intel Clear Video Technology:	N
Intel® Clear Video Technology for Mobile Internet Devices (Intel CVT for MID):	N
Intel 64:	Y
Intel Identity Protection Technology version:	1.00
Intel Virtualization Technology (VT-x):	Y
Intel TSX-NI version:	0.00
Intel Dual Display Capable Technology:	N
Intel FDI Technology:	N
Intel Fast Memory Access:	Y
Processor ARK ID:	65735

Power

Redundant power supply (RPS) support:	N
Power supply:	200 W
Number of main power supplies:	1

Weight & dimensions

Width:	232.4 mm
Depth:	230 mm
Height:	245 mm
Weight:	6800 g

Technical details

Product type:	Ultra Micro Tower
---------------	-------------------

Other features

Graphics adapter:	G200
Form factor:	Ultra Micro Tower
Graphics adapter family:	Matrox

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.