

# Hewlett Packard Enterprise ProLiant DL380 Gen9 server (752687-B21)

Intel Xeon E5-2620 v3 (2.4GHz, 15MB), 16GB (1 x 16GB) RDIMM, 8 SFF HDD, Dynamic Smart Array B140i & Smart Array P440ar/2GB FBWC, 500W PS



## Price details:

Price excl. VAT: 3,491.03 €

Eco fees: 0.08 €

VAT 21 %: 733.13 €

## Product details:

Product code: 752687-B21

EAN: 0888182442630

Manufacturer: Hewlett Packard Enterprise

**4,224.24 €**

\* VAT included

PDF generated on: 23 October, 2017



What is your server bottleneck...storage, processing, expansion? The world's best-selling server just got better. The HP ProLiant DL380 Gen9 Server delivers the latest performance and expandability in the HP 2P rack portfolio.

Reliability, serviceability and near continuous availability, backed by a comprehensive warranty, making it ideal for any server environment. Deploy the data center standard. Designed to reduce costs and complexity, leveraging Intel's latest E5-2600 v3 processors with up to 70% performance gain, plus the latest HP DDR4 SmartMemory offering up to 14% [3] performance increase.

Additional support for 12 Gb/s SAS, 10GbE NIC with a broad range of graphics and compute options. Manage the DL380 Gen9 Server in any IT environments by automating the most essential server lifecycle management tasks: deploy, update, monitor, and maintain with ease.

Run everything from the most basic to mission critical applications, and can be deployed with confidence.

## Features

Flexible Design Makes Your Investment "Future Proof" So It Can Grow as Your Business Needs Expand

- The HP ProLiant DL380 Gen9 Server has a flexible redesigned chassis, including new HP Universal Media Bay configuration options with 8 to 24 Small Form Factor (SFF) and 4 or 12 Large Form Factor (LFF) drive options; with additional rear drive support for expandability and investment protection.
- The redesigned HP Flexible Smart Array and HP Smart SAS HBA Controllers allow you the flexibility to choose the optimal 12 Gb/s controller most suited to your environment. In conjunction with the embedded SATA HP Dynamic Smart Array B140i Controller for boot, data and media needs.
- You have a choice of embedded 4x1GbE, HP FlexibleLOM or PCIe standup 1GbE or 10GbE Adapters provide you flexibility of networking bandwidth and fabric so you can adapt and grow to changing business needs.

World-class Performance and Industry-leading Energy Efficiency

- The HP ProLiant DL380 Gen9 Server supports industry standard Intel E5-2600v3 processors with up to 18 cores, 12G SAS and HP DDR4 Smart Memory.
- High efficiency redundant HP Flexible Slot Power Supplies provide up to 94% efficiency (Platinum Plus) and support for the HP Power Discovery Services offering.
- ENERGY STAR® qualified server configurations illustrate a continued commitment to helping customers conserve energy and save money.
- Improved ambient temperature standard with ASHRAE A3 and A4 4 helps you reduce cooling costs.
- Enhanced performance with active and passive, double-wide GPU support for workload acceleration.

Agile Infrastructure Management for Accelerating IT Service Delivery

- With HP DL380 Server, HP OneView provides converged management for automation simplicity across servers, storage and networking.
- Online personalized dashboard for converged infrastructure health monitoring and support management with HP Insight Online.
- Configure in Unified Extensible Firmware Interface (UEFI) boot mode, provision local and remote with Intelligent

## Provisioning and Scripting Toolkits.

- Embedded management to deploy, monitor and support your server remotely, out of band with HP iLO.
  - Optimize firmware and driver updates and reduce downtime with HP Smart Update, consisting of HP SUM and HP SPP.
- 

## Main specifications:

### Processor

Processor frequency:	2.4 GHz
Processor family:	Intel Xeon E5 v3
Processor model:	E5-2620V3
Processor cores:	6
Number of processors installed:	1
Processor cache type:	Smart Cache
Processor cache:	15 MB
System bus rate:	8 GT/s
Maximum number of SMP processors:	2
Processor socket:	LGA 2011-v3
Motherboard chipset:	Intel C610
Processor boost frequency:	3.2 GHz
Processor lithography:	22 nm
Processor threads:	12
Processor operating modes:	64-bit
Stepping:	R2
FSB Parity:	N
Bus type:	QPI
Number of QPI links:	2
Processor codename:	Haswell
Tcase:	72.6 °C
Maximum internal memory supported by processor:	66 GB
Memory types supported by processor:	DDR4-SDRAM
Memory clock speeds supported by processor:	1600,1866 MHz
Memory bandwidth supported by processor (max):	59 GB/s
Memory channels supported by processor:	Quad
ECC supported by processor:	Y
Execute Disable Bit:	Y
Idle States:	Y
Thermal Monitoring Technologies:	Y
Maximum number of PCI Express lanes:	40
PCI Express configurations:	x4, x8, x16
Processor package size:	52.5 mm
Supported instruction sets:	AVX
Processor code:	SR207
Scalability:	2S
Physical Address Extension (PAE):	Y
Physical Address Extension (PAE):	46 bit
Embedded options available:	Y
Thermal Design Power (TDP):	85 W
Processor series:	Intel Xeon E5-2600 v3
Conflict Free processor:	N

### Memory

Internal memory:	16 GB
Internal memory type:	DDR4-SDRAM
Maximum internal memory:	384 GB
Memory slots:	24
Memory clock speed:	2133 MHz
ECC:	Y
Memory layout (slots x size):	1 x 16 GB

### Storage

Hard drive size:	2.5 "
Hard drive interface:	Serial ATA,Serial Attached SCSI (SAS)
RAID support:	Y
Maximum storage capacity:	52 TB

Number of hard drives supported:	8
<b>Networking</b>	
Ethernet LAN:	Y
LAN controller:	HP 331i
Cabling technology:	10/100/1000Base-T(X)
Ethernet interface type:	Gigabit Ethernet
<b>Ports &amp; interfaces</b>	
VGA (D-Sub) ports quantity:	2
Ethernet LAN (RJ-45) ports:	4
USB 3.0 (3.1 Gen 1) Type-A ports quantity:	3
<b>Expansion slots</b>	
PCI Express slots version:	3.0
<b>Design</b>	
Chassis type:	Rack (2U)
Optical drive type:	N
<b>Performance</b>	
Operating system installed:	N
Compatible operating systems:	Microsoft Windows Server Canonical Ubuntu Red Hat Enterprise Linux (RHEL) SUSE Linux Enterprise Server (SLES) Oracle Solaris VMware Citrix XenServer
<b>Processor special features</b>	
CPU configuration (max):	2
Intel Rapid Storage Technology:	N
Enhanced Intel SpeedStep Technology:	Y
Intel® Identity Protection Technology (Intel® IPT):	N
Intel® Wireless Display (Intel® WiDi):	N
Intel Virtualization Technology for Directed I/O (VT-d):	Y
Intel® Anti-Theft Technology (Intel® AT):	N
Intel® Hyper Threading Technology (Intel® HT Technology):	Y
Intel® My WiFi Technology (Intel® MWT):	N
Intel® Turbo Boost Technology:	2.0
Intel® vPro® Technology:	Y
Intel® Quick Sync Video Technology:	N
Intel® InTru® 3D Technology:	N
Intel® Clear Video HD Technology (Intel® CVT HD):	N
Intel® Insider®:	N
Intel Flex Memory Access:	N
Intel® Smart Cache:	Y
Intel® AES New Instructions (Intel® AES-NI):	Y
Intel Trusted Execution Technology:	Y
Intel Enhanced Halt State:	Y
Intel VT-x with Extended Page Tables (EPT):	Y
Intel Demand Based Switching:	Y
Intel® Secure Key:	Y
Intel TSX-NI:	N
Intel® OS Guard:	Y
Intel Clear Video Technology:	N
Intel® Clear Video Technology for Mobile Internet Devices (Intel CVT for MID):	N
Intel 64:	Y
Intel Identity Protection Technology version:	0.00
Intel Secure Key Technology version:	1.00
Intel Virtualization Technology (VT-x):	Y
Intel TSX-NI version:	0.00
Intel Dual Display Capable Technology:	N
Intel FDI Technology:	N
Intel Fast Memory Access:	N
Processor ARK ID:	83352
<b>Power</b>	
Redundant power supply (RPS) support:	Y
Power supply:	500 W
Number of redundant power supplies supported:	2
Number of redundant power supplies installed:	1
<b>Certificates</b>	

Energy Star certified:	N
Weight & dimensions	
Width:	445.4 mm
Depth:	730.2 mm
Height:	87.3 mm
Weight:	14790 g
Other features	
Graphics adapter:	G200eH2
Graphics adapter family:	Matrox

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.