

Hewlett Packard Enterprise ProLiant m700 server (760133-B21)

ProLiant m700 (4) 4P X2150 CPU 4x8GB RAM Configure-to-order Server Cartridge



Price details:

Price excl. VAT: 1,101.34 €

Eco fees: 0.00 €

VAT 21 %: 231.28 €

Product details:

Product code: 760133-B21

EAN: 0888182759868

Manufacturer: Hewlett Packard Enterprise

1,332.62 €

* VAT included

PDF generated on: 23 October, 2017



HP Moonshot System with the HP ProLiant m700 server cartridge was created for cost-effective Hosted Desktop Infrastructure (HDI), Media Transcoding, and other video processing applications. The ProLiant m700 server cartridge has four AMD X2150 APU System on a Chip (SoC) having up to four x86 cores with integrated Graphics Processing Unit (GPU) and each supporting 8GB of memory.

HP Moonshot System uses an innovative new architecture that results from one simple design tenet: to align purpose-built modules with the right workload to provide optimal results for your environment. Traditional servers rely on dedicated components, including management, networking, storage, power cords and cooling fans in a single chassis. In contrast, the Moonshot system share these chassis components and are capable of supporting 45 cartridges per 4.3U chassis. This gives you the ability to generate greater revenue from a smaller footprint while driving down your operational costs.

HP Moonshot m700 cartridge is the power behind HP ConvergedSystem 100 for Hosted Desktops (751820-B21). All-in-one compute, storage, and networking system that delivers desktops for Citrix XenDesktop non-persistent users. Provide your mainstream users a dedicated PC experience with the business graphics and multimedia performance they need, while boosting TCO by up to 44 percent and lowering power requirements up to 63 percent.

Main specifications:

Processor

Processor frequency:	1.1 GHz
Processor family:	AMD Opteron
Processor model:	X2150
Processor cores:	4
Number of processors installed:	4
Processor cache type:	L2
Processor cache:	2 MB

Memory

Internal memory:	32 GB
Internal memory type:	DDR3-SDRAM
Maximum internal memory:	32 GB
Memory slots:	4 SODIMM
Memory clock speed:	1600 MHz
ECC:	Y
Memory layout (slots x size):	4 x 8 GB

Storage

RAID support:	N
---------------	---

Networking

Ethernet LAN:	Y
Ethernet interface type:	Gigabit Ethernet
Ports & interfaces	
Ethernet LAN (RJ-45) ports:	2
Design	
Chassis type:	Blade
Optical drive type:	N
Performance	
Operating system installed:	N
Compatible operating systems:	Windows 7 Enterprise SP1 Red Hat Enterprise Linux (RHEL) 6.5 & 7.0
Power	
Redundant power supply (RPS) support:	N
Power consumption (typical):	49 W
Weight & dimensions	
Width:	19.8 mm
Depth:	183.7 mm
Height:	167.1 mm
Other features	
Graphics adapter family:	AMD

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.