

Hewlett Packard Enterprise ProLiant ML150 server (776274-031)

Intel Xeon E5-2603 v3 (15M Cache, 1.60 GHz), 4GB RDIMM, LFF SATA, 550W, 5U



Price details:

Price excl. VAT: 1,244.98 €

Eco fees: 0.00 €

VAT 21 %: 261.45 €

Product details:

Product code: 776274-031

EAN: 0888793112564

Manufacturer: Hewlett Packard Enterprise

1,506.43 €

* VAT included

PDF generated on: 23 October, 2017



Are you searching for a tower server to meet the requirements of your small to medium-sized growing business? The HPE ProLiant ML150 Gen9 Server is a tower server that delivers exceptional value for a business with a limited budget with a 24-inch chassis depth. Providing dual processor sockets, it provides essential performance with the Intel® Xeon® E5-2600 v4 processors.

Built-in innovations that simplify server deployment and management, your business can continually reap these benefits on a daily basis, with expansion options that enable you to expand as needed, delivering increased business value. The HPE ProLiant ML150 Gen9 Server provides efficiency and productivity for both the small to medium organization that is growing.

Features

Performance to Meet Growing SMB Requirements

The HPE ProLiant ML150 Gen9 Server has built-in intelligence, with the right balance of storage, performance, efficiency, manageability and with enough headroom for future growth.

Supports up to two Intel® Xeon® E5-2600 v4 processors with up to 14 cores offering both improved performance and efficiency.

Help prevent data loss and downtime with enhanced error handling while improving workload performance and power efficiency with up to (16) DIMM slots of HPE DDR4 SmartMemory.

Embedded SATA HPE Dynamic Smart Array B140i Controller for boot and data. Choice of HPE Smart Array Controllers for increased performance, data availability and 12 Gb/s SAS technology or HPE Smart HBAs with reliable high-performance SAS connectivity capable of running HBA mode or simple RAID mode.

Increased GPU support (two single wide and one double wide GPU card support) to boost performance in graphic and VDI applications for financial services, education, scientific research and medical imaging.

Efficiency and Expandability to Fit the Needs of Growing, Budget-Conscious Businesses

The HPE ProLiant ML150 Gen9 Server is designed as a dual-socket tower server providing configuration flexibility and expansion options to meet a wide range of different capacities, connectivity, and design requirements.

Flexible expansion capacity with (6) PCIe expansion slots, (8) USB ports, and power supply options.

Compact server with a 24-inch chassis depth; newly designed and saves precious real estate space and is suitable for your growing business within a compact office environment.

Offering expandability with greater capacity with up to (10) Large Form Factor (LFF) disk drives or (16) Small Form Factor (SFF) disk drive options and increased I/O expansion.

Improved ambient temperature standard with ASHRAE A3 1 helps customer reduce cooling expense.

Infrastructure Management for Essential Server Administration

The HPE ProLiant ML150 Gen9 Server continues to provide a simplified server deployment with tiered management. Businesses continue to reap benefits on a daily basis, while expansion options allow them to grow as needed with HPE Integrated Lights-Out (iLO).

Configure with the Unified Extensible Firmware Interface (UEFI) boot mode, provision both locally and remotely with either the Intelligent Provisioning or Scripting Toolkits.

Online personalized dashboard for Converged Infrastructure (CI) for health monitoring and support management from within HPE Insight Online.

Optimize firmware and driver updates and reduce downtime with Smart Update, consisting of SUM (Smart Update Manager) and SPP (Service Pack for ProLiant).

Enhanced Serviceability Offerings

The HPE ProLiant ML150 Gen9 Server delivers a new style IT that delivers simplicity and agility needed to manage business investments.

Proven HPE ProLiant reliability, exceptional worldwide service 24x7, unparalleled remote management tools that reduce IT travel costs, while increasing time-to-resolution.

Worldwide availability, service and support with a complete range of service offerings from installation to extended support.

Main specifications:

Processor

Processor frequency:	1.6 GHz
Processor family:	Intel Xeon E5 v3
Processor model:	E5-2603V3
Processor cores:	6
Processor cache type:	Smart Cache
Processor cache:	15 MB
System bus rate:	6.4 GT/s
Processor socket:	LGA 2011-v3
Processor lithography:	22 nm
Processor threads:	6
Processor operating modes:	64-bit
Stepping:	R2
FSB Parity:	N
Bus type:	QPI
Number of QPI links:	2
Processor codename:	Haswell
Tcase:	72.8 °C
Maximum internal memory supported by processor:	768 GB
Memory types supported by processor:	DDR4-SDRAM
Memory clock speeds supported by processor:	1600 MHz
Memory bandwidth supported by processor (max):	51 GB/s
Memory channels supported by processor:	Quad
ECC supported by processor:	Y
Execute Disable Bit:	Y
Idle States:	Y
Thermal Monitoring Technologies:	Y
Maximum number of PCI Express lanes:	40
PCI Express configurations:	x4, x8, x16
Processor package size:	52.5 mm
Supported instruction sets:	AVX 2.0
Scalability:	2S
Physical Address Extension (PAE):	Y
Physical Address Extension (PAE):	46 bit
Embedded options available:	N
Thermal Design Power (TDP):	85 W
Processor series:	Intel Xeon E5-2600 v3
Conflict Free processor:	N

Memory

Internal memory:	4 GB
Internal memory type:	DDR4-SDRAM
Memory slots:	16 DIMM
Memory layout (slots x size):	1 x 4 GB

Storage

Hard drive interface:	Serial ATA
-----------------------	------------

Graphics

On-board graphics adapter:	N
On-board graphics adapter model:	Not available

Expansion slots

PCI Express slots version:	3.0
Design	
Chassis type:	Tower
Optical drive type:	N
Processor special features	
CPU configuration (max):	2
Intel Rapid Storage Technology:	N
Enhanced Intel SpeedStep Technology:	Y
Intel® Identity Protection Technology (Intel® IPT):	N
Intel® Wireless Display (Intel® WiDi):	N
Intel Virtualization Technology for Directed I/O (VT-d):	Y
Intel® Anti-Theft Technology (Intel® AT):	N
Intel® Hyper Threading Technology (Intel® HT Technology):	N
Intel® My WiFi Technology (Intel® MWT):	N
Intel® Turbo Boost Technology:	N
Intel® vPro® Technology:	Y
Intel® Quick Sync Video Technology:	N
Intel® InTru® 3D Technology:	N
Intel® Clear Video HD Technology (Intel® CVT HD):	N
Intel® Insider®:	N
Intel Flex Memory Access:	N
Intel® Smart Cache:	Y
Intel® AES New Instructions (Intel® AES-NI):	Y
Intel Trusted Execution Technology:	Y
Intel Enhanced Halt State:	Y
Intel VT-x with Extended Page Tables (EPT):	Y
Intel Demand Based Switching:	Y
Intel® Secure Key:	Y
Intel TSX-NI:	N
Intel® OS Guard:	Y
Intel Clear Video Technology:	N
Intel® Clear Video Technology for Mobile Internet Devices (Intel CVT for MID):	Y
Intel 64:	Y
Intel Identity Protection Technology version:	0.00
Intel Secure Key Technology version:	1.00
Intel Virtualization Technology (VT-x):	Y
Intel TSX-NI version:	0.00
Intel Dual Display Capable Technology:	N
Intel HD Graphics:	N
Intel FDI Technology:	N
Intel Fast Memory Access:	N
Processor ARK ID:	83349
Power	
Redundant power supply (RPS) support:	N
Power supply:	550 W
Weight & dimensions	
Width:	200 mm
Depth:	620 mm
Height:	432.6 mm
Weight:	22230 g

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.