

Hewlett Packard Enterprise ProLiant BL465c Gen8 server (708931-B21)

HP ProLiant BL465c Gen8 6344 2.6GHz 12-core 1P 16GB-R P220i Server



Price details:

Price excl. VAT: 2,769.90 €

Eco fees: 0.00 €

VAT 21 %: 581.68 €

Product details:

Product code: 708931-B21

EAN: 0887111625274

Manufacturer: Hewlett Packard Enterprise

3,351.58 €

* VAT included

PDF generated on: 22 October, 2017



Are you looking to expand your data center with a cost-effective two socket server blade offering exceptional price/performance in a half-height form factor?

The ProLiant BL465c Gen8 Server Blade provides a unique blend of core density combined with a broad memory footprint in a half-height form factor that delivers unparalleled price/performance leadership for virtualization, IT infrastructure, database, and high-performance computing (HPC) environments. With up to 512 cores in a single enclosure and up to 2048 cores in a single rack, these servers provide very dense deployment for your data center.

Innovations in performance, flexibility in networking options, and robust management features make this the ideal 2-socket server blade for midmarket and enterprise data centers.

Redefining the Customer Experience

• The user-inspired design features of the HP ProLiant BL465c Gen8 Server Blade anticipate your needs and virtually eliminate common issues that result in downtime.

Intuitive, Automated System Management Reduces Tedious, Time-Consuming Tasks

• HP Intelligent Provisioning is a single embedded tool for all server set-up and configuration tasks. All of the firmware, drivers, and tools that you need to quickly get your systems online are built into Gen8 servers - no more CDs or DVDs needed.

Improved Application, Storage, and I/O Performance

• HP SmartMemory provides unmatched performance, quality and manageability advantages above industry standard memory, with support for up to 512 GB capacity at 1333 MHz and up to 256 GB at 1600 MHz.

Built for Performance, Efficiency, and Serviceability

• AMD Opteron 6300 Series Processors provide new levels of performance and efficiency over the previous generation.

Main specifications:

Processor

Processor frequency: 2.6 GHz

Processor family:	AMD Opteron
Processor model:	6344
Processor cores:	12
Number of processors installed:	1
Processor cache type:	L3
Processor cache:	16 MB
System bus rate:	6.4 GT/s
Maximum number of SMP processors:	2
Processor socket:	Socket G34
Motherboard southbridge:	AMD SP5100
Motherboard chipset:	AMD SR5690
Memory	
Internal memory:	16 GB
Internal memory type:	DDR3-SDRAM
Maximum internal memory:	512 GB
Memory slots:	16 DIMM
Memory clock speed:	1333 MHz
ECC:	Y
Memory layout (slots x size):	2 x 8 GB
Storage	
Hard drive size:	2.5 "
Hard drive interface:	Serial ATA
RAID support:	Y
Maximum storage capacity:	2.4 TB
RAID levels:	0,1
Number of hard drives supported:	2
Hot-swap:	Y
Networking	
Ethernet LAN:	Y
Ethernet interface type:	10 Gigabit
Ports & interfaces	
Ethernet LAN (RJ-45) ports:	2
Design	
Chassis type:	Blade
Optical drive type:	N
Performance	
Operating system installed:	N
Compatible operating systems:	Microsoft Windows ServerRed Hat Enterprise Linux (RHEL)SUSE Linux Enterprise Server (SLES)Oracle SolarisVMwareCitrix XenServer
Power	
Redundant power supply (RPS) support:	N
Certificates	
Energy Star certified:	N
Weight & dimensions	
Width:	55.4 mm
Depth:	517.6 mm
Height:	180.7 mm
Weight:	7710 g
Other features	
Graphics adapter:	G200
Graphics adapter family:	Matrox

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.